

Revision Date: 04.01.2024 Date of last issue: 07.07.2021 Version 8.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaBond[®]-54 Parquet

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

Additional Labelling

EUH208	Contains 4,4'-methylenediphenyl diisocyanate, m-tolylidene diisocyanate, Hardener LI (Isophoronedialdimine), Hardener LH (1,6-Hexanedialdimine). May produce an allergic reaction.
EUH204	Contains isocyanates. May produce an allergic reaction.
	"As from 24 August 2023 adequate training is required before industrial or pro- fessional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SikaBond[®]-54 Parquet

Print Date 04.01.2024

Revision Date: 04.01.2024 Date of last issue: 07.07.2021 Version 8.0

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

oomponents			
Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Urea,N,N''-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
Hardener LI (Isophoronedial- dimine)	932742-30-8 700-071-4 01-2119880654-28- XXXX	Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 0,5 - < 1
Hardener LH (1,6- Hexanedialdimine)	613222-52-9 479-930-8 01-0000020044-84- XXXX	Eye Dam. 1; H318 Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 0,5 - < 1

SikaBond[®]-54 Parquet

Revision Date: 04.01.2024 Date of last issue: 07.07.2021



Version 8.0

4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	< 0,1
m-tolylidene diisocyanate	26471-62-5 247-722-4 01-2119454791-34- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412 specific concentration limit Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (vapour): 0,107 mg/l	>= 0,025 - < 0,1

For explanation of abbreviations see section 16.

Revision Date: 04.01.2024 Date of last issue: 07.07.2021



Version 8.0

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: No hazards which require special first aid measures.
If inhaled	: Move to fresh air.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.
In case of eye contact	: Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	See Section 11 for more detailed information on health effects and symptoms.
Risks	:	No known significant effects or hazards.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from	the	e substance or mixture
		No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SikaBond®-54 Parquet

Revision Date: 04.01.2024 Date of last issue: 07.07.2021 Version 8.0



SECTION 6: Accidental release measures

6.1 Personal precautions, protect Personal precautions	tive :	equipment and emergency procedures For personal protection see section 8.
6.2 Environmental precautions		
Environmental precautions	:	No special environmental precautions required.
6.3 Methods and material for con	ntair	nment and cleaning up
Methods for cleaning up	:	Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.
6.4 Reference to other sections		
For personal protection see se	ectio	in 8.
SECTION 7: Handling and stor	rag	e
7.1 Precautions for safe handling	3	
Advice on safe handling	:	For personal protection see section 8. No special handling advice required. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	When using do not eat or drink. When using do not smoke.
7.2 Conditions for safe storage, in	inclu	uding any incompatibilities
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
Advice on common storage	:	No special restrictions on storage with other products.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

3.0



Revision Date: 04.01.2024 Date of last issue: 07.07.2021

Version 8.0

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m3 (NCO)	CH SUVA
	es, which are e tional skin reso inhalation by th an S can lead Executive (Occ	ation: Toxic by skin easily absored throu option a substancial ne airways., Sensitiz to very strong allerg cupational Medicine child is not to be exp	ugh the skin, can g higher risk compa zers; Substances gic reactions., Hea and Hygiene Lab	give by addi- ared to only marked with lth and Safety poratory), Harm
		STEL	0,02 mg/m3 (NCO)	CH SUVA
m-tolylidene diisocyanate	26471-62-5	STEL	0,02 mg/m3	CH SUVA
		TWA	0,02 mg/m3	CH SUVA
		TWA	0,02 mg/m3 (NCO)	CH SUVA
	Further inform	ation: Sensitizers; S	Substances marke	d with an S
	can lead to very strong allergic reactions., Health and Safety Ex- ecutive (Occupational Medicine and Hygiene Laboratory)			nd Safety Ex-
				atory)
		STEL	0,02 mg/m3 (NCO)	CH SUVA

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	4,4'- diaminodiphenyl- methane: 10 μg/g creatinine (Urine)	Immediately after exposure or after working hours	CH BAT
		4,4'- diaminodiphenyl- methane: 5 nmol/mmol creati- nine (Urine)	Immediately after exposure or after working hours	CH BAT

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses

SikaBond®-54 Parquet



Revision Date: 04.01.2024
Date of last issue: 07.07.2021

Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
		Butyl rubber/nitrile rubber gloves (> 0,1 mm) Recommended: Butyl rubber/nitrile rubber gloves.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Environmental exposure c	ontr	ols

General advice

: No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste brown
Odour	:	slight
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available

Upper/lower flammability or explosive limits

SikaBond[®]-54 Parquet

Revision Date: 04.01.2024 Date of last issue: 07.07.2021 Version 8.0



Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable
Viscosity		
Viscosity, dynamic	:	ca. 26.000 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
-		
Partition coefficient: n-		No data available
octanol/water	•	
Vapour pressure	:	0,01 hPa
Density	:	ca. 1,3 g/cm3 (20 °C)
	_	
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

Revision Date: 04.01.2024 Date of last issue: 07.07.2021 Version 8.0



SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid :	Avoid moisture.
-----------------------	-----------------

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402
Hardener LI (Isophoronedialdimine):		

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg	
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg	
4,4'-methylenediphenyl diisocyanate:			
4,4'-methylenediphenyl diise	су	anate:	

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h

SikaBond[®]-54 Parquet

Revision Date: 04.01.2024 Date of last issue: 07.07.2021 Print Date 04.01.2024

Version 8.0

Test atmosphere: dust/mist Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

m-tolylidene diisocyanate:

Acute inhalation toxicity

: LC50 (Rat): 0,107 mg/l Exposure time: 4 h Test atmosphere: vapour

> Acute toxicity estimate: 0,107 mg/l Test atmosphere: vapour Method: Calculation method

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

÷

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to

Revision Date: 04.01.2024 Date of last issue: 07.07.2021



Version 8.0

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h

Hardener LI (Isophoronedialdimine):

Toxicity to fish	:	LC50 (Fish): 87,2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): 180,4 mg/l Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Revision Date: 04.01.2024 Date of last issue: 07.07.2021 Version 8.0



12.6 Endocrine disrupting properties

Product:

Assessment	 The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
	-

12.7 Other adverse effects

Product:

Additional ecological infor-	:	There is no data available for this product.
mation		

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland VeVA/LVA	: 08 04 09 [S] waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good

Revision Date: 04.01.2024 Date of last issue: 07.07.2021



Version 8.0

ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors **REACH** Information: All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the folthe market and use of certain dangerous substances, lowing entries should be considered: mixtures and articles (Annex XVII) Number on list 75 4,4'-methylenediphenyl diisocyanate

(Number on list 74, 56) m-tolylidene diisocyanate (Number on list 74) 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (Number on list 52)

SikaBond®-54 Parquet



Revision Date: 04.01.2024 Date of last issue: 07.07.2021	Version 8.0

REACH - Candidate List of Substar Concern for Authorisation (Article 5	, ,	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subjec (Annex XIV)	t to authorisation	:	Not applicable
Regulation (EC) No 1005/2009 on splete the ozone layer	substances that de-	:	Not applicable
Regulation (EU) 2019/1021 on pers tants (recast)	sistent organic pollu-	:	Not applicable
PIC Ordinance, ChemPICO (814.82	2)	:	Not applicable
Chemical Risk Reduction Ordinanc 814.81)	e (ORRChem, SR	:	4,4'-methylenediphenyl diisocyanate
jor-accident hazards involving dang		ient	and of the Council on the control of ma-
	Law on the incentive ta (VOCV)	ix fo	or volatile organic compounds

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

no VOC duties

SECTION 16: Other information

F	ull	text	of	H-Statements
		IC AL	U 1	

H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H319 :	Causes serious eye irritation.
H330 :	Fatal if inhaled.
H332 :	Harmful if inhaled.

Revision Date: 04.01.2024 Date of I



ision Date: 04.01.2024 e of last issue: 07.07.2021	Version 8.0	Print Date 04.01.
H334	May cause allergy or asthma symptoms or b ties if inhaled.	preathing difficul-
H335	May cause respiratory irritation.	
H351	Suspected of causing cancer.	
H373	 May cause damage to organs through prolo exposure if inhaled. 	nged or repeated
H412	Harmful to aquatic life with long lasting effect	ts.
H413	May cause long lasting harmful effects to aq	
Full text of other abbreviation	S	
Acute Tox.	Acute toxicity	
Aquatic Chronic	Long-term (chronic) aquatic hazard	
Carc.	Carcinogenicity	
Eye Dam.	Serious eye damage	
Eye Irrit.	Eye irritation	
Resp. Sens.	Respiratory sensitisation	
Skin Irrit.	Skin irritation	
Skin Sens.	Skin sensitisation	
STOT RE	Specific target organ toxicity - repeated expo	osure
STOT SE	Specific target organ toxicity - single exposu	
CH BAT	Switzerland. List of BAT-values	10
CH SUVA	Switzerland. Limit values at the work place	
CH SUVA / TWA	Time Weighted Average	
CH SUVA / STEL	Short Term Exposure Limit	
ADR	European Agreement concerning the Interna	ational Carriage of
ABR	Dangerous Goods by Road	
CAS	Chemical Abstracts Service	
DNEL	Derived no-effect level	
EC50		
	Half maximal effective concentration	
GHS	Globally Harmonized System	
IATA	International Air Transport Association	
IMDG	International Maritime Code for Dangerous (
LD50	 Median lethal dosis (the amount of a materia once, which causes the death of 50% (one h test animals) 	
LC50	Median lethal concentration (concentrations air that kills 50% of the test animals during the test ani	
MARPOL	period) International Convention for the Prevention	of Pollution from
	Ships, 1973 as modified by the Protocol of 1	
OEL	Occupational Exposure Limit	
PBT	Persistent, bioaccumulative and toxic	
PNEC	Predicted no effect concentration	
REACH	 Regulation (EC) No 1907/2006 of the Europ and of the Council of 18 December 2006 con istration, Evaluation, Authorisation and Rest cols (REACH) octablishing a European Cho 	ncerning the Reg- riction of Chemi-
SVUC	cals (REACH), establishing a European Che	micals Agency
SVHC	Substances of Very High Concern	
vPvB	Very persistent and very bioaccumulative	

Further information

SikaBond®-54 Parquet

Print Date 04.01.2024

Revision Date: 04.01.2024 Date of last issue: 07.07.2021 Version 8.0

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN