

Revision Date: 15.01.2025 Date of last issue: 19.05.2022 Version 3.0

Print Date 15.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor[®]-10 Pronto N Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Acrylate coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

| Company name of supplier | : | Sika Schweiz AG |
|--------------------------|---|------------------|
| | | Tüffenwies 16 |
| | | 8048 Zürich |
| Telephone | : | +41 58 436 40 40 |
| Telefax | : | - |
| E-mail address of person | : | EHS@ch.sika.com |
| responsible for the SDS | | |

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| Flammable liquids, Category 2 | H225: Highly flammable liquid and vapour. |
|---|--|
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Specific target organ toxicity - single ex- posure, Category 3, Respiratory system | H335: May cause respiratory irritation. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Danger

2

Sikafloor®-10 Pronto N Part A



| Revision Date: 15.01.2025 Date of last issue: 19.05.2022 | | Version 3.0 | Print Date 15.01.2025 |
|---|--|--|-----------------------------|
| Hazard statements : | H315 C H317 M | ighly flammable liquid and vapour. auses skin irritation. lay cause an allergic skin reaction. lay cause respiratory irritation. | |
| Precautionary statements : | Prevention: P210 P233 P261 P264 P280 | Keep away from heat, hot surfa open flames and other ignition s smoking. Keep container tightly closed. Avoid breathing mist or vapours Wash skin thoroughly after han Wear protective gloves/ protect eye protection/ face protection. | sources. No s. dling. |
| | Response: P370 + P378 | In case of fire: Use dry sand, dr alcohol-resistant foam to exting | |

Hazardous components which must be listed on the label:

methyl methacrylate tetramethylene dimethacrylate 2-(N-methyl-p-toluidino)ethanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 15.01.2025 Date of last issue: 19.05.2022 Version 3.0

Print Date 15.01.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. | Classification | Concentration |
|---------------------------------|---------------------|----------------------|---------------|
| | EC-No. | | (% w/w) |
| | Registration number | | . , |
| methyl methacrylate | 80-62-6 | Flam. Liq. 2; H225 | >=80 |
| | 201-297-1 | Skin Irrit. 2; H315 | |
| | 01-2119452498-28- | Skin Sens. 1; H317 | |
| | XXXX | STOT SE 3; H335 | |
| | | (Respiratory system) | |
| tetramethylene dimethacrylate | 2082-81-7 | Skin Sens. 1B; H317 | >= 1 - < 2,5 |
| | 218-218-1 | | |
| | 01-2119967415-30- | | |
| | XXXX | | |
| 2-(N-methyl-p-toluidino)ethanol | 2842-44-6 | Eye Irrit. 2; H319 | >= 1 - < 2,5 |
| | 220-638-5 | Skin Sens. 1; H317 | |
| | 01-2120827830-56- | Aquatic Chronic 2; | |
| | XXXX | H411 | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

| General advice | : | Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. |
|-------------------------|---|---|
| If inhaled | : | Move to fresh air. Consult a physician after significant exposure. |
| In case of skin contact | : | Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. |
| In case of eye contact | : | Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. |
| If swallowed | : | Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. |

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Cough

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-10 Pronto N Part A



| Revision Date: 15.01.2025 Date of last issue: 19.05.2022 | Version 3.0 | Print Date 15.01.202 |
|---|--|----------------------|
| | Respiratory disorder Allergic reactions Erythema Dermatitis See Section 11 for more detailed information of and symptoms. | on health effects |
| Risks | : irritant effects sensitising effects | |
| | Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. | |
| 4.3 Indication of any immediate r | nedical attention and special treatment needed | |
| | · Treat symptomatically | |
| | : Treat symptomatically. | |
| SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing | ures | |
| SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing media | ures : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical : Water | |
| SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing media 5.2 Special hazards arising from | ures : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical : Water | 1 |
| SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing media 5.2 Special hazards arising from Hazardous combustion prod- | ures : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical : Water the substance or mixture | ٦ |
| SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing media 5.2 Special hazards arising from Hazardous combustion products | ures : Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical : Water : Water : No hazardous combustion products are known | |

| • | <i>,</i> | • • | | • | <i>y</i> 1 |
|---------------------|----------|------------|------------|---------|--------------------------------------|
| Personal precaution | s : | Use perso | nal protec | tive eq | quipment. |
| | | Remove a | II sources | of igni | ition. |
| | | Deny acce | ess to unp | rotecte | ed persons. |
| | | Beware of | vapours a | accumu | ulating to form explosive concentra- |
| | | tions. Vap | ours can a | accumu | ulate in low areas. |
| | | | | | |

Sikafloor[®]-10 Pronto N Part A



| Revision Date: 15.01.2025 | Version 3.0 | Print Date 15.01.2025 |
|--------------------------------|-------------|-----------------------|
| Date of last issue: 19.05.2022 | | |

6.2 Environmental precautions

| Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains in respective authorities. | nform |
|---|-------|
|---|-------|

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

| Advice on safe handling : | Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products |
|--|--|
| Advice on protection against : fire and explosion | Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges. |
| Hygiene measures : | Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. |
| 7.2 Conditions for safe storage, incl | luding any incompatibilities |
| Requirements for storage : areas and containers | Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikafloor[®]-10 Pronto N Part A

| Revision Date: 15.01.2025 Date of last issue: 19.05.2022 | Version 3.0 | Print Date 15.01.2025 |
|---|--|-----------------------|
| Further information on stor- age stability | : No decomposition if stored and applied | l as directed. |
| 7.3 Specific end use(s) Specific use(s) | : Consult most current local Product Data use. | a Sheet prior to any |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form | Control parame- | Basis * | |
|---------------------|---------------|---|-----------------|-------------|--|
| | | of exposure) | ters * | | |
| methyl methacrylate | 80-62-6 | TWA | 50 ppm | 2009/161/EU | |
| | Further infor | mation: Indicative | | | |
| | | STEL | 100 ppm | 2009/161/EU | |
| | | TWA | 50 ppm | CH SUVA | |
| | | | 210 mg/m3 | | |
| | Further infor | Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des | | | |
| | can lead to v | | | | |
| | Occupationa | | | | |
| | de Sécurité r | | | | |
| | | maladies professionnelles, Harm to the unborn child is not to be | | | |
| | expected wh | expected when the OEL-value is respected | | | |
| | | STEL | 100 ppm | CH SUVA | |
| | | | 420 mg/m3 | | |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

| Eye/face protection | : | Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water |
|---------------------|---|--|
| Hand protection | : | Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. |



| Revision Date: 15.01.2025 Date of last issue: 19.05.2022 | Version 3.0 | Print Date 15.01.2025 |
|---|--|--|
| Skin and body protection : | Protective clothing (e.g. Safety shoes acc. long-sleeved working clothing, long trouser and protective boots are additionaly recom and stirring work. | s). Rubber aprons |
| Respiratory protection : | In case of inadequate ventilation wear resp Respirator selection must be based on kno exposure levels, the hazards of the produc- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10 Ensure adequate ventilation. This can be a exhaust extraction or by general ventilation ods for determining inhalation exposure). T ticular to the mixing / stirring area. In case to keep the concentrations under the occup limits then respiration protection measures | own or anticipated t and the safe work- 0000 ppm Inchieved by local h. (EN 689 - Meth- This applies in par- this is not sufficent pational exposure |
| Environmental exposure cont | rols | |
| General advice | : Prevent product from entering drains. If the product contaminates rivers and lake | s or drains inform |

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Physical state | : | liquid |
|---|-----|-------------------|
| Colour | : | light yellow |
| Odour | : | unpleasant |
| Melting point/ range / Freez- ing point | : | No data available |
| Boiling point/boiling range | : | ca. 100 °C |
| Flammability (solid, gas) | : | No data available |
| Upper/lower flammability or e | -yn | losive limits |
| Upper explosion limit / Up- per flammability limit | • | |
| Lower explosion limit / Lower flammability limit | : | 2,1 %(V) |
| | | |

Sikafloor®-10 Pronto N Part A



| Revision Date: 15.01.2025 Date of last issue: 19.05.2022 | Version 3.0 | Print Date 15.01.2025 |
|---|-----------------------------------|-----------------------|
| Flash point | : ca. 10 °C Method: closed cup | |
| Auto-ignition temperature | : 430 °C | |
| Decomposition temperature | : No data available | |
| рН | : ca. 7 Concentration: 50 % | |
| Viscosity Viscosity, dynamic | : ca. 200 mPa.s (20 °C) | |
| Viscosity, kinematic | : > 20,5 mm2/s (40 °C) | |
| Solubility(ies) Water solubility | : No data available | |
| Partition coefficient: n- octanol/water | : No data available | |
| Vapour pressure | : 40 hPa | |
| Density | : ca. 0,99 g/cm3 (20 °C) | |
| Relative vapour density | : No data available | |
| Particle characteristics | : No data available | |
| | | |

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

Sikafloor®-10 Pronto N Part A



| Revision Date: 15.01.2025 Date of last issue: 19.05.2022 | | Version 3.0 | Print Date 15.01.2025 |
|---|-------|---|-----------------------|
| 10.3 Possibility of hazardous rea | actio | ns | |
| Hazardous reactions | : | Stable under recommended storage conditions. | |
| | | Vapours may form explosive mixture with air. | |
| 10.4 Conditions to avoid | | | |
| Conditions to avoid | : | Heat, flames and sparks. | |
| 10.5 Incompatible materials | | | |
| Materials to avoid | : | No data available | |
| 10.6 Hazardous decomposition | orod | ucts | |
| | : | No hazardous decomposition products are know | 'n. |
| | | | |
| Conditions to avoid 10.5 Incompatible materials Materials to avoid | : | Heat, flames and sparks. No data available ucts | 'n. |

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

| Acute toxicity Not classified due to lack of o <u>Components:</u> methyl methacrylate: | data. | | | | |
|---|--|--|--|--|--|
| Acute oral toxicity | : LD50 Oral (Rat): > 5.000 mg/kg | | | | |
| Acute inhalation toxicity | : LC50 (Rat): 29,8 mg/l Exposure time: 4 h Test atmosphere: vapour | | | | |
| Acute dermal toxicity | : LD50 Dermal (Rabbit): > 5.000 mg/kg | | | | |
| 2-(N-methyl-p-toluidino)eth | nanol: | | | | |
| Acute oral toxicity | : LD50 Oral (Rat): > 2.000 mg/kg | | | | |
| Skin corrosion/irritation Causes skin irritation. | | | | | |
| Serious eye damage/eye irritation Not classified due to lack of data. | | | | | |
| Respiratory or skin sensitisation | | | | | |
| Skin sensitisation May cause an allergic skin re | eaction. | | | | |



Revision Date: 15.01.2025 Date of last issue: 19.05.2022

Version 3.0

Print Date 15.01.2025

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

methyl methacrylate:

| Toxicity to fish | : | NOEC (Danio rerio (zebra fish)): 9,4 mg/l |
|---|---|--|
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 69 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 |
| | | NOEC : 37 mg/l Exposure time: 21 d Method: OECD Test Guideline 202 |
| Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity) | : | NOEC: 37 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) |



Sikafloor®-10 Pronto N Part A

Revision Date: 15.01.2025 Date of last issue: 19.05.2022 Version 3.0

Print Date 15.01.2025

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

| Product: | | |
|--|------------------------------------|---|
| Assessment | ered to ha REACH A (EU) 2017 | ance/mixture does not contain components consid- ve endocrine disrupting properties according to rticle 57(f) or Commission Delegated regulation 7/2100 or Commission Regulation (EU) 2018/605 at 0.1% or higher. |
| 12.7 Other adverse effects | | |
| Product: | | |
| Additional ecological infor- mation | There is r | o data available for this product. |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product: The generation of waste should be avoided or minimized
wherever possible.
Empty containers or liners may retain some product residues.
This material and its container must be disposed of in a safe
way.
Dispose of surplus and non-recyclable products via a licensed
waste disposal contractor.
Disposal of this product, solutions and any by-products should
at all times comply with the requirements of environmental
protection and waste disposal legislation and any regional
local authority requirements.
Avoid dispersal of spilled material and runoff and contact with
soil, waterways, drains and sewers.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikafloor®-10 Pronto N Part A



Print Date 15.01.2025

| Date of last issue: 19.05.2022 | | | 1 mil Dato 10.01.2020 | | |
|------------------------------------|-------------|---|-------------------------|--|--|
| | | | | | |
| Waste code Switzerland VeVA/LVA | - | S] Paint and varnish waste other hazardous substances | containing organic sol- | | |
| VEVALVA | vents of of | | | | |
| SECTION 14: Transport info | ormation | | | | |
| 14.1 UN number or ID number | | | | | |
| ADR | : UN 1247 | | | | |
| IMDG | : UN 1247 | | | | |
| ΙΑΤΑ | : UN 1247 | | | | |
| 14.2 UN proper shipping name | • | | | | |
| ADR | : METHYL I | METHACRYLATE MONOM | IER, STABILIZED | | |
| IMDG | : METHYL I | METHYL METHACRYLATE, MONOMER, STABILIZED | | | |
| ΙΑΤΑ | : Methyl me | Methyl methacrylate monomer, stabilized | | | |
| 14.3 Transport hazard class(es | 5) | | | | |
| | Class | Subsidiary risks | S | | |
| ADR | : 3 | | | | |

Version 3.0

| | | | , |
|------|--|---|--|
| | ADR | : | 3 |
| | IMDG | : | 3 |
| | ΙΑΤΑ | : | 3 |
| 14.4 | Packing group | | |
| | ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code | : | II F1 339 3 (D/E) |
| | IMDG Packing group Labels EmS Code | | ll 3 F-E, S-D |
| | IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels | | 364 Y341 II Flammable Liquids |
| | IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) | | 353 Y341 |

Revision Date: 15.01.2025

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikafloor®-10 Pronto N Part A

| Revision Date: 15.01.2025 Date of last issue: 19.05.2022 | Version 3.0 | Print Date 15.01.2025 |
|---|-----------------------------|-----------------------|
| Packing group Labels | : II : Flammable Liquids | |
| 14.5 Environmental hazards | | |
| ADR Environmentally hazardous | : no | |
| IMDG Marine pollutant | : no | |
| IATA (Passenger) Environmentally hazardous | : no | |
| IATA (Cargo) Environmentally hazardous | : no | |

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

| REACH Information: | All substances contain - registered by our up - registered by us, and - excluded from the re - exempted from the r | strea d/or egula | tion, and/or |
|--|--|------------------------|--|
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) | | : | Conditions of restriction for the fol- lowing entries should be considered: Number on list 3 |
| | | | Number on list 75: |
| REACH - Candidate List of S Concern for Authorisation (A | | : | None of the components are listed (=> 0.1 %). |
| REACH - List of substances (Annex XIV) | subject to authorisation | : | Not applicable |

Sikafloor[®]-10 Pronto N Part A



| Revision Date: 15.01.2025 Date of last issue: 19.05.2022 | Version 3.0 | Print Date 15.01.2025 | |
|---|---|-----------------------|--|
| Regulation (EC) on substances th layer | at deplete the ozone : Not applicable | e | |
| Regulation (EU) 2019/1021 on petants (recast) | rsistent organic pollu- : Not applicable | 9 | |
| PIC Ordinance, ChemPICO (814. | 82) : Not applicable | e | |
| Ordinance on Protection against I Threshold quantity according to M nance (MAO 814.012) | | | |
| Chemical Risk Reduction Ordinar (ORRChem, SR 814.81) Waters Protection Ordinance (WF | should be considered: Annex 1.11 Dangerous liquid s | - | |
| Water pollution class : | slightly hazardous to water Classification according to AwSV, Annex | 1 (5.2) | |
| Volatile organic compounds : | Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: < 0,01% w/w no VOC duties | | |
| | Directive 2010/75/EU of 24 November 20 emissions (integrated pollution prevention Volatile organic compounds (VOC) conte | n and control) | |

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

| H225 | : | Highly flammable liquid and vapour. |
|------|---|-------------------------------------|
| H315 | : | Causes skin irritation. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-10 Pronto N Part A



| Revision Date: 15.01.2025 Date of last issue: 19.05.2022 | | Version 3.0 | Print Date 15.01.2025 |
|---|------|--|-----------------------|
| H317 | • | May cause an allergic skin reaction. | |
| H319 | ÷ | Causes serious eye irritation. | |
| H335 | ÷ | May cause respiratory irritation. | |
| H411 | : | Toxic to aquatic life with long lasting effects. | |
| Full text of other abbreviat | ions | | |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard | |
| Eye Irrit. | : | Eye irritation | |
| Flam. Liq. | : | Flammable liquids | |
| Skin Irrit. | : | Skin irritation | |
| Skin Sens. | : | Skin sensitisation | |
| STOT SE | : | Specific target organ toxicity - single exposure | |
| 2009/161/EU | : | Europe. COMMISSION DIRECTIVE 2009/161/E | U establishing |
| | | a third list of indicative occupational exposure lin | |
| | | implementation of Council Directive 98/24/EC ar Commission Directive 2000/39/EC | id amending |
| CH SUVA | | Switzerland. Limit values at the work place | |
| 2009/161/EU / TWA | : | Limit Value - eight hours | |
| 2009/161/EU / STEL | : | Short term exposure limit | |
| CH SUVA / TWA | : | Time Weighted Average | |
| CH SUVA / STEL | : | Short Term Exposure Limit | |
| ADR | : | European Agreement concerning the Internation | al Carriage of |
| ABR | • | Dangerous Goods by Road | a camage of |
| CAS | | Chemical Abstracts Service | |
| DNEL | : | Derived no-effect level | |
| EC50 | : | Half maximal effective concentration | |
| GHS | : | Globally Harmonized System | |
| IATA | ÷ | International Air Transport Association | |
| IMDG | ÷ | International Maritime Code for Dangerous Good | ds |
| LD50 | : | Median lethal dosis (the amount of a material, gi | |
| | | once, which causes the death of 50% (one half) test animals) | |
| LC50 | | Median lethal concentration (concentrations of the | ne chemical in |
| 2000 | • | air that kills 50% of the test animals during the o | |
| | | period) | |
| MARPOL | : | International Convention for the Prevention of Po | ollution from |
| | | Ships, 1973 as modified by the Protocol of 1978 | |
| OEL | : | Occupational Exposure Limit | |
| PBT | : | Persistent, bioaccumulative and toxic | |
| PNEC | : | Predicted no effect concentration | |
| REACH | : | Regulation (EC) No 1907/2006 of the European | Parliament |
| | | and of the Council of 18 December 2006 concer | |
| | | istration, Evaluation, Authorisation and Restriction | on of Chemi- |
| | | cals (REACH), establishing a European Chemic | als Agency |
| SVHC | : | Substances of Very High Concern | |
| vPvB | : | Very persistent and very bioaccumulative | |
| Further information | | | |
| Classification of the mixtur | re: | Classification proced | ure: |
| Flam. Liq. 2 | | Based on product data | |
| 1 1a111. LIY. 2 | 112 | based on product data | 01 233533116111 |



Sikafloor®-10 Pronto N Part A

| | Version 3.0 | Print Date 15.01.2025 |
|------|--------------------|--|
| H315 | Calculation method | |
| H317 | Calculation method | |
| H335 | Calculation method | |
| | H317 | H315 Calculation method H317 Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN