Print Date 03.05.2023

Revision Date: 07.02.2023 Date of last issue: 21.06.2022 Version 7.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

SikaScreed[®] FastTop-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Concrete admixtures

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person responsible for the SDS	:	EHS@ch.sika.com

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)			
Eye irritation, Category 2	H319: Causes serious eye irritation.		
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.		

2.2 Label elements

Labelling (REGULATION (EC)	No 1272/2008)	
Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H317 H319	May cause an allergic skin reaction. Causes serious eye irritation.
Precautionary statements	:	Prevention:	

SikaScreed[®] FastTop-3

Revision Date: 07.02.2023 Date of last issue: 21.06.2022



P261 P280	Avoid breathing mist or vapours. Wear protective gloves/ eye protection/ face protection.
Response:	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.

Version 7.0

Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one (BIT) 2-octyl-2H-isothiazole-3-one (OIT) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: mixture of: 5-chloro-2-methyl-4isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)), 55965-84-9, 1,2-benzisothiazol-3(2H)-one (BIT), 2634-33-5, 2-octyl-2Hisothiazole-3-one (OIT), 26530-20-1. Please use treated articles responsibly.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
2-methylpentane-2,4-diol	107-41-5	Skin Irrit. 2; H315	>= 1 - < 2,5
	203-489-0	Eye Irrit. 2; H319	
	01-2119539582-35-	Repr. 2; H361d	
	XXXX		

SikaScreed[®] FastTop-3

Revision Date: 07.02.2023 Date of last issue: 21.06.2022



Version 7.0

2,2-dimethylpropane-1,3-diol	126-30-7 204-781-0 01-2119480396-30- XXXX	Eye Dam. 1; H318	>= 1 - < 2,5
1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5 220-120-9 01-2120761540-60- XXXX	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 specific concentration limit Skin Sens. 1; H317 >= 0,05 % Acute toxicity esti- mate Acute oral toxicity: 597 mg/kg Acute inhalation tox- icity (dust/mist): 0,4 mg/l	>= 0,0025 - < 0,025

SikaScreed[®] FastTop-3

Revision Date: 07.02.2023 Date of last issue: 21.06.2022



Version 7.0

2-octyl-2H-isothiazole-3-one (OIT)	26530-20-1 247-761-7 01-2120768921-45- XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071	>= 0,0015 - < 0,0025
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Sens. 1A; H317 >= 0,0015 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 125 mg/kg Acute inhalation tox- icity (dust/mist): 0,27 mg/l Acute dermal toxicity:	

SikaScreed[®] FastTop-3

Revision Date: 07.02.2023 Date of last issue: 21.06.2022



Version 7.0

mixture of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247- 500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239- 6] (3:1) (C(M)IT/MIT (3:1))	55965-84-9 911-418-6 01-2120764691-48- XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	< 0,0002
--	--	---	----------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	Move out of danger Consult a physician Show this safety da	
If inhaled	Move to fresh air. Consult a physician	after significant exposure.
In case of skin contact	Take off contaminat Wash off with soap If symptoms persist	
In case of eye contact	Remove contact len Keep eye wide oper	

SikaScreed[®] FastTop-3



Date of last issue: 21.06.2022		Version 7.0	Print Date 03.05.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	person.
4.2 Most important symptoms a	nd e	effects, both acute and delayed	
Symptoms	:	Allergic reactions Excessive lachrymation See Section 11 for more detailed information on and symptoms.	health effects
Risks	:	irritant effects sensitising effects	
		May cause an allergic skin reaction. Causes serious eye irritation.	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting mea	sur	es	
	sur	es	
		In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction.	
5.1 Extinguishing media Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction.	
 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from 	: n the	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction.	
 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Hazardous combustion prod- ucts 	: n the	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction.	
 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Hazardous combustion prod- 	: 1 the :	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction.	owder for
 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Hazardous combustion prod- ucts 5.3 Advice for firefighters Special protective equipment 	: 1 the :	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction. e substance or mixture No hazardous combustion products are known	owder for
 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Hazardous combustion prod- ucts 5.3 Advice for firefighters Special protective equipment for firefighters 	: • the : :	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction. e substance or mixture No hazardous combustion products are known In the event of fire, wear self-contained breathing Standard procedure for chemical fires.	owder for
 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Hazardous combustion products 5.3 Advice for firefighters Special protective equipment for firefighters Further information SECTION 6: Accidental releat 	: 1 the : :	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical po extinction. e substance or mixture No hazardous combustion products are known In the event of fire, wear self-contained breathing Standard procedure for chemical fires.	owder for

6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
---------------------------	---	---

SikaScreed® FastTop-3

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for	cleaning up
-------------	-------------

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection again fire and explosion	nst :	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe stora	ge, incl	uding any incompatibilities
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on sto age stability	or- :	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

Print Date 03.05.2023

Revision Date: 07.02.2023 Date of last issue: 21.06.2022

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *				
2-methylpentane-2,4-diol	107-41-5	TWA	10 ppm 49 mg/m3	CH SUVA				
	Further informa	ation: The substanc	e can be present	simultaneously				
	as vapor and a	as vapor and aerosol						
		STEL	20 ppm 98 mg/m3	CH SUVA				
2-octyl-2H-isothiazole-3-one (OIT)	26530-20-1	TWA (inhalable dust)	0,05 mg/m3	CH SUVA				
	Further informa	ation: Toxic by skin	resorption possibl	e; Substanc-				
	es, which are easily absored through the skin, can give by addi-							
	tional skin resoption a substancial higher risk compared to only							
	inhalation by the airways., Sensitizers; Substances marked with							
	an S can lead to very strong allergic reactions.							
		STEL (inhalable dust)	0,1 mg/m3	CH SUVA				
mixture of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	55965-84-9	TWA (inhalable dust)	0,2 mg/m3	CH SUVA				
	Further information: Sensitizers; Substances marked with an S							
	can lead to very strong allergic reactions., Harm to the unborn							
	child is not to be expected when the OEL-value is respected							
		STEL (inhalable dust)	0,4 mg/m3	CH SUVA				

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm)
	Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm),

SikaScreed® FastTop-3

Print Date 03.05.2023

Revision Date: 07.02.2023	
Date of last issue: 21.06.2022	

		breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Environmental exposure cor	ntr	ols
General advice	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid amber
Odour	:	characteristic
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Up- per flammability limit	•	
Lower explosion limit / Lower flammability limit	:	No data available

SikaScreed[®] FastTop-3

Revision Date: 07.02.2023 Date of last issue: 21.06.2022





Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	ca. 6,3 (20 °C)
Viscosity		
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies) Water solubility	:	soluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	23 hPa
Density	:	ca. 1 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

Revision Date: 07.02.2023 Date of last issue: 21.06.2022 Version 7.0



10.4 Conditions to avoid	
--------------------------	--

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008


Acute toxicity

Not classified based on available information.

Components:

2-methylpentane-2,4-diol:	
Acute oral toxicity :	LD50 Oral (Rat): 3.700 mg/kg
Acute dermal toxicity :	LD50 Dermal (Rabbit): > 5.000 mg/kg
2,2-dimethylpropane-1,3-diol:	
Acute oral toxicity :	LD50 Oral (Rat): > 5.000 mg/kg
1,2-benzisothiazol-3(2H)-one (E	BIT):
Acute oral toxicity :	LD50 Oral (Rat): 597 mg/kg
	Acute toxicity estimate: 597 mg/kg Method: Calculation method
Acute inhalation toxicity :	LC50: 0,4 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
	Acute toxicity estimate: 0,4 mg/l Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity :	LD50 Dermal (Rabbit): > 2.000 mg/kg
2-octyl-2H-isothiazole-3-one (C	DIT):
Acute oral toxicity :	Acute toxicity estimate: 125 mg/kg Method: Acute toxicity estimate according to Regulation (EC)

SikaScreed[®] FastTop-3





Revision Date: 07.02.2023 Date of last issue: 21.06.2022

Version 7.0



11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other	:	EC50 (Daphnia (water flea)): 3 mg/l
aquatic invertebrates		Exposure time: 48 h

2-octyl-2H-isothiazole-3-one (OIT):

M-Factor (Acute aquatic tox- : 100 icity)

M-Factor (Chronic aquatic : 100 toxicity)

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

M-Factor (Acute aquatic tox- : 100 icity)

M-Factor (Chronic aquatic : 100 toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

Revision Date: 07.02.2023 Date of last issue: 21.06.2022



Version 7.0

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher
levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	There is no data available for this product.
mation		

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

octamethylcyclotetrasiloxane [D4]:

20-year global warming potential: 2,66 100-year global warming potential: 0,739 500-year global warming potential: 0,211 Atmospheric lifetime: 0,027 yr Radiative efficiency: 0,12 Wm2ppb Further information: Miscellaneous compounds

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: The generation of waste should be avoided or minimized wherever possible.
	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland	: 16 10 01 -

Revision Date: 07.02.2023 Date of last issue: 21.06.2022 Version 7.0



VeVA/LVA

Contaminated packaging

: 15 01 10 [S] packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	Not regulated as a dangerous good	
IMDG	:	Not regulated as a dangerous good	
ΙΑΤΑ	:	Not regulated as a dangerous good	
14.2 UN proper shipping name			
ADR	:	Not regulated as a dangerous good	
IMDG	:	Not regulated as a dangerous good	
ΙΑΤΑ	:	Not regulated as a dangerous good	
14.3 Transport hazard class(es)			
ADR	:	Not regulated as a dangerous good	
IMDG	:	Not regulated as a dangerous good	
ΙΑΤΑ	:	Not regulated as a dangerous good	
14.4 Packing group			
ADR	:	Not regulated as a dangerous good	
IMDG	:	Not regulated as a dangerous good	
IATA (Cargo)	:	Not regulated as a dangerous good	
IATA (Passenger)	:	Not regulated as a dangerous good	
14.5 Environmental hazards			

4.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

SikaScreed[®] FastTop-3

Revision Date: 07.02.2023 Date of last issue: 21.06.2022 Version 7.0



		2-methy	Ipentane-2,4-diol
International Chemical Weapo Schedules of Toxic Chemicals	;) : Not app	licable	
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).		h : None of (=> 0.1	the components are listed %).
REACH - List of substances subject to authorisation (Annex XIV)		n : Not app	licable
Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer		de- : Not app	licable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)		ollu- : Not app	licable
PIC Ordinance, ChemPICO (814.82)		: Not app	licable
REACH Information:	 registered by c registered by u 	he regulation, and/	ers, and/or
Seveso III: Directive 2012/18/I jor-accident hazards involving			ne Council on the control of i
Water hazard class (Germa- ny)	: WGK 2 obvious Classification ac	/ hazardous to wat cording to AwSV, A	
Volatile organic compounds	(VOCV)		organic compounds content: < 0,01% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,13% w/w

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people. ma-

SikaScreed[®] FastTop-3

Revision Date: 07.02.2023 Date of last issue: 21.06.2022

Version 7.0



15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H301 H302 H310 H311 H314 H315 H317 H318 H319 H330 H361d H400 H410 H411	 Toxic if swallowed. Harmful if swallowed. Fatal in contact with skin. Toxic in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Fatal if inhaled. Suspected of damaging the unborn child. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	
Acute Tox. Aquatic Acute Aquatic Chronic Eye Dam. Eye Irrit. Repr. Skin Corr.	 Acute toxicity Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Serious eye damage Eye irritation Reproductive toxicity Skin corrosion
Skin Irrit. Skin Sens. CH SUVA CH SUVA / TWA CH SUVA / STEL ADR	 Skin irritation Skin sensitisation Switzerland. Limit values at the work place Time Weighted Average Short Term Exposure Limit European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS DNEL EC50 GHS IATA IMDG LD50	 Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of
LC50	test animals) Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL OEL	 International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 Occupational Exposure Limit

SikaScreed® FastTop-3

Print Date 03.05.2023

Revision Date: 07.02.2023		
Date of last issue: 21.06.2022		

Version 7.0

PBT PNEC REACH	 Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi-
SVHC vPvB	 cals (REACH), establishing a European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative
Further information	

Classification of the mixtu	Classification procedure:	
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN