

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikafloor<sup>®</sup>-320 N Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Flooring system, For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

#### **1.4 Emergency telephone number**

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure.

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0



### 2.2 Label elements

Labelling (REGULATION	(EC)	No 1272/2008)	
Hazard pictograms	:		!
Signal word	:	Danger	
Hazard statements	:	H315 H317 H319 H332 H334 H335 H351 H373	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through pro- longed or repeated exposure.
Precautionary statements	:	<b>Prevention:</b> P201 P260 P264 P280	Obtain special instructions before use. Do not breathe mist or vapours. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		<b>Response:</b> P304 + P340 + P342 + P311	P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

### Hazardous components which must be listed on the label:

4,4`-Methylenediphenyl diisocyanate, oligomers aromatic isocyanate-prepolymer

#### **Additional Labelling**

"As from 24 August 2023 adequate training is required before industrial or professional use."

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# Sikafloor<sup>®</sup>-320 N Part B

Print Date 11.09.2023

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		(70 00/00)
4,4`-Methylenediphenyl diisocya- nate, oligomers	25686-28-6 500-040-3 01-2119457013-49- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H314 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Acute toxicity estimate	>= 60 - < 80
		Acute inhalation tox- icity (dust/mist): 1,5 mg/l	
aromatic isocyanate-prepolymer	9048-57-1 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H319 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Acute toxicity esti- mate	>= 25 - < 40
		Acute inhalation tox- icity (dust/mist): 1,5 mg/l	

For explanation of abbreviations see section 16.

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0



### **SECTION 4: First aid measures**

4.1 Description of first aid measures						
General advice :	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.					
If inhaled :	Move to fresh air. Consult a physician after significant exposure.					
In case of skin contact :	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.					
In case of eye contact :	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.					
If swallowed :	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.					

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	<ul> <li>Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed information on health effects and symptoms.</li> </ul>
Risks	<ul> <li>irritant effects sensitising effects</li> <li>Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.</li> </ul>



Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

Extinguishing media		
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
Special hazards arising from	the	e substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.
	Suitable extinguishing media Special hazards arising from Hazardous combustion prod- ucts Advice for firefighters Special protective equipment for firefighters	Suitable extinguishing media : Special hazards arising from the Hazardous combustion prod- : ucts Advice for firefighters Special protective equipment : for firefighters

# **SECTION 6: Accidental release measures**

<b>6.1 Personal precautions, protec</b> Personal precautions		e equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for cor	ntai	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
6.4 Reference to other sections		
For personal protection see se	ectio	on 8.

# **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling	:	Avoid formation of aerosol.
		Avoid exceeding the given occupational exposure limits (see

# Sikafloor<sup>®</sup>-320 N Part B

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0



			<ul> <li>section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Provide sufficient air exchange and/or exhaust in work rooms.</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage,	inc	luding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
4,4`-Methylenediphenyl diisocyanate, oligomers	25686-28-6	TWA	0,02 mg/m3 (NCO)	CH SUVA
	total of its reac Therefore the i cancelled., To are easily abso	ation: The limit valu- tive NCO-groups of ndividual limit value kic by skin resorptio pred through the ski pstancial higher risk	f all monomers an es for individual iso n possible; Substa in, can give by ado	d prepolymers. ocyanates are ances, which ditional skin



Revision Date: 11.09.2023 Date of last issue: 18.11.2021

to very strong (Occupational	Sensitizers; Substan allergic reactions., H Medicine and Hygie not to be expected	Health and Safety ene Laboratory), H	Executive larm to the
	STEL	0,02 mg/m3 (NCO)	CH SUVA

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment				
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water			
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.			
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.			
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.			
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.			

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0



# **Environmental exposure controls**

General advice

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

# **SECTION 9: Physical and chemical properties**

9.1	9.1 Information on basic physical and chemical properties		
	Physical state Colour	:	liquid yellow
	Odour	:	slight
	Melting point/range / Freezing point	:	No data available
	Boiling point/boiling range	:	No data available
	Flammability (solid, gas)	:	No data available
	Upper/lower flammability or e	əxp	losive limits
	Upper explosion limit / Up- per flammability limit	:	No data available
	Lower explosion limit / Lower flammability limit	:	No data available
	Flash point	:	195 °C Method: closed cup
	Auto-ignition temperature	:	No data available
	Decomposition temperature	:	No data available
	рН	:	Not applicable substance/mixture reacts with water
	Viscosity Viscosity, kinematic	:	> 7 mm2/s (40 °C)
	<b>Solubility(ies)</b> Water solubility	:	insoluble

# Sikafloor<sup>®</sup>-320 N Part B

Print Date 11.09.2023

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0

Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,01 hPa	
Density	: ca. 1,21 g/cm3 (20	) °C)
Relative vapour density	: No data available	
Particle characteristics	: No data available	

# 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

available

# 10.5 Incompatible materials

Materials to avoid : No data available

### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Harmful if inhaled.

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0



# Components:

4,4`-Methylenediphenyl dii	SOC	vanate, oligomers:		
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg		
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement		
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method		
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 9.400 mg/kg		
aromatic isocyanate-prepo	lym	er:		
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Acute toxicity estimate: 1,5 mg/l		
		Test atmosphere: dust/mist Method: Calculation method		
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 9.400 mg/kg		
Skin corrosion/irritation Causes skin irritation.				
Serious eye damage/eye ir	ritat	ion		
Causes serious eye irritation				
Respiratory or skin sensitisation				
Skin sensitisation May cause an allergic skin re	eacti	on.		
Respiratory sensitisation				
May cause allergy or asthma symptoms or breathing difficulties if inhaled.				
Germ cell mutagenicity Not classified based on avail	able	information.		
Carcinogenicity				
Suspected of causing cancel	r.			
Reproductive toxicity				
Not classified based on avail	able	information.		
<b>STOT - single exposure</b> May cause respiratory irritation	on.			

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0



### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration toxicity

Not classified based on available information.

#### 11.2 Information on other hazards

#### Endocrine disrupting properties

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

#### aromatic isocyanate-prepolymer:

Toxicity to fish

: LC50 (Danio rerio (zebra fish)): > 1.000 mg/l Exposure time: 96 h

### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

:

#### Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### **12.6 Endocrine disrupting properties**

#### Product:

Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to
		REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

# Sikafloor®-320 N Part B

Print Date 11.09.2023

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0

# levels of 0.1% or higher.

### 12.7 Other adverse effects

### Product:

Additional ecological infor-	:	There is no data available for this product.
mation		

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	: The generation of waste should be avoided or minimized wherever possible.
	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

# 14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
Country CH 000000214439		

Print Date 11.09.2023

Revision Date: 11.09.2023
Date of last issue: 18.11.2021

Version 10.0

IMDG	: Not regulated as a da	naei	rous good
IATA (Cargo)	: Not regulated as a da	-	-
IATA (Passenger)	: Not regulated as a da	-	•
14.5 Environmental hazards		5-	
Not regulated as a dangerous	good		
14.6 Special precautions for use Not applicable	r		
14.7 Maritime transport in bulk a	ccording to IMO instrum	ents	
Not applicable for product as	-	onte	
SECTION 15: Regulatory info	rmation		
<b>15.1 Safety, health and environm</b> International Chemical Weapo Schedules of Toxic Chemicals	ons Convention (CWC)	tion :	specific for the substance or mixture Not applicable
REACH Information:	All substances contain - registered by our up - registered by us, and - excluded from the re - exempted from the re	strea d/or egula	am suppliers, and/or ation, and/or
REACH - Restrictions on the the market and use of certain mixtures and articles (Annex )	dangerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
			4,4`-Methylenediphenyl diisocya- nate, oligomers (Number on list 74, 56)
REACH - Candidate List of Su Concern for Authorisation (Art		:	None of the components are listed (=> 0.1 %).
REACH - List of substances s (Annex XIV)	ubject to authorisation	:	Not applicable
Regulation (EC) No 1005/200 plete the ozone layer	9 on substances that de-	:	Not applicable
Regulation (EU) 2019/1021 or tants (recast)	n persistent organic pollu-	:	Not applicable
PIC Ordinance, ChemPICO (8	314.82)	:	Not applicable
Seveso III: Directive 2012/18/	EU of the European Parlia	men	t and of the Council on the control of ma-

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0



Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

#### Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

# **SECTION 16: Other information**

#### **Full text of H-Statements**

H315 H317	:	Causes skin irritation. May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
Full text of other abbre	viations	
Acute Tox.	:	Acute toxicity
Carc.	:	Carcinogenicity
Eve Irrit.	:	Eye irritation

Revision Date: 11.09.2023 Date of last issue: 18.11.2021



Version 10.0

Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
CH SUVA	:	Switzerland. Limit values at the work place
CH SUVA / TWA		Time Weighted Average
CH SUVA / STEL		Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of
ABR .	•	Dangerous Goods by Road
CAS		Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
	:	
GHS	÷	Globally Harmonized System
IATA	÷	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
	-	and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC		Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative
	•	vory persistent and very bloaccumulative

### Further information

Classification of the mixture:		
H332	Calculation method	
H315	Calculation method	
H319	Calculation method	
H334	Calculation method	
H317	Calculation method	
H351	Calculation method	
H335	Calculation method	
H373	Calculation method	
	H332 H315 H319 H334 H317 H351 H335	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

# Sikafloor<sup>®</sup>-320 N Part B

Revision Date: 11.09.2023 Date of last issue: 18.11.2021 Version 10.0



Changes as compared to previous version !

CH / EN