

Revision Date: 17.04.2023 Date of last issue: 19.03.2021 Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor[®]-390 ECF N Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

| Company name of supplier | : | Sika Schweiz AG |
|--------------------------|---|------------------|
| | | Tüffenwies 16 |
| | | 8048 Zürich |
| Telephone | : | +41 58 436 40 40 |
| Telefax | : | - |
| E-mail address of person | : | EHS@ch.sika.com |
| responsible for the SDS | | |

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| Skin irritation, Category 2 | H315: Causes skin irritation. |
|---|--|
| Serious eye damage, Category 1 | H318: Causes serious eye damage. |
| Skin sensitisation, Category 1 | H317: May cause an allergic skin reaction. |
| Germ cell mutagenicity, Category 2 | H341: Suspected of causing genetic defects. |
| Reproductive toxicity, Category 1B | H360F: May damage fertility. |
| Long-term (chronic) aquatic hazard, Cat- egory 2 | H411: Toxic to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Print Date 16.10.2024

| Revision Date: 17.04.2023 Date of last issue: 19.03.2021 | | V | /ersion 2.0 | Print Date 16 |
|---|---|--|--|-----------------------------------|
| Hazard pictograms | : | | | 2 |
| Signal word | : | Danger | • • | |
| Hazard statements | : | H315 H317 H318 H341 H360F H411 | Causes skin irritation. May cause an allergic skin Causes serious eye damag Suspected of causing gene May damage fertility. Toxic to aquatic life with lor | ge. etic defects. |
| Precautionary statements | : | Prevention: P201 P273 P280 | Obtain special instructions Avoid release to the enviro Wear protective gloves/ pro eye protection/ face protect | nment. ptective clothing/ |
| | | Response: P305 + P351 + P308 + P313 P391 | P338 + P310 IF IN EYES: with water for several minu tact lenses, if present and e tinue rinsing. Immediately of CENTER/ doctor. IF exposed or concerned: (vice/ attention. Collect spillage. | easy to do. Con- call a POISON |
| | | - | | |

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane bis-[4-(2,3-epoxypropoxy)phenyl]methane Trimethylolpropane triglycidylether p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikafloor[®]-390 ECF N Part A

Revision Date: 17.04.2023 Date of last issue: 19.03.2021



Version 2.0

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Components Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|---|--|--|--------------------------|
| bis-[4-(2,3- epoxipropoxi)phenyl]propane | 1675-54-3 216-823-5 01-2119456619-26- XXXX | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 % | >= 20 - < 25 |
| bis-[4-(2,3- epoxypropoxy)phenyl]methane | Not Assigned 701-263-0 01-2119454392-40- XXXX | Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411 | >= 10 - < 20 |
| Trimethylolpropane triglycidylether | Not Assigned 701-135-4 01-2120078341-60- XXXX | Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Muta. 2; H341 Repr. 1B; H360F Aquatic Chronic 2; H411 | >= 3 - < 5 |
| benzyl alcohol | 100-51-6 202-859-9 01-2119492630-38- XXXX | Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l | >= 2,5 - < 5 |
| p-tert-butylphenyl 1-(2,3- epoxy)propyl ether For explanation of abbreviations se | 3101-60-8 221-453-2 01-2119959496-20- XXXX | Skin Sens. 1; H317 Aquatic Chronic 2; H411 | >= 0,5 - < 1 |

For explanation of abbreviations see section 16.

Sikafloor®-390 ECF N Part A

Revision Date: 17.04.2023 Date of last issue: 19.03.2021 Version 2.0



SECTION 4: First aid measures

| 4.1 Description of first aid measures | | | |
|---------------------------------------|---|--|--|
| General advice : | Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. | | |
| If inhaled : | Move to fresh air. Consult a physician after significant exposure. | | |
| In case of skin contact : | Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. | | |
| In case of eye contact : | Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. | | |
| If swallowed : | Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. | | |
| 4.2 Most important symptoms and | effects, both acute and delayed | | |
| Symptoms : | Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms. | | |
| Risks : | irritant effects sensitising effects toxic effects for reproduction | | |
| | Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic defects. May damage fertility. | | |
| 4.3 Indication of any immediate me | dical attention and special treatment needed | | |
| Treatment : | Treat symptomatically. | | |

Print Date 16.10.2024

Revision Date: 17.04.2023 Date of last issue: 19.03.2021 Version 2.0

SECTION 5: Firefighting measures

| 5.1 Extinguishing media Suitable extinguishing media | : | In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction. |
|--|-----|---|
| 5.2 Special hazards arising from | the | e substance or mixture |
| Specific hazards during fire- fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion prod- ucts | : | No hazardous combustion products are known |
| 5.3 Advice for firefighters | | |
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

| • • • | | • • | 0 71 |
|----------------------|---|----------------------|-------------------|
| Personal precautions | : | Use personal protect | ctive equipment. |
| | | Deny access to unp | rotected persons. |

6.2 Environmental precautions

| Environmental precautions | : | Do not flush into surface water or sanitary sewer system. |
|---------------------------|---|---|
| | | If the product contaminates rivers and lakes or drains inform |
| | | respective authorities. |

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Sikafloor[®]-390 ECF N Part A



| Revision Date: 17.04.2023 Date of last issue: 19.03.2021 | | Version 2.0 | Print Date 16.10.2 |
|---|------|--|--|
| Advice on safe handling | : | Avoid exceeding the given occupational exp section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation ma, allergies, chronic or recurrent respirato not be employed in any process in which th used. Smoking, eating and drinking should be pro- plication area. Pregnant women or women of child-bearing exposed to this product. Follow standard hygiene measures when has products | problems or asth- ry disease should is mixture is being hibited in the ap- g age should not be |
| Advice on protection against fire and explosion | : | Normal measures for preventive fire protect | ion. |
| Hygiene measures | : | Handle in accordance with good industrial h practice. When using do not eat or drink. W smoke. Wash hands before breaks and at t | hen using do not |
| 7.2 Conditions for safe storage, i | incl | luding any incompatibilities | |
| Requirements for storage areas and containers | : | Keep container tightly closed in a dry and w place. Containers which are opened must b sealed and kept upright to prevent leakage. ance with local regulations. | e carefully re- |
| Further information on stor- age stability | : | No decomposition if stored and applied as o | lirected. |
| 7.3 Specific end use(s) | | | |
| Specific use(s) | : | Consult most current local Product Data Sh use. | eet prior to any |

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parame- ters * | Basis * |
|----------------|---|---|---|---|
| benzyl alcohol | 100-51-6 | TWA | 5 ppm 22 mg/m3 | CH SUVA |
| | as vapor and a stances, which additional skin | ation: The substance lerosol, Toxic by sk are easily absored resoption a substa by the airways., Na | in resorption poss I through the skin, ncial higher risk co | ible; Sub- can give by ompared to |



Revision Date: 17.04.2023 Date of last issue: 19.03.2021 Version 2.0

| | Safety and Health, Harm to the unborn child is not to be expected when the OEL-value is respected | |
|--|---|--|
| | when the OEL-value is respected | |
| a above mentioned values are in accordance with the logislation in effect at the date of the re- | | |

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

| Personal protective equipment | | | | |
|-------------------------------|---|--|--|--|
| Eye/face protection | : | Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water | | |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. | | |
| | | Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min. | | |
| Skin and body protection | : | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work. | | |
| Respiratory protection | : | In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. | | |

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Sikafloor®-390 ECF N Part A

Print Date 16.10.2024

Revision Date: 17.04.2023 Date of last issue: 19.03.2021

Version 2.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Physical state Appearance Colour | : | liquid viscous liquid various |
|---|-----|---|
| Odour | : | epoxy-like |
| Melting point/range / Freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper/lower flammability or e | avn | losive limits |
| Upper explosion limit / Up- per flammability limit | - | |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Flash point | : | > 101 °C Method: closed cup |
| Auto-ignition temperature | : | No data available |
| | | No data available |
| Decomposition temperature | : | No data available |
| рН | : | Not applicable substance/mixture is non-soluble (in water) |
| Viscosity | | |
| Viscosity, dynamic | : | ca. 4.900 mPa.s (20 °C) |
| Viscosity, kinematic | : | > 20,5 mm2/s (40 °C) |
| Solubility(ies) | | |
| Water solubility | : | insoluble |

Revision Date: 17.04.2023 Date of last issue: 19.03.2021





| Partition coefficient: n- octanol/water | : No data available |
|--|--------------------------|
| Vapour pressure | : 0,01 hPa |
| | 0,01 hPa |
| Density | : ca. 1,66 g/cm3 (20 °C) |
| Relative vapour density | : No data available |
| Particle characteristics | : No data available |

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Revision Date: 17.04.2023 Date of last issue: 19.03.2021 Version 2.0



SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not classified based on available information.

Components:

| <u>components.</u> | | | | | | |
|--|------|---|--|--|--|--|
| bis-[4-(2,3-epoxipropoxi)phenyl]propane: | | | | | | |
| Acute oral toxicity | : | LD50 Oral (Rat): > 5.000 mg/kg | | | | |
| Acute dermal toxicity | : | LD50 Dermal (Rabbit): > 5.000 mg/kg | | | | |
| Trimethylolpropane triglyci | dyle | ether: | | | | |
| Acute oral toxicity | : | LD50 Oral (Rat): 3.398 mg/kg | | | | |
| Acute dermal toxicity | : | LD50 Dermal (Rabbit): > 2.000 mg/kg | | | | |
| benzyl alcohol: | | | | | | |
| Acute oral toxicity | : | LD50 Oral (Rat): 1.620 mg/kg | | | | |
| | | Acute toxicity estimate: 1.620 mg/kg Method: Calculation method | | | | |
| Acute inhalation toxicity | : | LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist | | | | |
| | | Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method | | | | |
| p-tert-butylphenyl 1-(2,3-ep | оху |)propyl ether: | | | | |
| Acute oral toxicity | : | LD50 Oral (Rat): > 5.000 mg/kg | | | | |
| Acute inhalation toxicity | : | LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mist | | | | |
| Acute dermal toxicity | : | LD50 Dermal (Rabbit): 6.000 mg/kg | | | | |
| Skin corrosion/irritation Causes skin irritation. | | | | | | |
| Serious eye damage/eye irritation | | | | | | |
| | | | | | | |

Causes serious eye damage.

Revision Date: 17.04.2023 Date of last issue: 19.03.2021 Version 2.0



Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h |
|---|---|---|
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h |

Trimethylolpropane triglycidylether:

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (microalgae)): 9 mg/l



| | Version 2.0 | Print Date 16. |
|----------|---|---|
| | Exposure time: 72 h | |
| r : - | EC50: 3,7 mg/l Exposure time: 48 d Species: Daphnia magna (Water flea) | |
| | | |
| : | LC50 (Fish): > 100 mg/l Exposure time: 96 h | |
| r : | EC50 (Daphnia magna (Water flea)): > 100 mg/ Exposure time: 48 h | 1 |
| ility | | |
| | | |
| | | |
| isse | ssment | |
| | | |
| : | to be either persistent, bioaccumulative and tox | ic (PBT), or |
| ertie | s | |
| | | |
| : | ered to have endocrine disrupting properties ac REACH Article 57(f) or Commission Delegated | cording to regulation |
| | | |
| | | |
| : | An environmental hazard cannot be excluded in unprofessional handling or disposal. Toxic to aquatic life with long lasting effects. | the event of |
| | - Ility | Exposure time: 72 h : EC50: 3,7 mg/l Exposure time: 48 d Species: Daphnia magna (Water flea) : LC50 (Fish): > 100 mg/l Exposure time: 96 h : EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Insessment It is substance/mixture contains no component to be either persistent, bioaccumulative and tox very persistent and very bioaccumulative (vPvB 0.1% or higher erties : The substance/mixture does not contain comporered to have endocrine disrupting properties ac REACH Article 57(f) or Commission Delegated (EU) 2017/2100 or Commission Regulation (EU levels of 0.1% or higher. |

13.1 Waste treatment methods

Sikafloor[®]-390 ECF N Part A

Revision Date: 17.04.2023

Date of last issue: 19.03.2021

Print Date 16.10.2024

| | | wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. |
|----------------------------------|--------|---|
| Waste code Switzerla VeVA/LVA | and : | 08 01 11 - |
| Contaminated package | ging : | 15 01 10 [S] packaging containing residues of or contaminat- ed by dangerous substances |

Version 2.0

SECTION 14: Transport information

| 14.1 UN number or ID number | | | |
|---------------------------------|---|---|----------------------------------|
| ADR | : | UN 3082 | |
| IMDG | : | UN 3082 | |
| ΙΑΤΑ | : | UN 3082 | |
| 14.2 UN proper shipping name | | | |
| ADR | : | ENVIRONMENTALL N.O.S. (epoxy resin) | Y HAZARDOUS SUBSTANCE, LIQUID, |
| IMDG | : | ENVIRONMENTALL N.O.S. (epoxy resin) | Y HAZARDOUS SUBSTANCE, LIQUID, |
| ΙΑΤΑ | : | Environmentally haza (epoxy resin) | ardous substance, liquid, n.o.s. |
| 14.3 Transport hazard class(es) | | | |
| | | Class | Subsidiary risks |
| ADR | : | 9 | |
| IMDG | : | 9 | |
| ΙΑΤΑ | : | 9 | |
| 14.4 Packing group | | | |
| ADR Packing group | : | 111 | |



| Revision Date: 17.04.2023 Date of last issue: 19.03.2021 | | Version 2.0 | Print Date 16.10.2024 |
|---|---|--|-----------------------|
| Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks | : | M6 90 9 (-) Transport in accordance with special provision 37 | '5 |
| IMDG Packing group Labels EmS Code Remarks | : | III 9 F-A, S-F Transport in accordance with 2.10.2.7 of the IMD | G-Code |
| IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels Remarks | : | 964 Y964 III Miscellaneous Transport in accordance with special regulation A | . 197 |
| IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels | : | 964 Y964 III Miscellaneous | |
| 14.5 Environmental hazards | | | |
| ADR Environmentally hazardous | : | yes | |
| IMDG Marine pollutant | : | yes | |
| IATA (Passenger) Environmentally hazardous | : | yes | |
| IATA (Cargo) Environmentally hazardous | : | yes | |
| | | | |

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Sikafloor[®]-390 ECF N Part A



| Revision Date: 17.04.2023 Date of last issue: 19.03.2021 | Version 2 | 2.0 | Print Date 16.10.2 |
|---|--|---------------------|--|
| REACH - Restrictions on the mar the market and use of certain dar mixtures and articles (Annex XVII | ngerous substances, | : | Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3 |
| International Chemical Weapons Schedules of Toxic Chemicals an | | : | Not applicable |
| REACH - Candidate List of Subst Concern for Authorisation (Article | | : | None of the components are listed (=> 0.1 %). |
| REACH - List of substances subje (Annex XIV) | ect to authorisation | : | Not applicable |
| Regulation (EC) No 1005/2009 or plete the ozone layer | n substances that de- | : | Not applicable |
| Regulation (EU) 2019/1021 on pettants (recast) | ersistent organic pollu- | : | Not applicable |
| PIC Ordinance, ChemPICO (814. | .82) | : | Not applicable |
| REACH Information: | All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg | trea /or gula | am suppliers, and/or ation, and/or |
| | | | |

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

| Water hazard class (Germa- ny) | : | WGK 2 obviously hazardous to water Classification according to AwSV, Annex 1 (5.2) |
|-----------------------------------|---|--|
| Volatile organic compounds | : | Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 5,34% w/w |
| Volatile organic compounds | | Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 5,34% w/w |

Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Sikafloor[®]-390 ECF N Part A



Revision Date: 17.04.2023 Date of last issue: 19.03.2021 Version 2.0

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

The product belongs to group 1 according to the Swiss Chemicals Ordinance (ChemO 813.11).

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

| I un text of H-Otatements | | | | |
|----------------------------------|---|---|--|--|
| H302 | : | Harmful if swallowed. | | |
| H314 | : | Causes severe skin burns and eye damage. | | |
| H315 | : | Causes skin irritation. | | |
| H317 | : | May cause an allergic skin reaction. | | |
| H318 | : | Causes serious eye damage. | | |
| H319 | : | Causes serious eye irritation. | | |
| H332 | : | Harmful if inhaled. | | |
| H341 | : | Suspected of causing genetic defects. | | |
| H360F | : | May damage fertility. | | |
| H411 | : | Toxic to aquatic life with long lasting effects. | | |
| Full text of other abbreviations | | | | |
| Acute Tox. | : | Acute toxicity | | |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard | | |
| Eye Dam. | : | Serious eye damage | | |
| Eye Irrit. | : | Eye irritation | | |
| Muta. | : | Germ cell mutagenicity | | |
| Repr. | : | Reproductive toxicity | | |
| Skin Corr. | : | Skin corrosion | | |
| Skin Irrit. | : | Skin irritation | | |
| Skin Sens. | : | Skin sensitisation | | |
| CH SUVA | : | Switzerland. Limit values at the work place | | |
| CH SUVA / TWA | : | Time Weighted Average | | |
| ADR | : | European Agreement concerning the International Carriage of | | |
| | | Dangerous Goods by Road | | |
| CAS | : | Chemical Abstracts Service | | |
| DNEL | : | Derived no-effect level | | |
| EC50 | : | Half maximal effective concentration | | |
| GHS | : | Globally Harmonized System | | |
| | | | | |

Sikafloor®-390 ECF N Part A

Revision Date: 17.04.2023 Date of last issue: 19.03.2021



| IATA IMDG LD50 | International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
|----------------------|--|
| LC50 | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : Occupational Exposure Limit |
| PBT | : Persistent, bioaccumulative and toxic |
| PNEC | : Predicted no effect concentration |
| REACH | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency |
| SVHC vPvB | Substances of Very High Concern Very persistent and very bioaccumulative |

Version 2.0

Further information

| Classification of the mi | Classification procedure: | |
|--------------------------|---------------------------|--------------------|
| Skin Irrit. 2 | H315 | Calculation method |
| Eye Dam. 1 | H318 | Calculation method |
| Skin Sens. 1 | H317 | Calculation method |
| Muta. 2 | H341 | Calculation method |
| Repr. 1B | H360F | Calculation method |
| Aquatic Chronic 2 | H411 | Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN