

Revision Date: 27.11.2024 Date of last issue: 20.09.2023 Version 8.0

Print Date 27.11.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikafloor®-160 Part A

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

#### **1.4 Emergency telephone number**

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

## **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 127	72/2008)
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360F: May damage fertility.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-160 Part A



Revision Date: 27.11.2024 Date of last issue: 20.09.2023 Version 8.0

Print Date 27.11.2024

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H315 H317 H319 H360F H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility. Toxic to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b> P201 P261 P273 P280	Obtain special instructions before use. Avoid breathing mist or vapours. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		<b>Response:</b> P308 + P313	3 IF exposed or concerned: Get medical ad- vice/ attention.
		P391	Collect spillage.

#### Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Reaction mass of isomers of epoxy resin BFDGE benzyl alcohol

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 27.11.2024 Date of last issue: 20.09.2023 Version 8.0

Print Date 27.11.2024

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 %	>= 60 - < 80
		limit Skin Irrit. 2; H315 >= 5 %	
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	>= 5 - < 10
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 5 - < 10
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317	>= 2,5 - < 5
		Acute toxicity esti- mate	
		Acute oral toxicity: 1.200 mg/kg	

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice

: Move out of dangerous area.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-160 Part A



Revision Date: 27.11.2024 Version 8.0 Print Date 27.11.2024 Date of last issue: 20.09.2023 Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled Move to fresh air. • Consult a physician after significant exposure. In case of skin contact : Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eve wide open while rinsing. If eye irritation persists, consult a specialist. If swallowed Do not induce vomiting without medical advice. : Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Symptoms Allergic reactions Excessive lachrymation Ervthema Dermatitis See Section 11 for more detailed information on health effects and symptoms. Risks : Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May damage fertility. irritant effects sensitising effects toxic effects for reproduction 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-160 Part A



Revision Date: 27.11.2024 Date of last issue: 20.09.2023		Version 8.0	Print Date 27.11.2024
5.2 Special hazards arising from t	the	substance or mixture	
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter dra courses.	ins or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	j apparatus.
Further information	:	Collect contaminated fire extinguishing water sep must not be discharged into drains. Fire residues and contaminated fire extinguishing be disposed of in accordance with local regulatio	g water must

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures					
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.			
6.2 Environmental precautions					
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.			
6.3 Methods and material for cont	tai	nment and cleaning up			
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.			

## 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8).
		Do not get in eyes, on skin, or on clothing.
		For personal protection see section 8.
		Persons with a history of skin sensitisation problems or asth-
		ma, allergies, chronic or recurrent respiratory disease should
		not be employed in any process in which this mixture is being

Sikafloor®-160 Part A



Revision Date: 27.11.2024 Version 8.0 Print Date 27.11.2024 Date of last issue: 20.09.2023 used. Smoking, eating and drinking should be prohibited in the application area. Pregnant women or women of child-bearing age should not be exposed to this product. Follow standard hygiene measures when handling chemical products Advice on protection against Normal measures for preventive fire protection. 1 fire and explosion Hygiene measures Handle in accordance with good industrial hygiene and safety : practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage Keep container tightly closed in a dry and well-ventilated areas and containers place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations. Further information on stor-: No decomposition if stored and applied as directed. age stability 7.3 Specific end use(s) Specific use(s) Consult most current local Product Data Sheet prior to any use.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
benzyl alcohol	100-51-6	TWA	5 ppm 22 mg/m3	CH SUVA
	as vapor and a stances, which additional skin only inhalation Safety and He	ation: The substance aerosol, Toxic by sk a are easily absored resoption a substan by the airways., Na alth, Harm to the ur -value is respected	in resorption poss through the skin, ncial higher risk co ational Institute for	ible; Sub- can give by ompared to Occupational



Revision Date: 27.11.2024 Date of last issue: 20.09.2023 Version 8.0

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipmen	t
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	<ul> <li>Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.</li> <li>Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (&gt; 0,1 mm)</li> <li>Contaminated gloves should be removed.</li> <li>Suitable for permanent exposure:</li> <li>Viton gloves (0.4 mm),</li> <li>breakthrough time &gt;30 min.</li> </ul>
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Environmental exposure cont	ols
General advice	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

# Sikafloor<sup>®</sup>-160 Part A



Revision Date: 27.11.2024 Date of last issue: 20.09.2023		Version 8.0	Print Date 27.11.2024
Physical state Appearance Colour	:	liquid viscous liquid yellow	
Odour	:	aromatic	
Melting point/ range / Freez- ing point	:	No data available	
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	plosive limits	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 101 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	ca. 7 Concentration: 100 %	
Viscosity			
Viscosity, dynamic	:	900 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Country CH 10000000556			0 / 17



Revision Date: 27.11.2024 Date of last issue: 20.09.2023	Version 8.0	Print Date 27.11.2024
Density	: ca. 1,1 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
<b>9.2 Other information</b> No data available		
SECTION 10: Stability and r	eactivity	
10.1 Reactivity	up upder conditions of normal upo	

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

## 10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	--

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### **10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Components:

#### bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

·

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-160 Part A



evision Date: 27.11.2024 ate of last issue: 20.09.2023		Version 8.0	Print Date 27.11.20
Acute dermal toxicity	: L	D50 Dermal (Rabbit): > 5.000 mg/kg	
oxirane, mono[(C12-14-all	kyloxy)r	nethyl] derivs.:	
Acute oral toxicity	: L	D50 Oral (Rat): > 5.000 mg/kg	
benzyl alcohol:			
Acute oral toxicity	Ν	cute toxicity estimate: 1.200 mg/kg lethod: Acute toxicity estimate accordin lo. 1272/2008	g to Regulation (EC)
	L	D50 Oral (Rat): 1.200 mg/kg	
Skin corrosion/irritation Causes skin irritation.			
Serious eye damage/eye i Causes serious eye irritatio		1	
Respiratory or skin sensit	tisation		
<b>Skin sensitisation</b> May cause an allergic skin	reaction.		
Respiratory sensitisation Not classified due to lack of	data.		
Germ cell mutagenicity Not classified due to lack of	data.		
<b>Carcinogenicity</b> Not classified due to lack of	data.		
<b>Reproductive toxicity</b> May damage fertility.			
STOT - single exposure Not classified due to lack of	data.		
STOT - repeated exposure Not classified due to lack of			
Aspiration toxicity Not classified due to lack of	data.		
.2 Information on other haza	ards		
Endocrine disrupting pro	perties		
Product:			
Assessment	е	he substance/mixture does not contain red to have endocrine disrupting proper REACH Article 57(f) or Commission Dele	rties according to



Sikafloor<sup>®</sup>-160 Part A

Revision Date: 27.11.2024 Date of last issue: 20.09.2023 Version 8.0

Print Date 27.11.2024

levels of 0.1% or higher.

### **SECTION 12: Ecological information**

12.1 Toxicity

# Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:						
Toxicity to fish :	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h					
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h					
Reaction mass of isomers of e	poxy resin BFDGE:					
Toxicity to fish :	LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l Exposure time: 96 h					
Toxicity to daphnia and other : aquatic invertebrates	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h					
Toxicity to algae/aquatic : plants	EC50 (algae): 1,8 mg/l Exposure time: 72 h					
benzyl alcohol:						
-	LC50 (Fish): > 100 mg/l Exposure time: 96 h					
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h					

## 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..



Revision Date: 27.11.2024 Date of last issue: 20.09.2023 Version 8.0

Print Date 27.11.2024

#### 12.6 Endocrine disrupting properties

Product:		
Assessment	:	The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible.
		Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
		Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
		Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland VeVA/LVA	:	08 01 11 [S] Paint and varnish waste containing organic solvents or other hazardous substances

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADR	:	UN 3082
IMDG	:	UN 3082
ΙΑΤΑ	:	UN 3082


### 14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-160 Part A



Revision Date: 27.11.2024 Date of last issue: 20.09.2023		Version 8.0	Print Date 27.11.202		
ADR	:	ENVIRONMENTALLY HAZARDOUS SUI N.O.S. (epoxy resin)	BSTANCE, LIQUID,		
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)			
ΙΑΤΑ	:	Environmentally hazardous substance, lic (epoxy resin)	quid, n.o.s.		
14.3 Transport hazard class(es)					
		Class Subsidiary risks			
ADR	:	9			
IMDG	:	9			
ΙΑΤΑ	:	9			
14.4 Packing group					
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III M6 90 9 (-)			
IMDG Packing group Labels EmS Code	:	III 9 F-A, S-F			
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	964 Y964 III Miscellaneous			
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ)	:	964 Y964			
Packing group	:	III Miscellaneous			
14.5 Environmental hazards					
<b>ADR</b> Environmentally hazardous	:	yes			
IMDG Marine pollutant	:	yes			
, IATA (Passenger) Environmentally hazardous	:	yes			





Revision Date: 27.11.2024 Date of last issue: 20.09.2023 Version 8.0

#### IATA (Cargo)

Environmentally hazardous : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:	All substances contained in our Products are		
	- registered by our upstream suppliers, and/or		

- registered by us, and/or

- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)		Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 30: oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
		Number on list 75:
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable



Revision Date: 27.11.2024 Date of last issue: 20.09.2023

PIC Ordinance, ChemPICO (814.82)

Version 8.0

: Not applicable

Print Date 27.11.2024

52)	
Major Accidents Iajor Accidents Ordi-	: 20.000 kg
should be co Annex 1.11 I O 814.201) obviously hazardous to	Dangerous liquid substances
(VOCV)	ax for volatile organic compounds unds (VOC) content: 4,32% w/w
emissions (integrated p	of 24 November 2010 on industrial pollution prevention and control) unds (VOC) content: 4,32% w/w
	Major Accidents lajor Accidents Ordi- lace : Conditions of should be conditions of Annex 1.11 (20) 20) 814.201) obviously hazardous to Classification according Law on the incentive ta (VOCV) Volatile organic composition Directive 2010/75/EU of emissions (integrated points)

#### Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

The product belongs to group 1 according to the Swiss Chemicals Ordinance (ChemO 813.11).

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.



Revision Date: 27.11.2024 Date of last issue: 20.09.2023 Version 8.0

Print Date 27.11.2024

## **SECTION 16: Other information**

Full text of H-Statements		
H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332		Harmful if inhaled.
H360F	:	May damage fertility.
H411	÷	Toxic to aquatic life with long lasting effects.
Full text of other abbreviat	ions	
Acute Tox.	:	Acute toxicity
Aquatic Chronic		Long-term (chronic) aquatic hazard
Eye Irrit.		Eye irritation
Repr.		Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
CH SUVA	:	Switzerland. Limit values at the work place
CH SUVA / TWA	:	
	:	Time Weighted Average
ADR	•	European Agreement concerning the International Carriage of
<b>CAO</b>		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC		Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative
Further information		
Classification of the mixtu	re:	Classification procedure:
		-
Skin Irrit. 2	Ha	Calculation method

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

# Sikafloor®-160 Part A



Revision Date: 27.11.2024 Date of last issue: 20.09.2023		Version 8.0	Print Date 27.11.2024
Eye Irrit. 2	H319	Calculation method	
Skin Sens. 1	H317	Calculation method	
Repr. 1B	H360F	Calculation method	
Aquatic Chronic 2	H411	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN