

Revision Date: 21.03.2024 Date of last issue: 10.03.2023 Version 7.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sika Boom<sup>®</sup>-162 Foam Fix Plus

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

	Product use	: Polyurethane foam
--	-------------	---------------------

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

#### **1.4 Emergency telephone number**

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure if inhaled.

Revision Date: 21.03.2024 Date of last issue: 10.03.2023 Version 7.0



2.2 Label elements

Labelling (REGULATION (E	C)	No 1272/200	8)
Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H222 H229 H315 H317 H319 H334 H335 H351 H373	Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breath- ing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure if inhaled.
Precautionary statements	:	P101 P102	If medical advice is needed, have product container or label at hand. Keep out of reach of children.
		Prevention	•
		P202	Do not handle until all safety precautions have been read and understood.
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P211	Do not spray on an open flame or other igni- tion source.
		P251	Do not pierce or burn, even after use.
		P260	Do not breathe dust or mist.
		P271	Use only outdoors or in a well-ventilated ar- ea.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P304 + P34	0 + P312 IF INHALED: Remove person to fresh
		P342 + P31	air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
		10721101	POISON CENTER/ doctor.
		Storage:	
		P405 P410 + P41	<ul> <li>Store locked up.</li> <li>Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.</li> </ul>
		Disposal:	

Print Date 12.04.2024

Revision Date: 21.03.2024 Date of last issue: 10.03.2023 Version 7.0

P501

Dispose of contents/container in accordance with local regulation.

### Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues

#### Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

### Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		(/0 11/11)
Reaction products of phosphoryl	13674-84-5	Acute Tox. 4; H302	>= 10 - < 20
trichloride and methyloxirane	237-158-7	Aquatic Chronic 3;	
	01-2119486772-26-	H412	
	XXXX		
		Acute toxicity esti-	
		mate	
		Acute oral toxicity:	
		630 mg/kg	

# Sika Boom<sup>®</sup>-162 Foam Fix Plus

Revision Date: 21.03.2024 Date of last issue: 10.03.2023 Version 7.0



Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>= 10 - < 20
Substances with a workplace exp	osure limit :		
dimethyl ether	115-10-6 204-065-8 01-2119472128-37- XXXX	Flam. Gas 1A; H220	>= 5 - < 10
isobutane	75-28-5 200-857-2 01-2119485395-27- XXXX	Flam. Gas 1A; H220	>= 5 - < 10
propane	74-98-6 200-827-9 01-2119486944-21- XXXX	Flam. Gas 1A; H220	>= 2,5 - < 5

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

General advice	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attenda	ance.
If inhaled	Move to fresh air.	
In case of skin contact	Take off contaminated clothing and shoes immedia Wash off with soap and plenty of water. If symptoms persist, call a physician.	itely.
In case of eye contact	Immediately flush eye(s) with plenty of water.	

# Sika Boom<sup>®</sup>-162 Foam Fix Plus



Revision Date: 21.03.2024 Date of last issue: 10.03.2023	Version 7.0	Print Date 12.0
	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a speciali	st.
If swallowed :	Do not induce vomiting without medical a Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unco	
4.2 Most important symptoms and	effects, both acute and delayed	
Symptoms :	Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed informa and symptoms.	tion on health effects
Risks :	irritant effects sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms of ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through pro exposure if inhaled.	-
4.3 Indication of any immediate me	dical attention and special treatment nee	eded

Treatment	: Treat symptomatically.

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Water spray jet Dry powder Foam Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet

# 5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : Carbon dioxide (CO2)

Print Date 12.04.2024

Revision Date: 21.03.2024 Date of last issue: 10.03.2023		Version 7.0	Print Date 1
ucts		Carbon monoxide Nitrogen oxides (NOx) Hydrogen cyanide (hydrocyanic acid) Chlorine compounds Bromine compounds	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained brea	thing apparatus.
Further information	:	Use water spray to cool unopened container	S.
6.1 Personal precautions, protec Personal precautions	tivo :	e equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
6.2 Environmental precautions Environmental precautions	:	Do not flush into surface water or sanitary see If the product contaminates rivers and lakes respective authorities.	
•	: tai	If the product contaminates rivers and lakes respective authorities.	
Environmental precautions	: tai	If the product contaminates rivers and lakes respective authorities.	or drains inform
Environmental precautions 6.3 Methods and material for con	: tai :	If the product contaminates rivers and lakes respective authorities. nment and cleaning up Allow to solidify, use mechanical handling ed	or drains inform

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advice on safe handling	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Take precautionary measures against static discharge.</li> <li>Open drum carefully as content may be under pressure.</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>
-------------------------	---	--

Print Date 12.04.2024

Version 7.0

Advice on protection against fire and explosion	:	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, i	incl	luding any incompatibilities
Requirements for storage areas and containers	:	BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
Diphenylmethanediisocyanate, isomeres	9016-87-9	TWA	0,02 mg/m3	CH SUVA
and homologues			(NCO)	
	Further information	ation: Sensitizers; S	Substances marke	d with an S
	can lead to ver	ry strong allergic rea	actions., Health ar	nd Safety Ex-
	ecutive (Occup	pational Medicine ar	nd Hygiene Labora	atory)
		STEL	0,02 mg/m3	CH SUVA
			(NCO)	
dimethyl ether	115-10-6	TWA	1.000 ppm	2000/39/EC
			1.920 mg/m3	
	Further information			
		TWA	1.000 ppm	CH SUVA
			1.910 mg/m3	
isobutane	75-28-5	TWA	800 ppm	CH SUVA
			1.900 mg/m3	
		STEL	3.200 ppm	CH SUVA
			7.600 mg/m3	
propane	74-98-6	STEL	4.000 ppm	CH SUVA

Country CH 10000030931



Revision Date: 21.03.2024 Date of last issue: 10.03.2023

Ver	sion	7.0

		7.200 mg/m3	
Further information Health	ation: National Instit	ute for Occupation	nal Safety and
	TWA	1.000 ppm 1.800 mg/m3	CH SUVA

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

## Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Environmental exposure co	ntro	bls
General advice	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

# Sika Boom<sup>®</sup>-162 Foam Fix Plus

Print Date 12 04 2024

Revision Date: 21.03.2024 Date of last issue: 10.03.2023		Version 7.0	Print Date 12.04.2024
Physical state Colour	:	aerosol various	
Odour	:	ether-like	
Melting point/range / Freezing point	:	No data available	
Boiling point/boiling range	:	No data available	
Flammability	:	Extremely flammable aerosol.	
Upper/lower flammability or	exp	losive limits	
Upper explosion limit / Up- per flammability limit	-		
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	Not applicable	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture reacts with water	
Viscosity			
Viscosity, kinematic	:	Not applicable	
Solubility(ies)			
Water solubility	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	5100 hPa	
Density	:	ca. 1,05 g/cm3 (23 °C)	
Relative vapour density Country CH 10000030931	:	No data available	9 / 18

## Sika Boom<sup>®</sup>-162 Foam Fix Plus

Version 7.0

Particle characteristics : No data available

#### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### **10.2 Chemical stability**

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

## 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid	: Oxidizing agents
--------------------	--------------------

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### **Components:**

### Reaction products of phosphoryl trichloride and methyloxirane:

Acute oral toxicity	:	LD50 Oral (Rat): > 630 mg/kg
		Acute toxicity estimate: 630 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): > 7 mg/l Exposure time: 4 h Test atmosphere: dust/mist



Revision Date: 21.03.2024 Version 7.0 Date of last issue: 10.03.2023 Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg Diphenylmethanediisocyanate, isomeres and homologues: : LD50 Oral (Rat): > 10.000 mg/kg Acute oral toxicity Acute inhalation toxicity LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after short term inhalation. Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye irritation Causes serious eye irritation. Respiratory or skin sensitisation Skin sensitisation May cause an allergic skin reaction. **Respiratory sensitisation** May cause allergy or asthma symptoms or breathing difficulties if inhaled. Germ cell mutagenicity Not classified due to lack of data. Carcinogenicity Suspected of causing cancer. **Reproductive toxicity** Not classified due to lack of data. STOT - single exposure May cause respiratory irritation. STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure if inhaled. Aspiration toxicity Not classified due to lack of data. 11.2 Information on other hazards Endocrine disrupting properties Product: Assessment The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

S Version 7.0



Revision Date: 21.03.2024 Date of last issue: 10.03.2023

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

#### **Components:**

### Reaction products of phosphoryl trichloride and methyloxirane:

Toxicity to algae/aquatic : plants	EC50 (Pseudokirchneriella subcapitata (green algae)): 82 Exposure time: 72 h Method: OECD Test Guideline 201			
	NOEC (Pseudokirchneriella subcapitata (green algae)): 13 mg/l Exposure time: 72 h Method: OECD Test Guideline 201			
Toxicity to daphnia and other : aquatic invertebrates (Chron- ic toxicity)	NOEC: 32 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202			
Diphenylmethanediisocyanate, isomeres and homologues:				
Toxicity to fish :	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h			
Toxicity to algae/aquatic : plants	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h			

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Revision Date: 21.03.2024 Date of last issue: 10.03.2023 Version 7.0



#### 12.6 Endocrine disrupting properties

#### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

#### Product:

Additional ecological infor- : There is no data available for this product. mation

#### **Global warming potential**

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

#### **Components:**

## propane:

20-year global warming potential: 0,072 100-year global warming potential: 0,02 500-year global warming potential: 0,006 Atmospheric lifetime: 0,036 yr Radiative efficiency: 0 Wm2ppb Further information: Miscellaneous compounds

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible.	
		Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.	
		Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.	
		Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.	
Waste code Switzerland VeVA/LVA	:	16 05 04 -	
Contaminated packaging	:	15 01 10 [S] packaging containing residues of or contaminat- ed by dangerous substances	
Country CH 10000030931		13 /	•

Revision Date: 21.03.2024 Date of last issue: 10.03.2023 Version 7.0



## **SECTION 14: Transport information**

14.1 UN number or ID number					
ADR	:	UN 1950			
IMDG	:	UN 1950			
ΙΑΤΑ	:	UN 1950			
14.2 UN proper shipping name					
ADR	:	AEROSOLS			
IMDG	:	AEROSOLS			
ΙΑΤΑ	:	Aerosols, flammable			
14.3 Transport hazard class(es)					
		Class	Subsidiary risks		
ADR	:	2	2.1		
IMDG	:	2.1			
ΙΑΤΑ	:	2.1			
14.4 Packing group					
ADR Packing group Classification Code Labels Tunnel restriction code Remarks		Not assigned by regu 5F 2.1 (D) Transport according t	ılation to chapter 3.4 (LQ) possible		
IMDG Packing group Labels EmS Code Remarks		Not assigned by regu 2.1 F-D, S-U Transport according t	ilation to chapter 3.4 (LQ) possible		
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group		203 Y203 Not assigned by regu Flammable Gas 203 Y203 Not assigned by regu			

Revision Date: 21.03.2024 Date of last issue: 10.03.2023 Version 7.0



Labels Flammable Gas • 14.5 Environmental hazards ADR Environmentally hazardous : no IMDG Marine pollutant no IATA (Passenger) Environmentally hazardous • no IATA (Cargo) Environmentally hazardous no

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

**REACH** Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75
		Diphenylmethanediisocyanate, iso- meres and homologues (Number on list 74, 56)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that de-	:	Not applicable

## Sika Boom<sup>®</sup>-162 Foam Fix Plus



Revision Date: 21.03.2024 Date of last issue: 10.03.2023	Version 7	.0	Print Date 12.04.2024	
plete the ozone layer				
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)			Not applicable	
PIC Ordinance, ChemPICO (814.82)		:	Not applicable	
Chemical Risk Reduction Ordinance (ORRChem, SR 814.81)		:	Diphenylmethanediisocyanate, iso- meres and homologues	
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS				
Volatile organic compounds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 15% w/w			
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 15% w/w			
Other regulations:				

75/324/EEC

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## **SECTION 16: Other information**

#### Full text of H-Statements

H220	: Extremely flammable gas.
H302	: Harmful if swallowed.

Revision Date: 21.03.2024 Date of last issue: 10.03.2023 Version 7.0



ale of last issue. 10.03.2023		
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul-
		ties if inhaled.
H335		May cause respiratory irritation.
	:	Suspected of causing cancer.
H351	•	
H373		May cause damage to organs through prolonged or repeated
		exposure if inhaled.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Acute Tox.	•	Acute toxicity
Aquatic Chronic		Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
	÷	
Eye Irrit.	·	Eye irritation
Flam. Gas	:	Flammable gases
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE		Specific target organ toxicity - single exposure
2000/39/EC		Europe. Commission Directive 2000/39/EC establishing a first
2000/00/20	•	list of indicative occupational exposure limit values
CH SUVA		
	•	Switzerland. Limit values at the work place
2000/39/EC / TWA		Limit Value - eight hours
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL		Derived no-effect level
EC50		Half maximal effective concentration
GHS	:	Globally Harmonized System
	÷	
IATA	·	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL		International Convention for the Prevention of Pollution from
MARFOL	•	
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC		Substances of Very High Concern
	:	
vPvB		Very persistent and very bioaccumulative

# Sika Boom<sup>®</sup>-162 Foam Fix Plus

Revision Date: 21.03.2024 Date of last issue: 10.03.2023 Version 7.0

**Classification procedure:** 



### **Further information**

## Classification of the mixture:

Aerosol 1	H222, H229	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN