

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Version 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor®-3240 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure.

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Version 5.0



2.2 Label elements

Labelling (REGULATION (Hazard pictograms	(EC) No :	o 1272/2008)	\wedge
Signal word	: [Danger	
Hazard statements	: F F F F	H315 H317 H319 H332 H334 H335 H351 H373	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through pro- longed or repeated exposure.
Precautionary statements	F F F F	Prevention: P201 P260 P264 P280 Response: P304 + P340 + P342 + P311	 Obtain special instructions before use. Do not breathe mist or vapours. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection. P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues methylenediphenyl diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikafloor[®]-3240 Part B

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Print Date 15.05.2023

Version 5.0

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H314 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 $\overline{}$ specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>= 40 - < 60

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Version 5.0



methylenediphenyl diisocyanate	26447-40-5 905-806-4 01-2119457015-45- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 \longrightarrow specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %	>= 40 - < 60
--------------------------------	--	--	--------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid me	easures
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptom	s and effects, both acute and delayed
Symptoms	: Asthmatic appearance Cough

Sikafloor[®]-3240 Part B

Revision Date: 15.05.2023

Print Date 15.05.2023

Date of last issue: 08.07.2021	Version etc	
	Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed inform and symptoms.	ation on health effects
Risks	: irritant effects sensitising effects	
	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through p exposure.	-

Version 5.0

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : T	Freat symptomatically.
---------------	------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from	the	substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Version 5.0



Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, in	nclu	uding any incompatibilities
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor-	:	No decomposition if stored and applied as directed.

Revision Date: 15.05.2023 Date of last issue: 08.07.2021

age stability

7.3 Specific end use(s)

Specific use(s)

Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

Version 5.0

SECTION 8: Exposure controls/personal protection

1

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	CH SUVA	
	Further informa	ation: Sensitizers; S	ubstances marke	d with an S	
		y strong allergic rea			
	ecutive (Occup	ational Medicine ar	nd Hygiene Labora	atory)	
		STEL	0,02 mg/m3	CH SUVA	
			(NCO)		
methylenediphenyl diisocyanate	26447-40-5	TWA	0,02 mg/m3 (NCO)	CH SUVA	
	Further information: Sensitizers; Substances marked with an S				
	can lead to very strong allergic reactions., Health and Safety Ex-				
	ecutive (Occup	ational Medicine ar	nd Hygiene Labora	atory)	
		STEL	0,02 mg/m3 (NCO)	CHSUVA	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.



Sikafloor[®]-3240 Part B

Print Date 15.05.2023

Revision Date: 15.05.2023 Date of last issue: 08.07.2021	Version 5.0	Print Date 15.
Skin and body protection	 Protective clothing (e.g. Safety shoes and long-sleeved working clothing, long trou and protective boots are additionally rec and stirring work. 	sers). Rubber aprons
Respiratory protection	 In case of inadequate ventilation wear r Respirator selection must be based on exposure levels, the hazards of the proci- ing limits of the selected respirator. Use a properly fitted NIOSH approved a respirator complying with an approved a sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < Ensure adequate ventilation. This can b exhaust extraction or by general ventila ods for determining inhalation exposure ticular to the mixing / stirring area. In can 	known or anticipated duct and the safe work- air-purifying or air-fed standard if a risk as- < 10000 ppm be achieved by local tion. (EN 689 - Meth-). This applies in par-

Environmental exposure controls

General advice	: Do not flush into surface water or sanitary sewer system.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid light brown			
Odour	:	musty			
Melting point/range / Freezing point	:	No data available			
Boiling point/boiling range	:	No data available			
Flammability (solid, gas)	:	No data available			
Upper/lower flammability or explosive limits					

Upper explosion limit / Up- : No data available



Revision Date: 15.05.2023 Date of last issue: 08.07.2021		Version 5.0	Print Date 15.05.20
per flammability limit			
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 150 °C Method: open cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity			
Viscosity, dynamic	:	70 - 90 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	ca. 1,18 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Version 5.0



10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous re	actio	ons
Hazardous reactions	:	No hazards to be specially mentioned.
10.4 Conditions to avoid Conditions to avoid	:	No data available
10.5 Incompatible materials		

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity	:	LD50 Oral (Rat): > 10.000 mg/kg
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after short term inhalation.
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 9.400 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Revision Date: 15.05.2023 Date of last issue: 08.07.2021

Version 5.0



Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Version 5.0



12.5 Results of PBT and vPvB assessment

Product:

mation

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:		
Assessment :		The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects		
Product:		
Additional ecological infor-	:	There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: The generation of waste should be avoided or minimized wherever possible.
	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland VeVA/LVA	: 08 01 11 -
Contaminated packaging	: 15 01 10 [S] packaging containing residues of or contaminat- ed by dangerous substances

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Version 5.0



SECTION 14: Transport information

14.1 UN number or ID number					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.2 UN proper shipping name					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.3 Transport hazard class(es)					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.4 Packing group					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
IATA (Cargo)	:	Not regulated as a dangerous good			
IATA (Passenger)	:	Not regulated as a dangerous good			
14.5 Environmental hazards					
Not regulated as a dangerous good					
14.6 Special precautions for user					

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

: Conditions of restriction for the following entries should be considered: Number on list 75, 3

Diphenylmethanediisocyanate, isomeres and homologues (Number on

Sikafloor[®]-3240 Part B



Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Version 5.0

			list 74, 56) methylenediphenyl diisocyanate (Number on list 74, 56)		
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors		:	Not applicable		
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).		:	None of the components are listed (=> 0.1 %).		
REACH - List of substances subject to authorisation (Annex XIV)		:	Not applicable		
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer		:	Not applicable		
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)		:	Not applicable		
PIC Ordinance, ChemPICO (814.82)		:	Not applicable		
REACH Information:	EACH Information: - registered by our upstr - registered by us, and/o - excluded from the registered from		im suppliers, and/or tion, and/or		
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma- jor-accident hazards involving dangerous substances. Not applicable					
Water hazard class (Germa- : ny)	WGK 1 slightly hazardous to water Classification according to AwSV, Annex 1 (5.2)				
Volatile organic compounds : Law on the incentive ta (VOCV) no VOC duties		ax fo	or volatile organic compounds		

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Sikafloor[®]-3240 Part B

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Print Date 15.05.2023

Version 5.0

vant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

Full lext of H-Statements			
H315	:	Causes skin irritation.	
H317	:	May cause an allergic skin reaction.	
H319	:	Causes serious eye irritation.	
H332	:	Harmful if inhaled.	
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.	
H335	:	May cause respiratory irritation.	
H351	:	Suspected of causing cancer.	
H373	:	May cause damage to organs through prolonged or repeated exposure.	
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.	
Full text of other abbreviation	ons		
Acute Tox.	:	Acute toxicity	
Carc.	:	Carcinogenicity	
Eye Irrit.	:	Eye irritation	
Resp. Sens.	:	Respiratory sensitisation	
Skin Irrit.	:	Skin irritation	
Skin Sens.	:	Skin sensitisation	
STOT RE	:	Specific target organ toxicity - repeated exposure	
STOT SE	:	Specific target organ toxicity - single exposure	
CH SUVA	:	Switzerland. Limit values at the work place	
CH SUVA / TWA	:	Time Weighted Average	
CH SUVA / STEL	:	Short Term Exposure Limit	
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road	
CAS	:	Chemical Abstracts Service	
DNEL	:	Derived no-effect level	
EC50	:	Half maximal effective concentration	
GHS	:	Globally Harmonized System	
ΙΑΤΑ	:	International Air Transport Association	
IMDG	:	International Maritime Code for Dangerous Goods	
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)	
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation	

Revision Date: 15.05.2023 Date of last issue: 08.07.2021 Version 5.0



MARPOL	period) International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN