



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Sikafloor®-18 Pronto

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Acrylate coating, Product is not intended for consumer use

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Schweiz AG  
Tüffenwies 16  
8048 Zürich  
Telephone : +41 58 436 40 40  
Telefax : -  
E-mail address of person : EHS@ch.sika.com  
responsible for the SDS

### 1.4 Emergency telephone number

Tox Info Suisse  
CH-8028 Zurich  
+41(0)44 251 51 51 / Speed calling: 145

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Respiratory system H335: May cause respiratory irritation.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger



Hazard statements	:	H225	Highly flammable liquid and vapour.
		H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H335	May cause respiratory irritation.
Precautionary statements	:	<b>Prevention:</b>	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P233	Keep container tightly closed.
		P261	Avoid breathing mist or vapours.
		P264	Wash skin thoroughly after handling.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
		<b>Response:</b>	
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Hazardous components which must be listed on the label:**

methyl methacrylate  
2-ethylhexyl acrylate  
tetramethylene dimethacrylate  
2-(N-methyl-p-toluidino)ethanol

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
methyl methacrylate	80-62-6 201-297-1 01-2119452498-28-XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system)	>= 40 - < 60
2-ethylhexyl acrylate	103-11-7 203-080-7 01-2119453158-37-XXXX	Skin Irrit. 2; H315 Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412	>= 5 - < 10
tetramethylene dimethacrylate	2082-81-7 218-218-1 01-2119967415-30-XXXX	Skin Sens. 1B; H317	>= 1 - < 2,5
2-(N-methyl-p-toluidino)ethanol	2842-44-6 220-638-5 01-2120827830-56-XXXX	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,25 - < 0,5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.



Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Cough  
Respiratory disorder  
Allergic reactions  
Erythema  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
sensitising effects
- Causes skin irritation.  
May cause an allergic skin reaction.  
May cause respiratory irritation.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide
- No hazardous combustion products are known

#### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use water spray to cool unopened containers.



---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.



Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

**7.3 Specific end use(s)**

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU
		Further information: Indicative		
		STEL	100 ppm	2009/161/EU
		TWA	50 ppm 210 mg/m3	CH SUVA
		Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected		
		STEL	100 ppm 420 mg/m3	CH SUVA
2-ethylhexyl acrylate	103-11-7	TWA	5 ppm 38 mg/m3	CH SUVA
		Further information: The substance can be present simultaneously as vapor and aerosol, Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Harm to the unborn child is not to be expected when the OEL-value is respected		
		STEL	5 ppm 38 mg/m3	CH SUVA



\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## 8.2 Exposure controls

### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
organic vapor filter (Type A)  
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm  
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

- General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties



Physical state	: liquid
Colour	: various
Odour	: unpleasant
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: ca. 100 °C
Flammability (solid, gas)	: No data available

**Upper/lower flammability or explosive limits**

Upper explosion limit / Upper flammability limit	: Upper flammability limit 12,5 %(V)
Lower explosion limit / Lower flammability limit	: Lower flammability limit 0,8 %(V)
Flash point	: ca. 10 °C Method: closed cup
Auto-ignition temperature	: ca. 245 °C
Decomposition temperature	: No data available
pH	: Not applicable substance/mixture is non-soluble (in water)

**Viscosity**

Viscosity, dynamic	: ca. 250 mPa.s (20 °C)
Viscosity, kinematic	: > 20,5 mm <sup>2</sup> /s (40 °C)

**Solubility(ies)**

Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Vapour pressure	: ca. 38,7 hPa





Density : ca. 0,98 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

## 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **methyl methacrylate:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 29,8 mg/l  
Exposure time: 4 h

---



Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

**2-ethylhexyl acrylate:**

Acute oral toxicity : LD50 Oral (Rat): 4.435 mg/kg

**2-(N-methyl-p-toluidino)ethanol:**

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Not classified due to lack of data.

**Respiratory or skin sensitisation**

**Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified due to lack of data.

**Germ cell mutagenicity**

Not classified due to lack of data.

**Carcinogenicity**

Not classified due to lack of data.

**Reproductive toxicity**

Not classified due to lack of data.

**STOT - single exposure**

May cause respiratory irritation.

**STOT - repeated exposure**

Not classified due to lack of data.

**Aspiration toxicity**

Not classified due to lack of data.

**11.2 Information on other hazards**

**Endocrine disrupting properties**

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **methyl methacrylate:**

- Toxicity to fish : NOEC (Danio rerio (zebra fish)): 9,4 mg/l
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 69 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- NOEC : 37 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 202

- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 37 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

##### **2-ethylhexyl acrylate:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,81 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,3 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 1,71 mg/l  
Exposure time: 72 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

- Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

#### Product:



Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste code Switzerland VeVA/LVA : 08 01 11 -

Contaminated packaging : 15 01 10 [S] packaging containing residues of or contaminated by dangerous substances

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 1247  
IMDG : UN 1247  
IATA : UN 1247

### 14.2 UN proper shipping name

ADR : METHYL METHACRYLATE MONOMER, STABILIZED  
IMDG : METHYL METHACRYLATE, MONOMER, STABILIZED



**IATA** : Methyl methacrylate monomer, stabilized

**14.3 Transport hazard class(es)**

	Class	Subsidiary risks
<b>ADR</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

**14.4 Packing group**

**ADR**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 339  
Labels : 3  
Tunnel restriction code : (D/E)

**IMDG**  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-D

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

**14.5 Environmental hazards**

**ADR**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

**IATA (Passenger)**  
Environmentally hazardous : no

**IATA (Cargo)**  
Environmentally hazardous : no

**14.6 Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 75, 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

PIC Ordinance, ChemPICO (814.82) : Not applicable

Chemical Risk Reduction Ordinance (ORRChem, SR 814.81) : See respective Annex to the Chemical Risk Reduction Ordinance (ORRChem, 814.81) for Conditions of Restriction.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: < 0,01% w/w  
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)



Volatile organic compounds (VOC) content: < 0,01% w/w

**Other regulations:**

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

**15.2 Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

**SECTION 16: Other information**

**Full text of H-Statements**

H225 : Highly flammable liquid and vapour.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H335 : May cause respiratory irritation.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

**Full text of other abbreviations**

Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
STOT SE : Specific target organ toxicity - single exposure  
2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC  
  
CH SUVA : Switzerland. Limit values at the work place  
2009/161/EU / TWA : Limit Value - eight hours  
2009/161/EU / STEL : Short term exposure limit  
CH SUVA / TWA : Time Weighted Average  
CH SUVA / STEL : Short Term Exposure Limit  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at



	once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

**Further information**

**Classification of the mixture:**

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Skin Sens. 1	H317
STOT SE 3	H335

**Classification procedure:**

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

CH / EN