

Revision Date: 08.01.2025 Date of last issue: 19.01.2022 Version 7.0

Print Date 08.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaGard®-6060

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Corrosion protection

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12	
Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.
Label elements	
Labelling (REGULATION (EC) No 1272/20	008)
Hazard pictograms :	! ***

Signal word

2.2

Danger

1

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaGard®-6060



Revision Date: 08.01.2025 Date of last issue: 19.01.2022			V	ersion 7.0	Print Date 08.01.2025
Hazard statements	:	H225 H336 H411	Ma	hly flammable liquid and vapour. y cause drowsiness or dizziness. ic to aquatic life with long lasting	
Supplemental Hazard Statements	:	EUH066		Repeated exposure may cause or cracking.	skin dryness
Precautionary statements	:	Prevention	:		
		P210		Keep away from heat, hot surfa open flames and other ignition s smoking.	· •
		P233		Keep container tightly closed.	
		P261		Avoid breathing mist or vapours	
		P273		Avoid release to the environme	nt.
		Response:			
		P370 + P37	78	In case of fire: Use dry sand, dr alcohol-resistant foam to exting	
		P391		Collect spillage.	

Hazardous components which must be listed on the label:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaGard®-6060



Revision Date: 08.01.2025 Date of last issue: 19.01.2022 Version 7.0

Print Date 08.01.2025

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Not Assigned 920-750-0 01-2119473851-33- XXXX [corresponding group CAS 64742-49- 0]	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 25 - < 40
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [corresponding group CAS 64742-95- 6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 2,5 - < 5
propylene carbonate	108-32-7 203-572-1 01-2119537232-48- XXXX	Eye Irrit. 2; H319	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaGard®-6060



Version 7.0	Print Date 08.01.2025
 Do not induce vomiting without medical are Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an uncom 	
and effects, both acute and delayed	
: Erythema Loss of balance Vertigo See Section 11 for more detailed informat and symptoms.	tion on health effects
: No known significant effects or hazards.	
May cause drowsiness or dizziness. Repeated exposure may cause skin dryne	ess or cracking.
	 Do not induce vomiting without medical a Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unco and effects, both acute and delayed Erythema Loss of balance Vertigo See Section 11 for more detailed informa and symptoms. No known significant effects or hazards. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Treat symptomatically
rieauneni	. near symptomatical

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 SikaGard®-6060

Jika®

Revision Date: 08.01.2025Version 7.0Print Date 08.01.2025Date of last issue: 19.01.2022

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaGard®-6060



Revision Date: 08.01.2025 Date of last issue: 19.01.2022	Version 7.0	Print Date 08.01.2025			
Hygiene measures	: Handle in accordance with good indust practice. When using do not eat or drin smoke. Wash hands before breaks and	k. When using do not			
7.2 Conditions for safe storage, including any incompatibilities					
Requirements for storage areas and containers	: Store in cool place. Containers which a carefully resealed and kept upright to p in accordance with local regulations.	•			
Further information on stor- age stability	: No decomposition if stored and applied	l as directed.			
7.3 Specific end use(s)					
Specific use(s)	: Consult most current local Product Dat use.	a Sheet prior to any			

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
propylene carbonate	108-32-7	STEL	6 ppm	CH SUVA
			25,5 mg/m3	
	Further infor	mation: Harm to the ι	unborn child is not	to be ex-
	pected when	the OEL-value is res	spected	
		TWA	6 ppm	CH SUVA
			25,5 mg/m3	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaGard®-6060



Revision Date: 08.01.2025 Date of last issue: 19.01.2022		Version 7.0	Print Date 08.01.2025
		Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. long-sleeved working clothing, long trouser and protective boots are additionally recom and stirring work.	rs). Rubber aprons
Respiratory protection	:	In case of inadequate ventilation wear resp Respirator selection must be based on kno exposure levels, the hazards of the product ing limits of the selected respirator. organic vapor (Type A) and particulate filte A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10 P1: Inert material; P2, P3: hazardous subs Ensure adequate ventilation. This can be a exhaust extraction or by general ventilation ods for determining inhalation exposure). T ticular to the mixing / stirring area. In case to keep the concentrations under the occup limits then respiration protection measures	own or anticipated et and the safe work- er 0000 ppm tances achieved by local n. (EN 689 - Meth- This applies in par- this is not sufficent pational exposure

Environmental exposure controls

General advice	: Prevent product from entering drains.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid black
Odour	:	solvent-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	106 °C
Flammability (solid, gas)	:	No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : Upper flammability limit

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaGard®-6060



Revision Date: 08.01.2025 Date of last issue: 19.01.2022		Version 7.0	Print Date 08.01.2025
per flammability limit		ca. 7,0 %(V)	
Lower explosion limit / Lower flammability limit	:	Lower flammability limit ca. 0,6 %(V)	
Flash point	:	ca. 6 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity Viscosity, dynamic	:	4.500 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	ca. 20 hPa (20 °C)	
Density	:	ca. 1,09 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available



Revision Date: 08.01.2025 Date of last issue: 19.01.2022	Version 7.0	Print Date 08.01.2025	
SECTION 10: Stability and re	activity		
10.1 Reactivity No dangerous reaction know	n under conditions of normal use.		
10.2 Chemical stability The product is chemically sta	ble.		
10.3 Possibility of hazardous re	actions		
Hazardous reactions		Stable under recommended storage conditions.	
	Vapours may form explosive mixture with a	air.	
10.4 Conditions to avoid			
Conditions to avoid	: Heat, flames and sparks.		
10.5 Incompatible materials			
Materials to avoid	: No data available		
10.6 Hazardous decomposition	products		
	: No hazardous decomposition products are	e known.	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity :	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 23,3 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity :	:	LD50 Dermal (Rabbit): > 2.800 mg/kg
Hydrocarbons, C9, aromatics	:	
Acute oral toxicity :	:	LD50 Oral (Rat): > 2.000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaGard®-6060



Revision Date: 08.01.2025 Date of last issue: 19.01.2022	Version 7.0	Print Date 08.01.2025
Skin corrosion/irritation		
Repeated exposure may cause	e skin dryness or cracking.	
Components:		
Hydrocarbons, C9, aromatics	:	
Assessment	: Repeated exposure may cause skin dr	ryness or cracking.
Serious eye damage/eye irrit	ation	
Not classified due to lack of da	a.	
Respiratory or skin sensitisa	tion	
Skin sensitisation		
Not classified due to lack of da	a.	
Respiratory sensitisation		
Not classified due to lack of da	a.	
Germ cell mutagenicity		
Not classified due to lack of da	a.	
Carcinogenicity		
Not classified due to lack of da	a.	
Reproductive toxicity Not classified due to lack of da		
	la.	
STOT - single exposure May cause drowsiness or dizzi	ness	
STOT - repeated exposure		
Not classified due to lack of da	a.	
Aspiration toxicity		
Not classified due to lack of da	a.	
1.2 Information on other hazards	5	
Endocrine disrupting proper	ies	
Product:		
Assessment	: The substance/mixture does not contain ered to have endocrine disrupting prop	

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 08.01.2025 Date of last issue: 19.01.2022 Version 7.0

Print Date 08.01.2025

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

- Toxicity to fish
- : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13,4 mg/l Exposure time: 96 h

Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic	:	(Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9
plants		mg/l
		Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment
Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.



Revision Date: 08.01.2025 Date of last issue: 19.01.2022 Version 7.0

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland	: 08 01 11 [S] Paint and varnish waste containing organic sol-
VeVA/LVA	vents or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	UN 1139	
IMDG	:	UN 1139	
ΙΑΤΑ	:	UN 1139	
14.2 UN proper shipping name	9		
ADR	:	COATING SOLUTIO	N
IMDG	:	COATING SOLUTION	N
ΙΑΤΑ	:	Coating solution	
	••		
14.3 Transport hazard class(es	<i>>)</i>		
14.3 Transport nazard class(es	>)	Class	Subsidiary risks
ADR	>) :		Subsidiary risks
	-	3	Subsidiary risks
ADR	:	3	Subsidiary risks
ADR IMDG	:	3 3	Subsidiary risks

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

SikaGard®-6060

Sika®

Revision Date: 08.01.2025 Date of last issue: 19.01.2022		Version 7.0	Print Date 08.01.2025
Labels Tunnel restriction code	:	3 (D/E)	
IMDG Packing group Labels EmS Code	:	II 3 F-E, <u>S-E</u>	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	364 Y341 II Flammable Liquids	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	353 Y341 II Flammable Liquids	
14.5 Environmental hazards			
ADR Environmentally hazardous	:	yes	
IMDG Marine pollutant	:	yes	
IATA (Passenger) Environmentally hazardous	:	yes	

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:	All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or
Ountry CH 10000001331	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 SikaGard®-6060



Revision Date: 08.01.2025 Date of last issue: 19.01.2022	Version 7.0		Print Date 08.01.2025					
- exempted from the registration.								
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)			Conditions of restriction for the fol- lowing entries should be considered: Number on list 3					
			Number on list 75:					
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).					
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable					
Regulation (EC) on substances th layer	at deplete the ozone	:	Not applicable					
Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu-	:	Not applicable					
PIC Ordinance, ChemPICO (814.	82)	:	Not applicable					
Ordinance on Protection against I Threshold quantity according to M nance (MAO 814.012)		:	20.000 kg					
Chemical Risk Reduction Ordinar (ORRChem, SR 814.81)	should be co	onsi	estriction for the following annexes idered: ngerous liquid substances					
Waters Protection Ordinance (WF Water pollution class :		o wa	ater					
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 34,8% w/w					
	emissions (integrated p	coll	4 November 2010 on industrial ution prevention and control) ds (VOC) content: 34,8% w/w					

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Revision Date: 08.01.2025 Date of last issue: 19.01.2022

SikaGard[®]-6060

Version 7.0

Print Date 08.01.2025

and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements		
H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H319	:	Causes serious eye irritation.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
STOT SE	:	Specific target organ toxicity - single exposure
CH SUVA	:	Switzerland. Limit values at the work place
CH SUVA / TWA	÷	Time Weighted Average
CH SUVA / STEL ADR	÷	Short Term Exposure Limit
ADR	•	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation period)
MARPOL		International Convention for the Prevention of Pollution from
MARFOL	•	Ships, 1973 as modified by the Protocol of 1978
OEL		Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	÷	Predicted no effect concentration
REACH	÷	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

H411

SikaGard®-6060



Revision Date: 08.01.2025 Date of last issue: 19.01.202	22	Version 7.0	Print Date 08.01.2025
SVHC vPvB Further information	: Substances	H), establishing a Europear of Very High Concern ent and very bioaccumulati	<u> </u>
Classification of the	mixture:	Classificatior	n procedure:
Flam. Liq. 2	H225	Based on proc	luct data or assessment
STOT SE 3	H336	Calculation me	ethod

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN

Aquatic Chronic 2