

Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Version 11.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name

: Sikafloor®-376 Part A

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use	: Polyurethane coating

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

#### **1.4 Emergency telephone number**

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)Skin sensitisation, Category 1H317: May cause an allergic skin reaction.Long-term (chronic) aquatic hazard, Category 2H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H317 H411	May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

## Sikafloor<sup>®</sup>-376 Part A

Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Version 11.0



Precautionary statements	:	<b>Prevention:</b> P261 P273 P280	Avoid breathing mist or vapours. Avoid release to the environment. Wear protective gloves.
		Response:	
		P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
		P362 + P364	Take off contaminated clothing and wash it before reuse.
		P391	Collect spillage.

#### Hazardous components which must be listed on the label:

6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine

#### **Additional Labelling**

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 28.02.2024 Date of last issue: 05.07.2022



Version 11.0

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
6-methyl-2,4- bis(methylthio)phenylene-1,3- diamine	106264-79-3 403-240-8 01-0000015292-76- XXXX	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Acute toxicity esti- mate Acute oral toxicity: 1.515 mg/kg	>= 10 - < 20
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [corresponding group CAS 64742-95- 6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 2,5 - < 5
N-methyl-2-pyrrolidone	872-50-4 212-828-1 01-2119472430-46- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 1B; H360D STOT SE 3; H335 (Respiratory system) 	>= 0,1 - < 0,3

For explanation of abbreviations see section 16.

:

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

# Sikafloor®-376 Part A



Revision Date: 28.02.2024 Date of last issue: 05.07.2022	Version 11.0	Print Date 28.02.20
If inhaled	: Move to fresh air. Consult a physician after significar	nt exposure.
In case of skin contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.	
In case of eye contact	: Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a s	
If swallowed	<ul> <li>Do not induce vomiting without medical advice.</li> <li>Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>	
4.2 Most important symptoms and	d effects, both acute and delayed	
Symptoms	: Allergic reactions See Section 11 for more detailed i and symptoms.	information on health effects
Risks	: sensitising effects	
	May cause an allergic skin reactio	n.
4.3 Indication of any immediate m	May cause an allergic skin reaction nedical attention and special treatm	
<b>4.3 Indication of any immediate n</b> Treatment		
-	nedical attention and special treatm : Treat symptomatically.	
Treatment SECTION 5: Firefighting meas	nedical attention and special treatm : Treat symptomatically.	
Treatment	nedical attention and special treatm : Treat symptomatically. ures	ray/water jet/carbon diox-
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media	<ul> <li>inedical attention and special treatment</li> <li>Treat symptomatically.</li> <li>ures</li> <li>In case of fire, use water/water spide/sand/foam/alcohol resistant for extinction.</li> </ul>	ray/water jet/carbon diox-
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media	<ul> <li>inedical attention and special treatment</li> <li>Treat symptomatically.</li> <li>ures</li> <li>In case of fire, use water/water spide/sand/foam/alcohol resistant for extinction.</li> </ul>	ray/water jet/carbon diox- am/chemical powder for
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from the Specific hazards during fire- fighting	<ul> <li>inedical attention and special treatment</li> <li>Treat symptomatically.</li> <li>ures</li> <li>In case of fire, use water/water spide/sand/foam/alcohol resistant for extinction.</li> <li>ine substance or mixture</li> <li>Do not allow run-off from fire fighting</li> </ul>	ray/water jet/carbon diox- am/chemical powder for
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from the Specific hazards during fire- fighting Hazardous combustion prod-	<ul> <li>inedical attention and special treatment</li> <li>Treat symptomatically.</li> <li>in case of fire, use water/water spide/sand/foam/alcohol resistant for extinction.</li> <li>ine substance or mixture</li> <li>Do not allow run-off from fire fighticourses.</li> </ul>	ray/water jet/carbon diox- am/chemical powder for
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from the Specific hazards during fire- fighting Hazardous combustion prod- ucts	<ul> <li>inedical attention and special treatment</li> <li>Treat symptomatically.</li> <li>ures</li> <li>In case of fire, use water/water spin ide/sand/foam/alcohol resistant for extinction.</li> <li>ine substance or mixture</li> <li>Do not allow run-off from fire fightic courses.</li> <li>No hazardous combustion product</li> </ul>	ray/water jet/carbon diox- am/chemical powder for
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from the Specific hazards during fire- fighting Hazardous combustion prod- ucts 5.3 Advice for firefighters Special protective equipment	<ul> <li>inedical attention and special treatment</li> <li>Treat symptomatically.</li> <li>ures</li> <li>In case of fire, use water/water spin ide/sand/foam/alcohol resistant for extinction.</li> <li>ine substance or mixture</li> <li>Do not allow run-off from fire fightic courses.</li> <li>No hazardous combustion product</li> </ul>	ent needed

Revision Date: 28.02.2024 Date of last issue: 05.07.2022



Version 11.0

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective	e equipment and emergency procedures
Personal precautions :	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions	
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for contai	nment and cleaning up
Methods for cleaning up :	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Follow standard hygiene measures when handling chemical products</li> </ul>
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.



Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Version 11.0

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
N-methyl-2-pyrrolidone	872-50-4	TWA	10 ppm 40 mg/m3	2009/161/EU
		mation: Identifies the skin, Indicative	possibility of signi	ificant uptake
		STEL	20 ppm 80 mg/m3	2009/161/EU
		STEL	40 ppm 160 mg/m3	CH SUVA
	stances, whi additional sk only inhalatio de Sécurité p maladies pro	aerosol, Toxic by sk ch are easily absored in resoption a substa on by the airways., In our la prévention de ofessionnelles, Harm en the OEL-value is	I through the skin, ncial higher risk c stitut National de l s accidents du tra to the unborn child	can give by ompared to Recherche et vail et des
		TWA	20 ppm 80 mg/m3	CH SUVA
		TWA	10 ppm 40 mg/m3	2004/37/EC
	Further infor	mation: Skin, Carcino	gens or mutagens	5
		STEL	20 ppm 80 mg/m3	2004/37/EC

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Version 11.0



#### Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### Environmental exposure controls

General advice	: Do not flush into surface water or sanitary sewer system.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	: liquid
Appearance	: viscous
Colour	: various
Odour	: amine-like

Melting point/range / Freezing : No data available

Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Version 11.0



#### point

Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or of Upper explosion limit / Upper explosion limit / Upper flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	ca. 71 °C Method: closed cup
Auto-ignition temperature	:	ca. 450 °C
Decomposition temperature	:	No data available
рН	:	ca. 7
Viscosity		
Viscosity, dynamic	:	ca. 4.200 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	0,01 hPa
Density	:	ca. 1,76 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Version 11.0



#### 9.2 Other information

No data available

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### **10.2 Chemical stability**

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

#### Hazardous reactions

: Stable under recommended storage conditions.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

#### **10.5** Incompatible materials

Materials to avoid	:	No data available
--------------------	---	-------------------

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified due to lack of data.

#### **Components:**

#### 6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine:

Acute oral toxicity	:	LD50 Oral (Rat): 1.515 mg/kg

Acute toxicity estimate: 1.515 mg/kg Method: Calculation method

#### Hydrocarbons, C9, aromatics:

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg

#### N-methyl-2-pyrrolidone:

Acute oral toxicity	: LD	50 Oral (Rat): 4.150 mg/kg	
Country CH 000000121096			9 / 17



Revision Date: 28.02.2024 Version 11.0 Date of last issue: 05.07.2022 Acute inhalation toxicity : LC50 (Rat): 5,1 mg/l Exposure time: 4 h Test atmosphere: dust/mist : LD50 Dermal (Rabbit): > 5.000 mg/kg Acute dermal toxicity Skin corrosion/irritation Not classified due to lack of data. Components: Hydrocarbons, C9, aromatics: Assessment 2 Repeated exposure may cause skin dryness or cracking. Serious eye damage/eye irritation Not classified due to lack of data. Respiratory or skin sensitisation Skin sensitisation May cause an allergic skin reaction. **Respiratory sensitisation** Not classified due to lack of data. Germ cell mutagenicity Not classified due to lack of data. Carcinogenicity Not classified due to lack of data. **Reproductive toxicity** Not classified due to lack of data. STOT - single exposure Not classified due to lack of data. **STOT - repeated exposure** Not classified due to lack of data. Aspiration toxicity Not classified due to lack of data. 11.2 Information on other hazards Endocrine disrupting properties Product: Assessment The substance/mixture does not contain components consid-5 ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## Sikafloor<sup>®</sup>-376 Part A

Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Print Date 28.02.2024

Version 11.0

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

#### Hydrocarbons, C9, aromatics:

5

Toxicity to algae/aquatic plants

(Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 mg/l Exposure time: 72 h

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or
	very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **12.6 Endocrine disrupting properties**

Product:		
Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

#### **SECTION 13: Disposal considerations**

2

#### 13.1 Waste treatment methods

Product

The generation of waste should be avoided or minimized

# Sikafloor®-376 Part A

Revision Date: 28.02.2024 Date of last issue: 05.07.2022



Version 11.0

	<ul> <li>wherever possible.</li> <li>Empty containers or liners may retain some product resi</li> <li>This material and its container must be disposed of in a way.</li> <li>Dispose of surplus and non-recyclable products via a lic waste disposal contractor.</li> <li>Disposal of this product, solutions and any by-products s at all times comply with the requirements of environment protection and waste disposal legislation and any region local authority requirements.</li> <li>Avoid dispersal of spilled material and runoff and contact soil, waterways, drains and sewers.</li> </ul>	safe ensed should tal al
Waste code Switzerland VeVA/LVA	: 08 01 11 -	
Contaminated packaging	: 15 01 10 [S] packaging containing residues of or contain ed by dangerous substances	inat-

### **SECTION 14: Transport information**

14.1 UN number or ID number					
ADR	:	UN 3082			
IMDG	:	UN 3082			
ΙΑΤΑ	:	UN 3082			
14.2 UN proper shipping name					
ADR	:	N.O.S.	Y HAZARDOUS SUBSTANCE, LIQUID, ethylthio)phenylene-1,3-diamine)		
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)			
ΙΑΤΑ	:	Environmentally hazardous substance, liquid, n.o.s. (6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine)			
14.3 Transport hazard class(es)					
		Class	Subsidiary risks		
ADR	:	9			
IMDG	:	9			
ΙΑΤΑ	:	9			
14.4 Packing group					
ADR Packing group	:	Ш			



Revision Date: 28.02.2024 Date of last issue: 05.07.2022		Version 11.0	Print Date 28.02.
Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks	: M6 : 90 : 9 : (-) : Tra	nsport in accordance with special provis	ion 375
IMDG Packing group Labels EmS Code Remarks		م, S-F Insport in accordance with 2.10.2.7 of the	e IMDG-Code
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels Remarks	-		tion A 197
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels 14.5 Environmental hazards	: 964 : Y96 : III : Mis		
ADR			
Environmentally hazardous <b>IMDG</b> Marine pollutant	: yes : yes		
IATA (Passenger) Environmentally hazardous	: yes		
IATA (Cargo) Environmentally hazardous	: yes	5	

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# Sikafloor®-376 Part A



	sion Date: 28.02.2024 of last issue: 05.07.2022	Ver	rsion 11.	0		Print Date 28.02.202
	International Chemical Weapons Schedules of Toxic Chemicals ar		C) :	:	Not applicable	
	REACH Information:		our upstro us, and/o the regu	ea r Ilat		
	REACH - Restrictions on the mar the market and use of certain dar mixtures and articles (Annex XVI	ngerous substanc		:	Conditions of restriction lowing entries should be Number on list 75, 3	
	REACH - Candidate List of Subst Concern for Authorisation (Article		gh :	:	N-methyl-2-pyrrolidone	9
	REACH - List of substances subj (Annex XIV)	ect to authorisatio	n :	:	Not applicable	
	Regulation (EC) No 1005/2009 or plete the ozone layer	n substances that	de-	:	Not applicable	
	Regulation (EU) 2019/1021 on petants (recast)	ersistent organic p	ollu-	:	Not applicable	
	PIC Ordinance, ChemPICO (814	.82)	:	:	Not applicable	
	Chemical Risk Reduction Ordinar 814.81) Seveso III: Directive 2012/18/EU	of the European I	Parliame	: ent	See respective Annex cal Risk Reduction Orc (ORRChem, 814.81) fo of Restriction. and of the Council on the	dinance or Conditions
	jor-accident hazards involving da E2	ENVIRONMEN		ZAI	RDS	
	34	(including jet fue heating oils and alternative fuels properties as rea	els), (c) g gas oil t serving gards fla	jas ole the	asolines and naphthas, ( s oils (including diesel fu ending streams),(d) heav e same purposes and w mability and environment in points (a) to (d)	uels, home vy fuel oils (e) vith similar
•	Volatile organic compounds :	(VOCV)			or volatile organic compo ls (VOC) content: 3,57%	
		emissions (integ	grated po	ollu	4 November 2010 on ind ution prevention and cor Is (VOC) content: 3,58%	ntrol)

Sikafloor<sup>®</sup>-376 Part A

Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Version 11.0



#### Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

ECTION 16: Other info	rmation	
Full text of H-Stateme	nts	
H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H360D	:	May damage the unborn child.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbr	eviations	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation

Skin sensitisation

Specific target organ toxicity - single exposure

#### SE

Skin Sens.

STOT SE

Sikafloor®-376 Part A

Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Version 11.0

2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens
2009/161/EU	:	at work Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
CH SUVA	:	Switzerland. Limit values at the work place
2004/37/EC / STEL		Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
2009/161/EU / TWA	:	Limit Value - eight hours
2009/161/EU / STEL	:	Short term exposure limit
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL		Short Term Exposure Limit
ADR	÷	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL		International Convention for the Prevention of Pollution from
	•	Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT		Persistent, bioaccumulative and toxic
PNEC	÷	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative
Further information		

Classification of the mixtur	Classification procedure:	
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



# Sikafloor®-376 Part A

Revision Date: 28.02.2024 Date of last issue: 05.07.2022 Version 11.0



Changes as compared to previous version !

CH / EN