Sikagard[®]-Wallcoat AT / N / T Part B



Revision Date: 18.12.2024 Date of last issue: 08.03.2023 Version 12.0

Print Date 18.12.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Sikagard[®]-Wallcoat AT / N / T Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

lassification (REGULATION (EC) No 1272/2008)				
Skin irritation, Category 2	H315: Causes skin irritation.			
Eye irritation, Category 2	H319: Causes serious eye irritation.			
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.			
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.			

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Warning

1

Sikagard[®]-Wallcoat AT / N / T Part B



Revision Date: 18.12.2024 Date of last issue: 08.03.2023		Version 12.0	Print Date 18.12.2024
Hazard statements	: H315 H317 H319 H411	Causes skin irritation. May cause an allergic skin reaction Causes serious eye irritation. Toxic to aquatic life with long last	
Precautionary statements	: P101 P102	If medical advice is needed, container or label at hand. Keep out of reach of childre	
	Preventior P273 P280	n: Avoid release to the environ Wear protective gloves/ eye protection.	
	Response	:	
	P391	Collect spillage.	
	Disposal:		
	P501	Dispose of contents/contain with local regulation.	er in accordance

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane Reaction mass of isomers of epoxy resin BFDGE oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikagard[®]-Wallcoat AT / N / T Part B



Revision Date: 18.12.2024 Date of last issue: 08.03.2023 Version 12.0

Print Date 18.12.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Skin Irrit. 2; H315 >= 5 %	>= 40 - < 60
Reaction mass of isomers of epoxy resin BFDGE	Not Assigned 701-263-0 01-2119454392-40- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 10 - < 20
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	68609-97-2 271-846-8 01-2119485289-22- XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360F	>= 2,5 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.

Sikagard[®]-Wallcoat AT / N / T Part B



ate of last issue: 08.03.2023		Version 12.0	Print Date 18.12.202
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconsciou	
4.2 Most important symptoms ar	nd e	effects, both acute and delayed	
Symptoms	:	Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information of and symptoms.	n health effects
Risks	:	irritant effects sensitising effects	
4.3 Indication of any immediate	me	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
-	:	Treat symptomatically.	
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media	: sur	Treat symptomatically.	
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media	: sur	Treat symptomatically.	powder for
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Specific hazards during fire-	: sur	Treat symptomatically. es In case of fire, use water/water spray/water jet/ ide/sand/foam/alcohol resistant foam/chemical extinction. substance or mixture Do not allow run-off from fire fighting to enter definition of the substance of the su	powder for
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Specific hazards during fire- fighting Hazardous combustion prod-	: sur : the	Treat symptomatically. Tes In case of fire, use water/water spray/water jet/ ide/sand/foam/alcohol resistant foam/chemical extinction. E substance or mixture Do not allow run-off from fire fighting to enter de courses.	powder for
Treatment SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media 5.2 Special hazards arising from Specific hazards during fire- fighting Hazardous combustion prod- ucts	: sur : :	Treat symptomatically. Tes In case of fire, use water/water spray/water jet/ ide/sand/foam/alcohol resistant foam/chemical extinction. E substance or mixture Do not allow run-off from fire fighting to enter de courses.	powder for rains or water

Sikagard[®]-Wallcoat AT / N / T Part B



Revision Date: 18.12.2024 Date of last issue: 08.03.2023 Version 12.0

Print Date 18.12.2024

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.

6.2 Environmental precautions

- Environmental precautions
- Do not flush into surface water or sanitary sewer system.
 If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, i	incl	uding any incompatibilities

Requirements for storage	:	Keep container tightly closed in a dry and well-ventilated
areas and containers		place. Containers which are opened must be carefully re-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-Wallcoat AT / N / T Part B



Revision Date: 18.12.2024 Date of last issue: 08.03.2023		Version 12.0	Print Date 18.12.2024
		sealed and kept upright to prevent leakage. Stor ance with local regulations.	e in accord-
Further information on stor- age stability	:	No decomposition if stored and applied as direct	ed.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet p use.	rior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
Contains no substances with accurational exposure limit values						

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water		
Hand protection	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.		
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.		
Respiratory protection	No special measures required.		
Environmental exposure controls			
General advice	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform		



Revision Date: 18.12.2024 Date of last issue: 08.03.2023 Version 12.0

Print Date 18.12.2024

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physica Physical state Colour	l an : :	d chemical properties liquid white
Odour	:	very faint
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	exn	losive limits
Upper explosion limit / Upper flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	No data available
рН	:	ca. 7 Concentration: 100 %
Viscosity		
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	soluble
Partition coefficient: n- octanol/water	:	No data available



Sikagard[®]-Wallcoat AT / N / T Part B

Revision Date: 18.12.2024	Version 12.0	Print Date 18.12.2024
Date of last issue: 08.03.2023		

Vapour pressure	:	23 hPa
Density	:	ca. 1,07 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information


11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Sikagard[®]-Wallcoat AT / N / T Part B



SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:				
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h		
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h		
Reaction mass of isomers of epoxy resin BFDGE:				
Toxicity to fish	:	LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l Exposure time: 96 h		
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h		
Toxicity to algae/aquatic plants	:	EC50 (algae): 1,8 mg/l Exposure time: 72 h		
	4			

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available



Sikagard[®]-Wallcoat AT / N / T Part B



Revision Date: 18.12.2024 Date of last issue: 08.03.2023

Version 12.0

Print Date 18.12.2024

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Pro	duct:

Assessment	: The substance/mixture does not contain components consid-
	ered to have endocrine disrupting properties according to
	REACH Article 57(f) or Commission Delegated regulation
	(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at
	levels of 0.1% or higher.
	-

12.7 Other adverse effects

Treaden		
Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland VeVA/LVA	: 08 01 11 [S] Paint and varnish waste containing organic solvents or other hazardous substances



Revision Date: 18.12.2024

Version 12.0

Print Date 18.12.2024

SECTION 14: Transport information

14.1 UN number or ID number

Date of last issue: 08.03.2023

	ADR	:	UN 3082		
	IMDG	:	UN 3082		
	ΙΑΤΑ	:	UN 3082		
14.2	UN proper shipping name				
	ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)		
	IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)		
	ΙΑΤΑ	:	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)		
14.3	Transport hazard class(es)				
			Class Subsidiary risks		
	ADR	:	9		
	IMDG	:	9		
	ΙΑΤΑ	:	9		
14.4	Packing group				
	ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks	: : : : : : : : : : : : : : : : : : : :	III M6 90 9 (-) Transport in accordance with special provision 375		
	IMDG Packing group Labels EmS Code Remarks IATA (Cargo) Packing instruction (cargo aircraft)		III 9 F-A, S-F Transport in accordance with 2.10.2.7 of the IMDG-Code 964		
	Packing instruction (LQ) Packing group Labels Remarks	: : :	Y964 III Miscellaneous Transport in accordance with special regulation A 197		

Sikagard[®]-Wallcoat AT / N / T Part B



Revision Date: 18.12.2024 Date of last issue: 08.03.2023 Version 12.0

Print Date 18.12.2024

IATA (Passenger)

:	964
:	Y964
:	III
:	Miscellaneous
	:

14.5 Environmental hazards

ADR Environmentally hazardous	:	yes
IMDG Marine pollutant	:	yes
IATA (Passenger) Environmentally hazardous	:	yes
IATA (Cargo) Environmentally hazardous	:	yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:	All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.	
REACH - Restrictions on the mar the market and use of certain dar mixtures and articles (Annex XVII	igerous substances,	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 75:
REACH - Candidate List of Subst Concern for Authorisation (Article	, ,	None of the components are listed (=> 0.1 %).

Sikagard[®]-Wallcoat AT / N / T Part B



Revision Date: 18.12.2024 Date of last issue: 08.03.2023	Version 12.0		Print Date 18.12.2024
REACH - List of substances subje (Annex XIV)	ect to authorisation :	Not applicable	
Regulation (EC) on substances th layer	at deplete the ozone :	Not applicable	
Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu- :	Not applicable	
PIC Ordinance, ChemPICO (814.	82) :	Not applicable	
Ordinance on Protection against M Threshold quantity according to M nance (MAO 814.012)		20.000 kg	
Waters Protection Ordinance (WF Water pollution class :	O 814.201) obviously hazardous to wa Classification according to		
Volatile organic compounds :	Law on the incentive tax for (VOCV) no VOC duties	or volatile organic comp	ounds
	Directive 2010/75/EU of 24 emissions (integrated pollu Not applicable		

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Staten	nents
-----------------------	-------

H315

: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikagard[®]-Wallcoat AT / N / T Part B



Revision Date: 18.12.2024 Date of last issue: 08.03.2023	Version 12.0	Print Date 18.12.2024
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H360F H411	May damage fertility. Toxic to aquatic life with long lasting effects.	
[141]	Toxic to aquatic life with long lasting effects.	
Full text of other abbreviation	S	
Aquatic Chronic	Long-term (chronic) aquatic hazard	
Eye Irrit.	Eye irritation	
Repr.	Reproductive toxicity	
Skin Irrit.	Skin irritation	
Skin Sens.	Skin sensitisation	
ADR	European Agreement concerning the Internat	ional Carriage of
	Dangerous Goods by Road	
CAS	Chemical Abstracts Service	
DNEL	Derived no-effect level	
EC50	Half maximal effective concentration	
GHS	Globally Harmonized System	
IATA	International Air Transport Association	
IMDG	International Maritime Code for Dangerous G	
LD50	Median lethal dosis (the amount of a material	
	once, which causes the death of 50% (one ha	alf) of a group of
	test animals)	
LC50	Median lethal concentration (concentrations c	
	air that kills 50% of the test animals during the	e observation
	period)	
MARPOL	International Convention for the Prevention of	
	Ships, 1973 as modified by the Protocol of 19	178
OEL	Occupational Exposure Limit	
PBT	Persistent, bioaccumulative and toxic	
PNEC	Predicted no effect concentration	
REACH	Regulation (EC) No 1907/2006 of the Europe	
	and of the Council of 18 December 2006 cond	
	istration, Evaluation, Authorisation and Restri	
	cals (REACH), establishing a European Chen	nicals Agency
SVHC	Substances of Very High Concern	
vPvB	Very persistent and very bioaccumulative	
Further information		

Classification of the mixture:		Classification procedure:
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Jika®

Revision Date: 18.12.2024 Date of last issue: 08.03.2023 Version 12.0

Print Date 18.12.2024

Changes as compared to previous version !

CH / EN