according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikafloor® P 922 Part A

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special coating

## 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Schweiz AG

Tüffenwies 16 8048 Zürich

: +41 58 436 40 40

Telefax :

E-mail address of person

responsible for the SDS

: EHS@ch.sika.com

## 1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich

Telephone

+41(0)44 251 51 51 / Speed calling: 145

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single ex-

posure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -









Signal word : Danger

Hazard statements : H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

# Hazardous components which must be listed on the label:

calcium dihydroxide bis(isopropyl)naphthalene

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Revision Date: 15.04.2024 Version 1.0 Print Date 15.04.2024

Date of last issue: -

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)		
calcium dihydroxide	1305-62-0 215-137-3 01-2119475151-45- XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system)	>= 20 - < 25		
bis(isopropyl)naphthalene	38640-62-9 254-052-6 01-2119565150-48- XXXX	Asp. Tox. 1; H304 Aquatic Chronic 1; H410	>= 10 - < 20		
Poly(oxy-1,2-ethanediyl), .alpha tridecylomegahydroxy-, branched	69011-36-5 Not Assigned	Eye Irrit. 2; H319 Aquatic Chronic 3; H412	>= 1 - < 2,5		
Substances with a workplace exposure limit :					
glycerol	56-81-5 200-289-5 01-2119471987-18- XXXX		>= 10 - < 20		

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Revision Date: 15.04.2024 Version 1.0 Print Date 15.04.2024

Date of last issue: -

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** Aspiration may cause pulmonary oedema and pneumonitis.

Cough

Respiratory disorder **Excessive lachrymation** 

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eve damage. May cause respiratory irritation.

Risk of serious damage to the lungs (by aspiration).

irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

### SECTION 5: Firefighting measures

## 5.1 Extinguishing media

Suitable extinguishing media In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
calcium dihydroxide	1305-62-0	TWA (Respirable fraction)	1 mg/m3	2017/164/EU
	Further informa	Further information: Indicative		
		STEL (Respirable fraction)	4 mg/m3	2017/164/EU
		TWA (inhalable dust)	1 mg/m3	CH SUVA
	Further information: National Institute for Occupational Safety and			
	Health, Harm to the unborn child is not to be expected when the			
	OEL-value is respected			
		STEL (inhalable dust)	4 mg/m3	CH SUVA
3,111	56-81-5	TWA (inhalable dust)	50 mg/m3	CH SUVA
	Further information: Harm to the unborn child is not to be ex-			
	pected when the OEL-value is respected			
		STEL (inhalable dust)	100 mg/m3	CH SUVA

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

## 8.2 Exposure controls

# **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

## Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Revision Date: 15.04.2024 Version 1.0 Print Date 15.04.2024

Date of last issue: -

Viton gloves (0.4 mm), breakthrough time >30 min.

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, Skin and body protection

> long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection In case of inadequate ventilation wear respiratory protection.

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

**Environmental exposure controls** 

General advice Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state liquid Appearance viscous Colour yellow

Odour slight

Melting point/range / Freezing : No data available

point

No data available Boiling point/boiling range

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Revision Date: 15.04.2024 Version 1.0 Print Date 15.04.2024

Date of last issue: -

Lower explosion limit / Lower flammability limit

: No data available

Flash point : > 110 °C

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

**Viscosity** 

Viscosity, dynamic : ca. 2.500 mPa.s (20 °C)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 23 hPa

Density : ca. 1,21 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

#### 9.2 Other information

No data available

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -

# 10.2 Chemical stability

The product is chemically stable.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified due to lack of data.

## **Components:**

## bis(isopropyl)naphthalene:

Acute oral toxicity : LD50 Oral (Rat): > 3.900 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,64 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 4.500 mg/kg

### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye damage.

# Respiratory or skin sensitisation

### Skin sensitisation

Not classified due to lack of data.

## Respiratory sensitisation

Not classified due to lack of data.

## Germ cell mutagenicity

Not classified due to lack of data.

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -

# Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Not classified due to lack of data.

## STOT - single exposure

May cause respiratory irritation.

## STOT - repeated exposure

Not classified due to lack of data.

### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

#### 11.2 Information on other hazards

## **Endocrine disrupting properties**

## **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

No data available

## 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components consid-

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number

 ADR
 : UN 3082

 IMDG
 : UN 3082

 IATA
 : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(bis(isopropyl)naphthalene)

**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(bis(isopropyl)naphthalene)

**IATA** : Environmentally hazardous substance, liquid, n.o.s.

(bis(isopropyl)naphthalene)

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -

# 14.3 Transport hazard class(es)

Class Subsidiary risks

 ADR
 : 9

 IMDG
 : 9

 IATA
 : 9

## 14.4 Packing group

**ADR** 

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

**IMDG** 

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passen: 964

ger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

#### 14.5 Environmental hazards

**ADR** 

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances.

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 75, 3

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

PIC Ordinance, ChemPICO (814.82) : Not applicable

Chemical Risk Reduction Ordinance (ORRChem, SR

814.81)

See respective Annex to the Chemical Risk Reduction Ordinance

(ORRChem, 814.81) for Conditions

of Restriction.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of ma-

jor-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 0,95% w/w

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2,15% w/w

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Revision Date: 15.04.2024 Version 1.0 Print Date 15.04.2024

Date of last issue: -

## Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

## 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.

H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage Eye Irrit. : Eye irritation

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a

fourth list of indicative occupational exposure limit values

CH SUVA : Switzerland. Limit values at the work place

2017/164/EU / STEL : Short term exposure limit 2017/164/EU / TWA : Limit Value - eight hours CH SUVA / TWA : Time Weighted Average CH SUVA / STEL : Short Term Exposure Limit

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration
GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

according to Regulation (EC) No. 1907/2006

# Sikafloor® P 922 Part A

Date of last issue: -

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

Classification of the mixture: Classification procedure:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
STOT SE 3	H335	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

CH / EN