

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika Boom®-524 Formwork Seal

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane foam

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Schweiz AG
Tüffenwies 16
8048 Zürich
Telephone : +41 58 436 40 40
Telefax : -
E-mail address of person : EHS@ch.sika.com
responsible for the SDS

1.4 Emergency telephone number

Tox Info Suisse
CH-8028 Zurich
+41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Effects on or via lactation	H362: May cause harm to breast-fed children.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

Specific target organ toxicity - repeated exposure, Category 2

H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

Long-term (chronic) aquatic hazard, Category 4

H413: May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H413	May cause long lasting harmful effects to aquatic life.

Precautionary statements :

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Prevention:

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust or mist.
P263	Avoid contact during pregnancy and while nursing.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues alkanes, C14-17, chloro

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 % specific concentration limit Skin Irrit. 2; H315 >= 5 % specific concentration limit STOT SE 3; H335 >= 5 %	>= 10 - < 20
alkanes, C14-17, chloro	85535-85-9 287-477-0 01-2119519269-33-XXXX	Lact.H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH066 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	>= 5 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024

Version 9.0

Print Date 28.10.2024

Date of last issue: 20.03.2024

Reaction products of phosphoryl trichloride and methyloxirane	1244733-77-4 237-158-7 01-2119486772-26-XXXX	Acute Tox. 4; H302 Carc. 2; H351 Aquatic Chronic 3; H412 Acute toxicity estimate Acute oral toxicity: 630 mg/kg	$\geq 2,5 - < 5$
Substances with a workplace exposure limit :			
isobutane	75-28-5 200-857-2 01-2119485395-27-XXXX	Flam. Gas 1A; H220	$\geq 5 - < 10$
dimethyl ether	115-10-6 204-065-8 01-2119472128-37-XXXX	Flam. Gas 1A; H220	$\geq 5 - < 10$
propane	74-98-6 200-827-9 01-2119486944-21-XXXX	Flam. Gas 1A; H220	$\geq 2,5 - < 5$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

- Symptoms : Asthmatic appearance
Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects
- Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of causing cancer.
May cause harm to breast-fed children.
May cause damage to organs through prolonged or repeated exposure if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray jet
Dry powder
Foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Nitrogen oxides (NO_x)
Hydrogen cyanide (hydrocyanic acid)
Chlorine compounds

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Allow to solidify, use mechanical handling equipment.
Ventilate the area.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	CH SUVA
		Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Health and Safety Executive (Occupational Medicine and Hygiene Laboratory)		
		STEL	0,02 mg/m3 (NCO)	CH SUVA
isobutane	75-28-5	TWA	800 ppm 1.900 mg/m3	CH SUVA
		STEL	3.200 ppm 7.600 mg/m3	CH SUVA
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC
		Further information: Indicative		
		TWA	1.000 ppm 1.910 mg/m3	CH SUVA
propane	74-98-6	STEL	4.000 ppm 7.200 mg/m3	CH SUVA
		Further information: National Institute for Occupational Safety and Health		
		TWA	1.000 ppm 1.800 mg/m3	CH SUVA

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor (Type A) and particulate filter
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
P1: Inert material; P2, P3: hazardous substances
Ensure adequate ventilation, especially in confined areas.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : aerosol
Colour : various

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024

Version 9.0

Print Date 28.10.2024

Date of last issue: 20.03.2024

- Odour : No data available
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flammability : Extremely flammable aerosol.

Upper/lower flammability or explosive limits

- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Flash point : Not applicable
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- pH : Not applicable
substance/mixture reacts with water

Viscosity

- Viscosity, kinematic : Not applicable

Solubility(ies)

- Water solubility : No data available
- Partition coefficient: n-octanol/water : No data available
- Vapour pressure : 5100 hPa
- Density : ca. 0,95 g/cm³ (23 °C)
- Relative vapour density : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

Reaction products of phosphoryl trichloride and methyloxirane:

Acute oral toxicity : LD50 Oral (Rat): > 630 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

alkanes, C14-17, chloro:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

May cause harm to breast-fed children.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l
Exposure time: 72 h

alkanes, C14-17, chloro:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 10

Reaction products of phosphoryl trichloride and methyloxirane:

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 82 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 13 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 202

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB)..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
May cause long lasting harmful effects to aquatic life.

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

propane:

20-year global warming potential: 0,072
100-year global warming potential: 0,02
500-year global warming potential: 0,006
Atmospheric lifetime: 0,036 yr
Radiative efficiency: 0 Wm2ppb
Further information: Miscellaneous compounds

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste code Switzerland : 16 05 04 [S] gases in pressure containers (including halons)
VeVA/LVA containing dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)
Remarks : Transport according to chapter 3.4 (LQ) possible

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo) : 203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

aircraft)
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 56: Diphenylmethanediisocyanate, isomeres and homologues

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024

Version 9.0

Print Date 28.10.2024

Date of last issue: 20.03.2024

Number on list 74: Diphenylmethanediisocyanate, isomeres and homologues

Number on list 75:

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : alkanes, C14-17, chloro

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

PIC Ordinance, ChemPICO (814.82) : Not applicable

Ordinance on Protection against Major Accidents
Threshold quantity according to Major Accidents Ordinance (MAO 814.012) : 50.000 kg

Chemical Risk Reduction Ordinance (ORRChem, SR 814.81) : Conditions of restriction for the following annexes should be considered:
Diphenylmethanediisocyanate, isomeres and homologues: Annex 2.9 Plastics and additives

Waters Protection Ordinance (WPO 814.201)

Water pollution class : obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 23,7% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 23,7% w/w

Other regulations:

75/324/EEC

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H220	:	Extremely flammable gas.
H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H362	:	May cause harm to breast-fed children.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Lact.	:	Effects on or via lactation
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-524 Formwork Seal



Revision Date: 28.10.2024

Version 9.0

Print Date 28.10.2024

Date of last issue: 20.03.2024

2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
CH SUVA	:	Switzerland. Limit values at the work place
2000/39/EC / TWA	:	Limit Value - eight hours
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
Lact.	H362
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 4	H413

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Based on product data or assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom[®]-524 Formwork Seal



Revision Date: 28.10.2024
Date of last issue: 20.03.2024

Version 9.0

Print Date 28.10.2024

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

CH / EN