



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaCor® VE Solution Part A yellow glaze

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Schweiz AG
Tüffenwies 16
8048 Zürich
Telephone : +41 58 436 40 40
Telefax : -
E-mail address of person : EHS@ch.sika.com
responsible for the SDS

1.4 Emergency telephone number

Tox Info Suisse
CH-8028 Zurich
+41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 1, hearing organs	H372: Causes damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze






Revision Date: 10.08.2021
Date of last issue: 11.05.2021

Version 8.0

Print Date 03.05.2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:			
Signal word	:	Danger		
Hazard statements	:	H226 H302 H315 H317 H319 H335 H361d H372 H412	Flammable liquid and vapour. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging the unborn child. Causes damage to organs (hearing organs) through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.	
Precautionary statements	:	Prevention: P201 P210 P260 P264 P280 Response: P370 + P378	Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe mist or vapours. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.	

Hazardous components which must be listed on the label:

styrene
tetramethylammonium chloride
cobalt bis(2-ethylhexanoate)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021

Version 8.0

Print Date 03.05.2023

Date of last issue: 11.05.2021

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
styrene	100-42-5 202-851-5 01-2119457861-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (hearing organs) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	$\geq 25 - < 40$
methacrylic acid	79-41-4 201-204-4 01-2119463884-26-XXXX	Acute Tox. 4; H302 Skin Corr. 1A; H314 Eye Dam. 1; H318 Acute Tox. 3; H311 STOT SE 3; H335 Acute Tox. 4; H332 specific concentration limit STOT SE 3; H335 $\geq 1 \%$	$\geq 1 - < 2,5$
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47-XXXX	Repr. 2; H361d Aquatic Chronic 3; H412	$\geq 0,025 - < 0,25$
cobalt bis(2-ethylhexanoate)	136-52-7 205-250-6 01-2119524678-29-XXXX	Eye Irrit. 2; H319 Skin Sens. 1A; H317 Repr. 1B; H360 Aquatic Acute 1; H400 Aquatic Chronic 3; H412 M-Factor (Acute aquatic toxicity): 1	$\geq 0,1 - < 0,25$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021

Version 8.0

Print Date 03.05.2023

Date of last issue: 11.05.2021

1,4-dihydroxybenzene	123-31-9 204-617-8	Carc. 2; H351 Muta. 2; H341 Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 <hr/> M-Factor (Acute aquatic toxicity): 10	$\geq 0,025 - < 0,25$
----------------------	-----------------------	---	-----------------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Gastrointestinal discomfort
Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021
Date of last issue: 11.05.2021

Version 8.0

Print Date 03.05.2023

Harmful if swallowed.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
Suspected of damaging the unborn child.
Causes damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Water
High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform



respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.



7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
styrene	100-42-5	TWA	20 ppm 85 mg/m ³	CH SUVA
	Further information: noise amplifying ototoxicity, National Institute for Occupational Safety and Health, Occupational Safety and Health Administration, Deutsche Forschungsgemeinschaft, Health and Safety Executive (Occupational Medicine and Hygiene Laboratory), Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	40 ppm 170 mg/m ³	CH SUVA
methacrylic acid	79-41-4	TWA	50 ppm 180 mg/m ³	CH SUVA
	Further information: Occupational Safety and Health Administration, Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	100 ppm 360 mg/m ³	CH SUVA
cobalt bis(2-ethylhexanoate)	136-52-7	TWA (inhalable dust)	0,05 mg/m ³ (Cobalt)	CH SUVA
	Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Contains substances which are possibly mutagenic to humans., Carcinogenic Category 2, Substance which should be considered to be reprotoxic; the reprotoxicity affects the fertility and sexuality., National Institute for Occupational Safety and Health, Health and Safety Executive (Occupational Medicine and Hygiene Laboratory), BG			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
styrene	100-42-5	mandelic acid plus phenylglyoxylic acid: 600 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	CH BAT



8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
Colour : yellow

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021
Date of last issue: 11.05.2021

Version 8.0

Print Date 03.05.2023

Odour : slight

Boiling point/boiling range : ca. 145 °C

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 7,7 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Flash point : ca. 31 °C
Method: closed cup

Auto-ignition temperature : ca. 490 °C

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Vapour pressure : 5,9995 hPa

Density : ca. 1,09 g/cm³ (20 °C)

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021
Date of last issue: 11.05.2021

Version 8.0

Print Date 03.05.2023

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

Components:

styrene:

Acute inhalation toxicity : LC50 (Rat): 11,8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Acute oral toxicity : LD50 Oral (Rat): > 3.200 mg/kg
Acute dermal toxicity : LD50 Dermal (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021
Date of last issue: 11.05.2021

Version 8.0

Print Date 03.05.2023

Reproductive toxicity

Suspected of damaging the unborn child.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs (hearing organs) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

cobalt bis(2-ethylhexanoate):

Toxicity to algae/aquatic plants : IC50 (Desmodesmus subspicatus (green algae)): 0,528 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

1,4-dihydroxybenzene:

M-Factor (Acute aquatic toxicity) : 10

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Country CH 000000123922

11 / 17

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021

Version 8.0

Print Date 03.05.2023

Date of last issue: 11.05.2021

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste code Switzerland : 08 01 11: -
VeVA/LVA

Contaminated packaging : 15 01 10 [S] packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

ADR : UN 1263

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021
Date of last issue: 11.05.2021

Version 8.0

Print Date 03.05.2023

IMDG : UN 1263

IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT

IMDG : PAINT

IATA : Paint

14.3 Transport hazard class(es)

ADR : 3

IMDG : 3

IATA : 3

14.4 Packing group

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021

Version 8.0

Print Date 03.05.2023

Date of last issue: 11.05.2021

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

PIC Ordinance, ChemPICO (814.82) : Not applicable

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 0,15% w/w

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021
Date of last issue: 11.05.2021

Version 8.0

Print Date 03.05.2023

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 35,95% w/w

Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

The product belongs to group 2 according to the Swiss Chemicals Ordinance (ChemO 813.11).

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H311	:	Toxic in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H341	:	Suspected of causing genetic defects.
H351	:	Suspected of causing cancer.
H360	:	May damage fertility or the unborn child.
H361d	:	Suspected of damaging the unborn child.
H372	:	Causes damage to organs through prolonged or repeated exposure.
H400	:	Very toxic to aquatic life.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021

Version 8.0

Print Date 03.05.2023

Date of last issue: 11.05.2021

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Carc.	:	Carcinogenicity
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Muta.	:	Germ cell mutagenicity
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
CH BAT	:	Switzerland. List of BAT-values
CH SUVA	:	Switzerland. Limit values at the work place
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H302
Skin Irrit. 2	H315
Eye Irrit. 2	H319

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

SikaCor® VE Solution Part A yellow glaze



Revision Date: 10.08.2021
Date of last issue: 11.05.2021

Version 8.0

Print Date 03.05.2023

Skin Sens. 1	H317	Calculation method
Repr. 2	H361d	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 1	H372	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

CH / EN