Sika[®] ADPrep



Print Date 04.06.2024

Revision Date: 04.06.2024 Date of last issue: 29.08.2022 Version 12.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® ADPrep

Sika Abrrep

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person responsible for the SDS	:	EHS@ch.sika.com

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] ADPrep



Revision Date: 04.06.2024 Date of last issue: 29.08.2022			Versio	on 12.0	Print Date 04.06.2024
Signal word	:	Danger			
Hazard statements	:	H317 H319	May ca Cause	flammable liquid and va use an allergic skin rea s serious eye irritation. use drowsiness or dizzi	ction.
Precautionary statements	:	Prevention: P210 P233 P261 P280	oj sr K A W	eep away from heat, hot ben flames and other igr noking. eep container tightly clos void breathing mist or va 'ear protective gloves/ p ve protection/ face prote	ition sources. No sed. pours. rotective clothing/
		Response:			
		P303 + P361	at	3 IF ON SKIN (or hair ely all contaminated clot ith water.	
		P370 + P378		case of fire: Use dry sa cohol-resistant foam to e	•

Hazardous components which must be listed on the label:

propan-2-ol Ethoxylated Trimethylolpropanetriacrylate resorcinol hexamethylene diacrylate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sika[®] ADPrep



Revision Date: 04.06.2024 Date of last issue: 29.08.2022 Version 12.0

Print Date 04.06.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7 01-2119457558-25- XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>=80
Ethoxylated Trimethylolpropane- triacrylate	28961-43-5 500-066-5 01-2119489900-30- XXXX	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 2,5
bis(methacryloyloxyethyl) hydro- gen phosphate	32435-46-4 251-040-2	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Chronic 3; H412	>= 1 - < 2,5
resorcinol	108-46-3 203-585-2 01-2119480136-40- XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Acute toxicity esti- mate Acute oral toxicity: 301 mg/kg	>= 1 - < 2,5
hexamethylene diacrylate Contains: cyclohexane >= 0,2 - <= 0,3 %	13048-33-4 235-921-9 01-2119484737-22- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2,5

For explanation of abbreviations see section 16.



Revision Date: 04.06.2024 Date of last issue: 29.08.2022

Version 12.0

Print Date 04.06.2024

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	 Allergic reactions Excessive lachrymation Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms.
Risks	: irritant effects sensitising effects
	May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.
4.3 Indication of any immediat	e medical attention and special treatment needed
Treatment	: Treat symptomatically.
SECTION 5: Firefighting me	Pasures

SECTION 5: Firefighting measures

5.1 Extinguishing media			
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	

tion (EU) 2020/878 Sika® ADPrep



Revision Date: 04.06.2024		Version 12.0	Print Date 04.06.2024
Date of last issue: 29.08.2022			
Unsuitable extinguishing media	:	Water High volume water jet	
5.2 Special hazards arising from	the	e substance or mixture	
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scat fire.	ter and spread
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	ng apparatus.
Further information	:	Use water spray to cool unopened containers.	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions		
Environmental precautions	:	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

2

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] ADPrep

Revision Date: 04.06.2024



Print Date 04.06.2024

Date of last issue: 29.08.2022		
		 section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, i	incl	uding any incompatibilities
Requirements for storage areas and containers	:	Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

Version 12.0

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
propan-2-ol	67-63-0	STEL	400 ppm 1.000 mg/m3	CH SUVA	
	Further information: National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la pré- vention des accidents du travail et des maladies professionnelles.				



Sika[®] ADPrep

Revision Date: 04.06.2024 Date of last issue: 29.08.2022 Version 12.0

Print Date 04.06.2024

		Harm to the unborn child is not to be expected when the OEL- value is respected					
		TWA	200 ppm 500 mg/m3	CH SUVA			
resorcinol	108-46-3	TWA	10 ppm 45 mg/m3	2006/15/EC			
		Further information: Indicative, Identifies the possibility of signifi- cant uptake through the skin					
		TŴA	10 mg/m3	CH SUVA			
	Further infor tion	Further information: Occupational Safety and Health Administra- tion					

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
propan-2-ol	67-63-0	Acetone: 25 mg/l (Urine)	Immediately after exposure or after working hours	CH BAT
		Acetone: 25 mg/l (Blood)	Immediately after exposure or after working hours	CH BAT
		Acetone: 0.4 Millimoles per liter (Urine)	Immediately after exposure or after working hours	CH BAT
		Acetone: 0.4 Millimoles per liter (Blood)	Immediately after exposure or after working hours	CH BAT

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.

Sika[®] ADPrep



evision Date: 04.06.2024 te of last issue: 29.08.2022		Version 12.0	Print Date 04.06.2024
Skin and body protection		Protective clothing (e.g. Safety shoes a long-sleeved working clothing, long trou and protective boots are additionaly rec and stirring work.	users). Rubber aprons
Respiratory protection		In case of inadequate ventilation wear r Respirator selection must be based on exposure levels, the hazards of the pro- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < Ensure adequate ventilation. This can be exhaust extraction or by general ventilation ods for determining inhalation exposure ticular to the mixing / stirring area. In can to keep the concentrations under the oc- limits then respiration protection measure	known or anticipated duct and the safe work- < 10000 ppm be achieved by local ation. (EN 689 - Meth- e). This applies in par- ase this is not sufficent ccupational exposure
Environmental exposure c	ontro	S	
General advice	:	Prevent product from entering drains.	

 Prevent product from entering drains.
 If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid colourless
Odour	:	solvent-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	12 %(V)
Lower explosion limit / Lower flammability limit	:	2 %(V)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] ADPrep



Revision Date: 04.06.2024 Date of last issue: 29.08.2022	Version 12.0	Print Date 04.06.2024
Flash point	: ca. 13 °C Method: closed cup	
Auto-ignition temperature	: 425 °C	
Decomposition temperature	: No data available	
рН	: Not applicable substance/mixture is non-soluble (in wa	ter)
Viscosity		
Viscosity, kinematic	: < 6,9 mm2/s (40 °C)	
Solubility(ies)		
Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 42,9963 hPa	
Density	: ca. 0,8 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Sika[®] ADPrep



Revision Date: 04.06.2024 Date of last issue: 29.08.2022	Version 12.0	Print Date 04.06.2024
	Vapours may form explosive mixture with air.	
10.4 Conditions to avoid Conditions to avoid	Heat, flames and sparks.	
10.5 Incompatible materials Materials to avoid	No data available	
10.6 Hazardous decomposition pro	ducts	
	No hazardous decomposition products are know	vn.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

propan-2-ol:	
Acute oral toxicity :	LD50 Oral (Rat): < 5.000 mg/kg
Acute inhalation toxicity :	LC50 (Rat): > 20 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity :	LD50 Dermal (Rabbit): > 5.000 mg/kg
resorcinol:	
Acute oral toxicity :	LD50 Oral (Rat): 301 mg/kg
	Acute toxicity estimate: 301 mg/kg Method: Calculation method
Acute dermal toxicity :	LD50 Dermal (Rabbit): 3.360 mg/kg
Skin corrosion/irritation	
Not classified due to lack of data	a.

Serious eye damage/eye irritation

Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] ADPrep

Revision Date: 04.06.2024 Date of last issue: 29.08.2022 Version 12.0

Print Date 04.06.2024

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

2

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:		
propan-2-ol:		
Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 9.714 mg/l Exposure time: 24 h Method: OECD Test Guideline 202



Sika[®] ADPrep



	Version 12.0	Print Date 04.06.202
:	EC50 (Scenedesmus capricornutum (fresh wate 100 mg/l Exposure time: 72 h	er algae)): >
:	1	
:	1	
lity		
sse	ssment	
:	to be either persistent, bioaccumulative and tox	ic (PBT), or
ertie	S	
:	ered to have endocrine disrupting properties ac REACH Article 57(f) or Commission Delegated	cording to regulation
:	There is no data available for this product.	
	: sses :	 EC50 (Scenedesmus capricornutum (fresh water 100 mg/l Exposure time: 72 h 1 1 1 1 ssessment This substance/mixture contains no components to be either persistent, bioaccumulative and toxi very persistent and very bioaccumulative (vPvB 0.1% or higher rrties The substance/mixture does not contain components ac REACH Article 57(f) or Commission Delegated (EU) 2017/2100 or Commission Regulation (EU levels of 0.1% or higher.

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. 	

Sika[®] ADPrep



Revision Date: 04.06.2024 Date of last issue: 29.08.2022		Version 12.0	Print Date 04.06.2024
	wa Dis wa Dis at pro loc Av	is material and its container must be y. spose of surplus and non-recyclable ste disposal contractor. sposal of this product, solutions and a all times comply with the requirement otection and waste disposal legislation al authority requirements. oid dispersal of spilled material and n I, waterways, drains and sewers.	products via a licensed any by-products should its of environmental on and any regional
Waste code Switzerland VeVA/LVA	: 08	01 11 -	
Contaminated packaging		01 10 [S] packaging containing resident by dangerous substances	dues of or contaminat-

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	UN 1219	
	IMDG	:	UN 1219	
	ΙΑΤΑ	:	UN 1219	
14.2	UN proper shipping name			
	ADR	:	ISOPROPANOL	
	IMDG	:	ISOPROPANOL	
	ΙΑΤΑ	:	Isopropanol	
14.3	Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	3	
	IMDG	:	3	
	ΙΑΤΑ	:	3	
14.4	Packing group			
	ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	•	II F1 33 3 (D/E)	
	IMDG Packing group	:	II	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] ADPrep

Revision Date: 04.06.2024

Jika®

Print Date 04.06.2024

Date of last issue: 29.08.2022			
Labels EmS Code	:	3 F-E, S-D	
IATA (Cargo) Packing instruction (cargo aircraft)	:	364	
Packing instruction (LQ) Packing group Labels	:	Y341 II Flammable Liquids	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels		353 Y341 II Flammable Liquids	
14.5 Environmental hazards			
ADR Environmentally hazardous	:	no	
IMDG Marine pollutant	:	no	
IATA (Passenger) Environmentally hazardous	:	no	
IATA (Cargo)			

Version 12.0

IATA (Cargo) Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] ADPrep



Revision Date: 04.06.2024 Date of last issue: 29.08.2022	Version 1	2.0	Print Date 04.06.2024	
the market and use of certain dan mixtures and articles (Annex XVII			lowing entries should be considered: Number on list 75, 3	
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).		:	None of the components are listed (=> 0.1 %).	
REACH - List of substances subject to authorisation (Annex XIV)		:	Not applicable	
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer		:	Not applicable	
Regulation (EU) 2019/1021 on pe tants (recast)	ersistent organic pollu-	:	Not applicable	
PIC Ordinance, ChemPICO (814.82)		:	Not applicable	
Chemical Risk Reduction Ordinance (ORRChem, SR 814.81)		:	See respective Annex to the Chemi- cal Risk Reduction Ordinance (ORRChem, 814.81) for Conditions of Restriction.	
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS				
Volatile organic compounds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 94% w/w			
Directive 2010/75/EU of 24 November 2010 of emissions (integrated pollution prevention and Volatile organic compounds (VOC) content: 9			ution prevention and control)	

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] ADPrep

Revision Date: 04.06.2024 Date of last issue: 29.08.2022 Version 12.0

Print Date 04.06.2024

SECTION 16: Other information

Full text of H-Statements

H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. : H315 Causes skin irritation. : H317 May cause an allergic skin reaction. : Causes serious eye irritation. H319 1 May cause drowsiness or dizziness. H336 H400 Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. H411 Harmful to aquatic life with long lasting effects. H412 Full text of other abbreviations Acute Tox. Acute toxicity Aquatic Acute Short-term (acute) aquatic hazard : Aquatic Chronic : Long-term (chronic) aquatic hazard Eye Irrit. Eve irritation 2 Flam. Liq. Flammable liquids Skin Irrit. Skin irritation : Skin Sens. Skin sensitisation : STOT SE Specific target organ toxicity - single exposure : 2006/15/EC Europe. Indicative occupational exposure limit values CH BAT Switzerland, List of BAT-values Switzerland. Limit values at the work place CH SUVA 2006/15/EC / TWA Limit Value - eight hours CH SUVA / TWA : **Time Weighted Average** CH SUVA / STEL Short Term Exposure Limit ADR European Agreement concerning the International Carriage of Dangerous Goods by Road CAS Chemical Abstracts Service Derived no-effect level DNEL **EC50** Half maximal effective concentration 2 **Globally Harmonized System** GHS IATA International Air Transport Association International Maritime Code for Dangerous Goods IMDG Median lethal dosis (the amount of a material, given all at LD50 once, which causes the death of 50% (one half) of a group of test animals) Median lethal concentration (concentrations of the chemical in LC50 air that kills 50% of the test animals during the observation period) MARPOL International Convention for the Prevention of Pollution from : Ships, 1973 as modified by the Protocol of 1978 OEL **Occupational Exposure Limit** PBT Persistent, bioaccumulative and toxic PNEC Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament REACH and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency



Sika[®] ADPrep



Revision Date: 04.06.2024 Date of last issue: 29.08.2022	Version 12.0	Print Date 04.06.2024
SVHC vPvB	Substances of Very High ConcernVery persistent and very bioaccumulative	

Further information

re:	Classification procedure:
H225	Based on product data or assessment
H319	Calculation method
H317	Calculation method
H336	Calculation method
	H319 H317

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN