Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikaflex[®]-296

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms		
Signal word	: Danger	
Hazard statements	: H317	May cause an allergic skin reaction.

Sikaflex[®]-296



Revision Date: 16.11.2023 Date of last issue: 09.08.2022	V	Print Date 16.11.20	
	H334	May cause allergy or asthma s breathing difficulties if inhaled.	ymptoms or
	H412	Harmful to aquatic life with long fects.	lasting ef-
Precautionary statements	: Prevention:		
	P261	Avoid breathing mist or vapours	S.
	P273	Avoid release to the environme	nt.
	P280	Wear protective gloves.	
	P284	In case of inadequate ventilatio atory protection.	n wear respir-
	Response:		
	P304 + P340	IF INHALED: Remove person to keep comfortable for breathing.	
	P342 + P311	If experiencing respiratory symposition of the sympositic symposit	

Hazardous components which must be listed on the label:

aliphatic prepolymer (t-polyether based) aliphatic prepolymer (d-polyether based) 4,4'-methylenediphenyl diisocyanate 2-ethyl-2-[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate Pentamethyl piperidylsebacate 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 16.11.2023 Date of last issue: 09.08.2022



Version 18.0

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
aliphatic prepolymer (t-polyether based)	138626-39-8 Not Assigned	Skin Sens. 1; H317	>= 5 - < 10
aliphatic prepolymer (d-polyether based)	39323-37-0 Not Assigned	Skin Sens. 1; H317	>= 2,5 - < 5
4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	>= 0,1 - < 0,5

Sikaflex[®]-296

Revision Date: 16.11.2023 Date of last issue: 09.08.2022



Version 18.0

2-ethyl-2-[[(1-oxoallyl)oxy]methyl]- 1,3-propanediyl diacrylate	15625-89-5 239-701-3 01-2119489896-11- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Carc. 2; H351 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 = specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 % Acute toxicity estimate Acute inhalation tox-	>= 0,025 - < 0,1
For explanation of abbreviations se		icity (dust/mist): 0,031 mg/l	

For explanation of abbreviations see section 16.

Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0



SECTION 4: First aid measures

4.1 Description of first aid measures				
General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.		
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.		
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.		
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.		
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.		
4.2 Most important symptoms a	nd e	ffects, both acute and delayed		
Symptoms	:	Asthmatic appearance Allergic reactions See Section 11 for more detailed information on health effects and symptoms.		
Risks	:	sensitising effects		
		May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.		
4.3 Indication of any immediate	mec	lical attention and special treatment needed		
Treatment	:	Treat symptomatically.		

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
Country CH 000000122941			5/



Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0

5.3 Advice for firefighters Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.	
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental releas	se i	measures	
6.1 Personal precautions, protect	ctiv	e equipment and emergency procedures	
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.	
6.3 Methods and material for co	ntai	nment and cleaning up	
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety
Country CH 000000122941		6 /

Revision Date: 16.11.2023

Date of last issue: 09.08.2022



Version 18.0

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s) Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m3 (NCO)	CH SUVA		
		ation: Toxic by skin				
	tional skin reso	es, which are easily absored through the skin, can give by addi- tional skin resoption a substancial higher risk compared to only inhalation by the airways., Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Health and Safety Executive (Occupational Medicine and Hygiene Laboratory), Harm to the unborn child is not to be expected when the OEL-value is respected				
	an S can lead Executive (Oc					
		STEL 0,02 mg/m3 CH SUVA (NCO)				
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,02 mg/m3 (NCO)	CH SUVA		
	can lead to ve	Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Health and Safety Ex- ecutive (Occupational Medicine and Hygiene Laboratory)				
	0,02 mg/m3 (NCO)	CHSUVA				

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	4,4'- diaminodiphenyl- methane: 10 μg/g creatinine (Urine)	Immediately after exposure or after working hours	CH BAT



Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0

	diaminodiphenyl- aft methane: 5 or	nmediately CH B fter exposure r after working ours	AT
--	---------------------------------------	---	----

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection :					
Eyenace protection .	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water				
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.				
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.				
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.				
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.				
Environmental exposure controls					

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.



Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste black
Odour	:	odourless
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	<u>-</u> xn	losive limits
Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available

water)

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikaflex®-296

Print Date 16.11.2023

Revision Date: 16.11.2023
Date of last issue: 09.08.2022

Version 18.0

Vapour pressure	: 0,01 hPa
Density	: ca. 1,2 g/cm3 (20 °C)
Relative vapour density	: No data available
Particle characteristics	: No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

nazardous reactions . No nazards to be specially mentione	Hazardous reactions	: No hazards to be specially mentioned.
---	---------------------	---

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

aliphatic prepolymer (d-polyether based):

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Print Date 16.11.2023

Revision Date: 16.11.2023	
Date of last issue: 09.08.2022	

Version 18.0

4,4'-methylenediphenyl dii	socy	anate:
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method
2-ethyl-2-[[(1-oxoallyl)oxy]	meth	yl]-1,3-propanediyl diacrylate:
Acute oral toxicity		LD50 Oral (Rat): 3.680 - 5.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg
Pentamethyl piperidylseba	acate	:
		LD50 Oral (Rat): 3.230 mg/kg
3-isocyanatomethyl-3,5,5-t	rime	thylcyclohexyl isocyanate:
Acute oral toxicity	:	LD50 Oral (Rat): 4.814 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist
		Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	LD50 Dermal (Rat): > 7.000 mg/kg
Skin corrosion/irritation Not classified due to lack of	data.	
Serious eye damage/eye ir Not classified due to lack of		
Respiratory or skin sensiti	isatio	on
Skin sensitisation May cause an allergic skin re	eactio	on.
Respiratory sensitisation		
	a sym	ptoms or breathing difficulties if inhaled.
Germ cell mutagenicity Not classified due to lack of	data.	

Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0



Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

aliphatic prepolymer (t-polyet Toxicity to algae/aquatic plants		
		NOEC (algae): 100 mg/l Exposure time: 72 h
aliphatic prepolymer (d-polye	eth	er based):
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l
		NOEC (Daphnia (water flea)): > 100 mg/l
Toxicity to algae/aquatic plants	:	EC50 (algae): > 100 mg/l Exposure time: 72 h
2-ethyl-2-[[(1-oxoallyl)oxy]me	eth	yl]-1,3-propanediyl diacrylate:
Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): 0,87 mg/l

Exposure time: 96 h

M-Factor (Acute aquatic tox- : 1

Sikaflex[®]-296

icity)

toxicity)

Print Date 16.11.2023

Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0

Method: OECD Test Guideline 203

96 h

M-Factor (Chronic aquatic : 1 Pentamethyl piperidylsebacate: LC50 (Fish): 0,97 mg/l

Toxicity to fish	:	LC50 (Fish): 0,9 Exposure time:
M-Factor (Acute aquatic tox- icity)	:	1
M-Factor (Chronic aquatic	:	1

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components consid-2 ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland VeVA/LVA	:	08 04 09 [S] waste adhesives and sealants containing organic solvents or other dangerous substances
Contaminated packaging	:	15 01 10 [S] packaging containing residues of or contaminat- ed by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
Country CH 000001229/1		

Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
		4,4'-methylenediphenyl diisocyanate (Number on list 74, 56) 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate (Number on list 74) 1,2-Benzenedicarboxylic acid, di-C9- 11-branched alkyl esters, C10-rich (Number on list 52)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
PIC Ordinance, ChemPICO (814.82)	:	Not applicable
untry CH_00000122941		15/1

Sikaflex[®]-296



Revision Date: 16.11.2023	Version 18.0
Date of last issue: 09.08.2022	

Chemical Risk Reduction Ordinal 814.81)	nce (ORRChem, SR	:	See respective Annex to the Chemi- cal Risk Reduction Ordinance (ORRChem, 814.81) for Conditions of Restriction.
Chemical Risk Reduction Ordinar 814.81)	nce (ORRChem, SR	:	4,4'-methylenediphenyl diisocyanate
Seveso III: Directive 2012/18/EU jor-accident hazards involving da	•	nent	t and of the Council on the control of ma-
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: < 0,01% w/w
	emissions (integrated p	ollu	4 November 2010 on industrial ution prevention and control) ds (VOC) content: < 0,01% w/w

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

H315 H317 H319	 Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	 May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer.
H361f	: Suspected of damaging fertility.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0



H411 :	Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	S
Acute Tox.	Acute toxicity
Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chronic	Long-term (chronic) aquatic hazard
Carc.	Carcinogenicity
Eye Irrit.	Eye irritation
Repr. :	Reproductive toxicity
Resp. Sens.	Respiratory sensitisation
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE :	Specific target organ toxicity - repeated exposure
STOT SE :	Specific target organ toxicity - single exposure
CH BAT :	Switzerland. List of BAT-values
CH SUVA :	Switzerland. Limit values at the work place
CH SUVA / TWA :	Time Weighted Average
CH SUVA / STEL	Short Term Exposure Limit
ADR :	European Agreement concerning the International Carriage of
	Dangerous Goods by Road
CAS :	Chemical Abstracts Service
DNEL :	Derived no-effect level
EC50	Half maximal effective concentration
GHS :	Globally Harmonized System
IATA : IMDG :	International Air Transport Association International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at
LD30 .	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50	Median lethal concentration (concentrations of the chemical in
2000	air that kills 50% of the test animals during the observation
	period)
MARPOL	International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL :	Occupational Exposure Limit
PBT :	Persistent, bioaccumulative and toxic
PNEC :	Predicted no effect concentration
REACH :	Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC :	Substances of Very High Concern
vPvB	Very persistent and very bioaccumulative

Further information

Classification of the	mixture:	Classification procedure:
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method



Print Date 16.11.2023

Revision Date: 16.11.2023 Date of last issue: 09.08.2022 Version 18.0

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN