Sikafloor[®]-16 Pronto

Revision Date: 18.05.2022 Date of last issue: 13.08.2019 Version 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor®-16 Pronto

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Acrylate coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Revision Date: 18.05.2022 Date of last issue: 13.08.2019



te of last issue: 13.08.2019			
Hazard statements	:	H225 H315 H317 H335	Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.
Precautionary statements	:	Prevention:	
		P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		P233	Keep container tightly closed.
		P261	Avoid breathing mist or vapours.
		P264	Wash skin thoroughly after handling.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Version 6.0

Hazardous components which must be listed on the label:

methyl methacrylate tetramethylene dimethacrylate 2-(N-methyl-p-toluidino)ethanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

oomponento			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
methyl methacrylate	80-62-6	Flam. Liq. 2; H225	>=80
	201-297-1	STOT SE 3; H335	
	01-2119452498-28-	Skin Irrit. 2; H315	
	XXXX	Skin Sens. 1; H317	



Revision Date: 18.05.2022 Date of last issue: 13.08.2019 Version 6.0

tetramethylene dimethacrylate	2082-81-7 218-218-1 01-2119967415-30- XXXX	Skin Sens. 1B; H317	>= 5 - < 10
2-(N-methyl-p-toluidino)ethanol	2842-44-6 220-638-5 01-2120827830-56- XXXX	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid meas	ure	S
General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms a	nd e	effects, both acute and delayed
Symptoms	:	Cough Respiratory disorder Allergic reactions Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.
Risks	:	irritant effects sensitising effects
		Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.



Revision Date: 18.05.2022 Date of last issue: 13.08.2019 Version 6.0

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1	Extinguishing media		
	Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
	Unsuitable extinguishing media	:	Water High volume water jet
5.2	Special hazards arising from	the	e substance or mixture
	Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire.
	Hazardous combustion prod- ucts	:	Carbon dioxide (CO2) Carbon monoxide
			No hazardous combustion products are known
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: Use personal protective equipment. Remove all sources of ignition.
	6
	Deny access to unprotected persons.
	Beware of vapours accumulating to form explosive concentra-
	tions. Vapours can accumulate in low areas.
	•

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local

Revision Date: 18.05.2022 Date of last issue: 13.08.2019 Print Date 03.05.2023

Version 6.0

/ national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling :	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
	Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
	Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, inc	luding any incompatibilities
	Requirements for storage : areas and containers	Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.
		Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
	Further information on stor- : age stability	No decomposition if stored and applied as directed.

Sikafloor[®]-16 Pronto

Revision Date: 18.05.2022 Date of last issue: 13.08.2019 Version 6.0



7.3 Specific end use(s)

Specific use(s)

: Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU	
	Further inforr	nation: Indicative			
		STEL	100 ppm	2009/161/EU	
		TWA	50 ppm 210 mg/m3	CH SUVA	
	can lead to v Occupational de Sécurité p maladies pro	Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	100 ppm 420 mg/m3	CH SUVA	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	: Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
ountry CH_00000120902	6

Revision Date: 18.05.2022 Date of last issue: 13.08.2019



Version 6.0

Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice	: F	Prevent product from entering drains.
	I	If the product contaminates rivers and lakes or drains inform
	r	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour		liquid dark blue
Odour	:	unpleasant
Melting point/freezing point	:	-48 °C
Boiling point/boiling range	:	100 °C
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	Upper flammability limit 12,5 %(V)
Lower explosion limit / Lower flammability limit	:	Lower flammability limit 2,1 %(V)
Flash point	:	ca. 10 °C Method: closed cup

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sikafloor®-16 Pronto



Revision Date: 18.05.2022 Date of last issue: 13.08.2019	Version 6.0	Print Date 03.05.202
Decomposition temperature	: No data available	
рН	: Not applicable substance/mixture is non-soluble (in wat	ter)
Viscosity Viscosity, dynamic	: ca. 70 mPa.s (20 °C)	
Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: ca. 38,7 hPa (20 °C)	
Density	: ca. 0,99 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
---------------------	---	--

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sikafloor[®]-16 Pronto



Revision Date: 18.05.2022 Date of last issue: 13.08.2019	Version 6.0	Print Date 03.05.202
Conditions to avoid	: Heat, flames and sparks.	
10.5 Incompatible materials		
Materials to avoid	: No data available	
10.6 Hazardous decompositio No decomposition if stored	-	
SECTION 11: Toxicological	information	
1.1 Information on hazard cla	asses as defined in Regulation (EC) No 1272/200	8
Acute toxicity Not classified based on ava	ailable information.	
Components:		
methyl methacrylate:		
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): 29,8 mg/l Exposure time: 4 h Test atmosphere: vapour	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5.000 mg/kg	
2-(N-methyl-p-toluidino)e	thanol:	
Acute oral toxicity	: LD50 Oral (Rat): > 2.000 mg/kg	
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye	irritation	
Not classified based on ava	ailable information.	
Respiratory or skin sensi	tisation	
Skin sensitisation		
May cause an allergic skin		
Respiratory sensitisation Not classified based on available		
Germ cell mutagenicity Not classified based on ava	ailable information.	
Carcinogenicity		
Not classified based on ava	ailable information.	
Reproductive toxicity		
Not classified based on ava	ailable information.	
Country CH 000000120902		9 / 15

Revision Date: 18.05.2022 Date of last issue: 13.08.2019

Version 6.0



STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

methyl methacrylate:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
		NOEC (Danio rerio (zebra fish)): 9,4 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 69 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
		NOEC : 37 mg/l Exposure time: 21 d Method: OECD Test Guideline 202

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

Revision Date: 18.05.2022 Date of last issue: 13.08.2019 Version 6.0



12.5 Results of PBT and vPvB assessment

Product:

mation

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:	
Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects	
Product: Additional ecological infor-	: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues.
	This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland VeVA/LVA	: 08 01 11 -
Contaminated packaging	: 15 01 10 [S] packaging containing residues of or contaminat- ed by dangerous substances

Revision Date: 18.05.2022 Date of last issue: 13.08.2019 Version 6.0



SECTION 14: Transport information

	14.1	UN	number
--	------	----	--------

ADR	:	UN 1247
IMDG	:	UN 1247
ΙΑΤΑ	:	UN 1247

14.2 UN proper shipping name

ADR	:	METHYL METHACRYLATE MONOMER, STABILIZED
IMDG	:	METHYL METHACRYLATE, MONOMER, STABILIZED
ΙΑΤΑ	:	Methyl methacrylate monomer, stabilized

14.3 Transport hazard class(es)

ADR	:	3
IMDG	:	3
ΙΑΤΑ	:	3

14.4 Packing group

ADR

Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	II F1 339 3 (D/E)
IMDG Packing group Labels EmS Code	:	ll 3 F-E, S-D
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	364 Y341 II Flammable Liquids
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels		353 Y341 II Flammable Liquids
14.5 Environmental hazards		

ADR

Environmentally hazardous	:	no
---------------------------	---	----

IMDG

Revision Date: 18.05.2022 Date of last issue: 13.08.2019 Version 6.0



Marine pollutant no 5 IATA (Passenger) Environmentally hazardous no IATA (Cargo) Environmentally hazardous : no 14.6 Special precautions for user The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations. 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture REACH - Restrictions on the manufacture, placing on Conditions of restriction for the fol-• the market and use of certain dangerous substances, lowing entries should be considered: mixtures and articles (Annex XVII) Number on list 3 International Chemical Weapons Convention (CWC) Not applicable Schedules of Toxic Chemicals and Precursors REACH - Candidate List of Substances of Very High None of the components are listed Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation Not applicable : (Annex XIV) Regulation (EC) No 1005/2009 on substances that de-Not applicable plete the ozone layer Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable 2 tants (recast) PIC Ordinance, ChemPICO (814.82) Not applicable **REACH** Information: All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or

- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sikafloor®-16 Pronto

Revision Date: 18.05.2022 Date of last issue: 13.08.2019



Water hazard class (Germa- ny)	:	WGK 1 slightly hazardous to water Classification according to AwSV, Annex 1 (5.2)
Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: < 0,01% w/w no VOC duties Directive 2010/75/EU of 24 November 2010 on industrial
		emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01% w/w

Version 6.0

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225 H315 H317 H319 H335	: C : N : C : N	Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Aquatic Chronic Eye Irrit. Flam. Liq. Skin Irrit. Skin Sens. STOT SE 2009/161/EU	: E : F : S : S : E	Long-term (chronic) aquatic hazard Eye irritation Flammable liquids Skin irritation Skin sensitisation Specific target organ toxicity - single exposure Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
CH SUVA 2009/161/EU / TWA 2009/161/EU / STEL CH SUVA / TWA CH SUVA / STEL ADR	: L : S : T	Switzerland. Limit values at the work place Limit Value - eight hours Short term exposure limit Time Weighted Average Short Term Exposure Limit European Agreement concerning the International Carriage of

Revision Date: 18.05.2022 Date of last issue: 13.08.2019



Version 6.0

CAS DNEL EC50 GHS IATA IMDG LD50		Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50		Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL		International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: (Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixt	ure:	Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method
3101 3E 3	11000	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN