

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024
Date of last issue: -

Version 1.0

Print Date 18.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor® TC 442 W Part A substrate

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating, Spray application

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Schweiz AG
Tüffenwies 16
8048 Zürich
Telephone : +41 58 436 40 40
Telefax : -
E-mail address of person : EHS@ch.sika.com
responsible for the SDS

1.4 Emergency telephone number

Tox Info Suisse
CH-8028 Zurich
+41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**

P261 Avoid breathing mist or vapours.
P272 Contaminated work clothing should not be allowed out of the workplace.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

P280	Wear protective gloves.
Response:	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal:	
P501	Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one (BIT)

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5 220-120-9 01-2120761540-60-XXXX	Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 specific concentration limit Skin Sens. 1; H317 >= 0,05 % Acute toxicity esti- mate Acute oral toxicity: 597 mg/kg Acute inhalation tox- icity (dust/mist): 0,4 mg/l	>= 0,025 - < 0,05
bronopol (INN)	52-51-7 200-143-0 01-2119980938-15-XXXX	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	>= 0,0025 - < 0,025

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	55965-84-9 911-418-6 01-2120764691-48-XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 %	>= 0,0015 - < 0,0025
--	--	--	----------------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions
See Section 11 for more detailed information on health effects and symptoms.

Risks : May cause an allergic skin reaction.

sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024
Date of last issue: -

Version 1.0

Print Date 18.04.2024

acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	55965-84-9	TWA (inhalable dust)	0,2 mg/m3	CH SUVA
	Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL (inhalable dust)	0,4 mg/m3	CH SUVA

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024
Date of last issue: -

Version 1.0

Print Date 18.04.2024

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Appearance : viscous
Colour : light grey

Odour : pleasant

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : ca. 1.200 mPa.s (20 °C)

Viscosity, kinematic : No data available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024
Date of last issue: -

Version 1.0

Print Date 18.04.2024

Solubility(ies)

Water solubility	:	partly soluble
Partition coefficient: n-octanol/water	:	No data available
Vapour pressure	:	23 hPa
Density	:	ca. 1,05 g/cm ³ (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.



SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : LD50 Oral (Rat): 597 mg/kg

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Assessment : May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 3 mg/l
Exposure time: 48 h

bronopol (INN):

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75, 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that de- : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

PIC Ordinance, ChemPICO (814.82) : Not applicable

Chemical Risk Reduction Ordinance (ORRChem, SR 814.81) : See respective Annex to the Chemical Risk Reduction Ordinance (ORRChem, 814.81) for Conditions of Restriction.

Chemical Risk Reduction Ordinance (ORRChem, SR 814.81) : Nonylphenol, branched, ethoxylated (>1-<2,5 EO)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: < 0,01% w/w

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H330 : Fatal if inhaled.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024

Version 1.0

Print Date 18.04.2024

Date of last issue: -

H331	:	Toxic if inhaled.
H335	:	May cause respiratory irritation.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
CH SUVA	:	Switzerland. Limit values at the work place
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Skin Sens. 1 H317

Classification procedure:

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikafloor® TC 442 W Part A substrate



Revision Date: 18.04.2024
Date of last issue: -

Version 1.0

Print Date 18.04.2024

|| Changes as compared to previous version !

CH / EN