

Revision Date: 22.01.2025 Date of last issue: - Version 1.0

Print Date 22.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Ucrete[®] PT2 PRG Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 127	/2/2008)
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure if inhaled.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: - Version 1.0

Print Date 22.01.2025

2.2 Label elements

Labelling (REGULATION (Hazard pictograms	(EC) :	No 1272/2008)	!
Signal word	:	Danger	
Hazard statements	:	H317 M H319 C H332 H H334 M H335 M H351 S H373 M	auses skin irritation. ay cause an allergic skin reaction. auses serious eye irritation. armful if inhaled. ay cause allergy or asthma symptoms or breath- g difficulties if inhaled. ay cause respiratory irritation. uspected of causing cancer. ay cause damage to organs through prolonged repeated exposure if inhaled.
Precautionary statements	:	Prevention: P201 P260 P264 P280 Response: P304 + P340 + P342 + P311	Obtain special instructions before use. Do not breathe mist or vapours. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection. - P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues 4,4'-methylenediphenyl diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Ucrete® PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: - Version 1.0

Print Date 22.01.2025

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 % specific concentration limit Skin Irrit. 2; H315 >= 5 % specific concentration limit StoT SE 3; H335 >= 5 %	>= 60 - < 80

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Ucrete[®] PT2 PRG Part B



Version 1.0 Revision Date: 22.01.2025 Print Date 22.01.2025 Date of last issue: ->= 40 - < 60 4,4'-methylenediphenyl diisocya-101-68-8 Acute Tox. 4; H332 202-966-0 Skin Irrit. 2: H315 nate 01-2119457014-47-Eye Irrit. 2; H319 XXXX Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit STOT SE 3; H335 >= 5 % specific concentration limit Skin Irrit. 2; H315 >= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 % Acute toxicity estimate Acute inhalation toxicity (dust/mist): 1,5 mg/l

For explanation of abbreviations see section 16.

:

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Ucrete[®] PT2 PRG Part B



evision Date: 22.01.2025 Date of last issue: -		Version 1.0	Print Date 22.01.202
If inhaled	:	Move to fresh air. Consult a physician after significant expo	osure.
In case of skin contact	:	Take off contaminated clothing and shoe Wash off with soap and plenty of water. If symptoms persist, call a physician.	es immediately.
In case of eye contact	:	Immediately flush eye(s) with plenty of w Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a special	
If swallowed	:	Do not induce vomiting without medical a Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unco	
4.2 Most important symptoms	s and e	ffects, both acute and delayed	
Symptoms	:	Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed informa and symptoms.	ation on health effects
Risks	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms of ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through pr exposure if inhaled.	
		irritant effects sensitising effects	
4.3 Indication of any immedia	te med	ical attention and special treatment ne	eded
Treatment	:	Treat symptomatically.	



Revision Date: 22.01.2025 Date of last issue: - Version 1.0

Print Date 22.01.2025

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	
		ide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-	:	No hazardous combustion products are known
ucts		

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Personal precautions Use personal protective equipment. Deny access to unprotected persons. 6.2 Environmental precautions Environmental precautions Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid formation of aerosol.	
	Avoid exceeding the given occupational exposure limits (see	
	section 8).	
	Do not get in eyes, on skin, or on clothing.	
	For personal protection see section 8.	

_

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: -		Version 1.0	Print Date 22.01.2025
		Persons with a history of skin sensitisation pro ma, allergies, chronic or recurrent respiratory of not be employed in any process in which this r used. Smoking, eating and drinking should be prohib plication area. Provide sufficient air exchange and/or exhaust Follow standard hygiene measures when hand products	disease should nixture is being nited in the ap- t in work rooms.
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection	ı.
Hygiene measures	:	Handle in accordance with good industrial hyg practice. When using do not eat or drink. Whe smoke. Wash hands before breaks and at the	n using do not
7.2 Conditions for safe storage,	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well place. Containers which are opened must be o sealed and kept upright to prevent leakage. St ance with local regulations.	arefully re-
Further information on stor- age stability	:	No decomposition if stored and applied as dire	ected.
7.3 Specific end use(s)			
Specific use(s)	:	Cleaning with aprotic polar solvents must be a Consult most current local Product Data Shee use.	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	CH SUVA		
	Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Health and Safety Ex-					
	ecutive (Occupational Medicine and Hygiene Laboratory)					
	STEL 0,02 mg/m3 CH SUVA (NCO)					
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m3 (NCO)	CH SUVA		
	Further information: Toxic by skin resorption possible; Substanc- es, which are easily absored through the skin, can give by addi-					

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Ucrete[®] PT2 PRG Part B

Revision Date: 22.01.2025 Date of last issue: - Version 1.0

Print Date 22.01.2025

inhalation by an S can lead Executive (Od					
	STEL	0,02 mg/m3 (NCO)	CH SUVA		

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	4,4'- diaminodiphenyl- methane: 10 μg/g creatinine (Urine)	Immediately after exposure or after working hours	CH BAT
		4,4'- diaminodiphenyl- methane: 5 nmol/mmol creati- nine (Urine)	Immediately after exposure or after working hours	CH BAT

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water	
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.	
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated	

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Version 1.0 Print Date 22.01.2025 Date of last issue: exposure levels, the hazards of the product and the safe working limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas. **Environmental exposure controls** General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

	Physical state Colour		liquid brown
C	Ddour	:	musty
	/lelting point/ range / Freez- ng point	:	No data available
E	Boiling point/boiling range	:	No data available
F	Flammability (solid, gas)	:	No data available
ι	Jpper/lower flammability or o	exp	losive limits
	Upper explosion limit / Upper flammability limit	:	No data available
	Lower explosion limit / Lower flammability limit	:	No data available
F	Flash point	:	> 200 °C Method: closed cup

_

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: -		Version 1.0	Print Date 22.01.2025
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	substance/mixture reacts with water	
Viscosity Viscosity, dynamic	:	89 mPa.s	
Viscosity, kinematic	:	No data available	
Solubility(ies) Water solubility	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	1,23 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

_

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: -	Version 1.0	Print Date 22.01.2025
10.4 Conditions to avoid Conditions to avoid	: No data available	
10.5 Incompatible materials Materials to avoid	: No data available	
10.6 Hazardous decomposition p	:	
	No hazardous decomposition products are k	nown.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity	:	LD50 Oral (Rat): > 10.000 mg/kg
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after short term inhalation.
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 9.400 mg/kg
4,4'-methylenediphenyl diiso	су	anate:
Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.





Revision Date: 22.01.2025 Date of last issue: - Version 1.0

Print Date 22.01.2025

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: - Version 1.0

Print Date 22.01.2025

Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

<u>Product:</u> Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects	

Product:

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

 The generation of waste should be avoided or minimized wherever possible.
 Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
 Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
 Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
 Avoid dispersal of spilled material and runoff and contact with

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: -	Version 1.0	Print Date 22.01.2025
	soil, waterways, drains and sewers.	
Waste code Switzerland VeVA/LVA	: 08 05 01 [S] waste isocyanates	

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good
14.5 Environmental hazards		

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: -	Version	1.0		Print Date 22.01.2025
REACH Information:	All substances contain - registered by our up - registered by us, and - excluded from the re - exempted from the r	strea d/or gulat	m suppliers, and/or tion, and/or	
REACH - Restrictions on the mathematic the market and use of certain date mixtures and articles (Annex X)	angerous substances,	:	Conditions of restriction lowing entries should Number on list 3	
			Number on list 56: Dip thanediisocyanate, iso homologues, 4,4'-met diisocyanate	omeres and
			Number on list 74: Dip thanediisocyanate, iso homologues, 4,4'-met diisocyanate	omeres and
			Number on list 75:	
REACH - Candidate List of Sub Concern for Authorisation (Artic		:	None of the compone (=> 0.1 %).	nts are listed
REACH - List of substances sul (Annex XIV)	pject to authorisation	:	Not applicable	
Regulation (EC) on substances layer	that deplete the ozone	:	Not applicable	
Regulation (EU) 2019/1021 on tants (recast)	persistent organic pollu-	:	Not applicable	
PIC Ordinance, ChemPICO (81	4.82)	:	Not applicable	
Ordinance on Protection agains Threshold quantity according to nance (MAO 814.012)		:	20.000 kg	
Chemical Risk Reduction Ordin (ORRChem, SR 814.81)	should be c Annex 1.11	onsio Dan	striction for the followin dered: gerous liquid substanc ediisocyanate, isomere	es

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: -		Version 1.0	Print Date 22.01.2025
		logues: Annex 2.9 Plastics at 4,4'-methylenediphenyl diiso tics and additives	
Waters Protection Ordinance Water pollution class	•	O 814.201) slightly hazardous to water Classification according to AwSV, Anne	ex 1 (5.2)
Volatile organic compounds	:	Law on the incentive tax for volatile org (VOCV) no VOC duties	anic compounds
		Directive 2010/75/EU of 24 November 2 emissions (integrated pollution prevention Not applicable	

Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	 May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	: May cause respiratory irritation.
H351	: Suspected of causing cancer.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: - Version 1.0

Print Date 22.01.2025

Full text of other abbreviations

 Acute toxicity Carcinogenicity Eye irritation Respiratory sensitisation Skin irritation Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure Switzerland. List of BAT-values Switzerland. Limit values at the work place Time Weighted Average Short Term Exposure Limit European Agreement concerning the International Carriage of
 Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation
 period) International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 Occupational Exposure Limit Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method

Ucrete[®] PT2 PRG Part B



Revision Date: 22.01.2025 Date of last issue: -		Version 1.0	Print Date 22.01.2025
STOT RE 2	H373	Calculation method	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN