

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Ergodur Pronto Hardener Pro Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Catalyst, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Schweiz AG
Tüffenwies 16
8048 Zürich
Telephone : +41 58 436 40 40
Telefax : -
E-mail address of person : EHS@ch.sika.com
responsible for the SDS

1.4 Emergency telephone number

Tox Info Suisse
CH-8028 Zurich
+41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type D	H242: Heating may cause a fire.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 1B	H360D: May damage the unborn child.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

Hazard pictograms :



Signal word : Danger

Hazard statements : H242 Heating may cause a fire.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360D May damage the unborn child.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234 Keep only in original packaging.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Hazardous components which must be listed on the label:

dibenzoyl peroxide
dicyclohexyl phthalate

Additional Labelling

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: This substance/mixture contains components considered to have endocrine disrupting properties affecting human health, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
dibenzoyl peroxide	94-36-0 202-327-6 01-2119511472-50-XXXX	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	>= 40 - < 60
dicyclohexyl phthalate	84-61-7 201-545-9 01-2119978223-34-XXXX	Skin Sens. 1; H317 Repr. 1B; H360D Aquatic Chronic 3; H412	>= 40 - < 60

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	Allergic reactions Excessive lachrymation See Section 11 for more detailed information on health effects and symptoms.
Risks	:	irritant effects sensitising effects toxic effects for reproduction May cause an allergic skin reaction. Causes serious eye irritation. May damage the unborn child.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.
-----------	---	------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.
Unsuitable extinguishing media	:	High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Avoid breathing dust.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Open drum carefully as content may be under pressure.
Pregnant women or women of child-bearing age should not be exposed to this product.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Store in accordance with local regulations.

Recommended storage temperature : 5 - 25 °C

Further information on storage stability : Keep in a dry place.
No decomposition if stored and applied as directed.

Keep in a dry place.
No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
dibenzoyl peroxide	94-36-0	TWA (inhalable dust)	5 mg/m ³	CH SUVA
Further information: Skin effect nearly absent or very weak (conc. 50%), National Institute for Occupational Safety and Health				
		STEL (inhalable dust)	5 mg/m ³	CH SUVA

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

general dust value

Form of exposure	Peak-limit: excursion factor (category)	Value type	Control parameters	Basis
alveolate dust		TWA	3 mg/m ³	CH SUVA
inhalable dust		TWA	10 mg/m ³	CH SUVA

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Recommended: Butyl rubber/nitrile rubber gloves.
Contaminated gloves should be removed.
- Skin and body protection : Dust impervious protective suit
Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
particulate filter P
P1: Inert material; P2, P3: hazardous substances
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : solid
Appearance : powder
Colour : white
- Odour : slight
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flammability : not auto-flammable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : ca. 180 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : 60 °C
Decomposes on heating.

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : ca. 1 hPa (20 °C)

Density : ca. 1,24 g/cm³ (20 °C)

Bulk density : 640 kg/m³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

Miscibility with water : immiscible



SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Decomposes on heating.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids and bases
Reducing agents
Heavy metals

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

dibenzoyl peroxide:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 24,3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

May damage the unborn child.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : This substance/mixture contains components considered to have endocrine disrupting properties affecting human health, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

SECTION 12: Ecological information

12.1 Toxicity

Components:

dibenzoyl peroxide:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

12.2 Persistence and degradability

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste code Switzerland : 16 09 03 -
VeVA/LVA

Contaminated packaging : 15 01 10 [S] packaging containing residues of or contaminat-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

ed by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3106
IMDG : UN 3106
IATA : UN 3106

14.2 UN proper shipping name

ADR : ORGANIC PEROXIDE TYPE D, SOLID
(dibenzoyl peroxide)
IMDG : ORGANIC PEROXIDE TYPE D, SOLID
(dibenzoyl peroxide)
IATA : Organic peroxide type D, solid
(dibenzoyl peroxide)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 5.2	
IMDG	: 5.2	
IATA	: 5.2	HEAT

14.4 Packing group

ADR
Packing group : Not assigned by regulation
Classification Code : P1
Labels : 5.2
Tunnel restriction code : (D)

IMDG
Packing group : Not assigned by regulation
Labels : 5.2
EmS Code : F-J, S-R

IATA (Cargo)

Packing instruction (cargo aircraft) : 570
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

IATA (Passenger)

Packing instruction (passenger aircraft) : 570
Packing group : Not assigned by regulation
Labels : Organic Peroxides, Keep Away From Heat

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75

dicyclohexyl phthalate (Number on list 30)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : dicyclohexyl phthalate

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

tants (recast)

PIC Ordinance, ChemPICO (814.82) : Not applicable

Chemical Risk Reduction Ordinance (ORRChem, SR 814.81) : dicyclohexyl phthalate

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

The product belongs to group 1 according to the Swiss Chemicals Ordinance (ChemO 813.11).

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H241 : Heating may cause a fire or explosion.

H317 : May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

H319	:	Causes serious eye irritation.
H360D	:	May damage the unborn child.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Org. Perox.	:	Organic peroxides
Repr.	:	Reproductive toxicity
Skin Sens.	:	Skin sensitisation
CH SUVA	:	Switzerland. Limit values at the work place
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Org. Perox. D	H242
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 1B	H360D
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sika® Ergodur Pronto Hardener Pro Part B



Revision Date: 17.01.2024

Version 3.0

Print Date 17.01.2024

Date of last issue: 25.05.2022

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

CH / EN