

Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikaflex[®]-403 Tank & Silo

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

·

Hazard pictograms

Signal word	:	Danger	
Hazard statements	:	H334	May cause allergy or asthma symptoms or breath- ing difficulties if inhaled.
Precautionary statements	:	Prevention P261	: Avoid breathing mist or vapours.

Sikaflex[®]-403 Tank & Silo

Revision Date: 28.04.2024 Date of last issue: 18.12.2023



P284In case of inadequate ventilation wear respiratory protection.Response:IF INHALED: Remove person to fresh air and keep comfortable for breathing.P304 + P340IF INHALED: Remove person to fresh air and keep comfortable for breathing.P342 + P311If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.Disposal:Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

4,4'-methylenediphenyl diisocyanate

Additional Labelling

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Version 2.0

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Urea,N,N"-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5

Sikaflex[®]-403 Tank & Silo

Revision Date: 28.04.2024 Date of last issue: 18.12.2023



Version 2.0

4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H315 Resp. Sens. 1; H314 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315	>= 0,1 - < 0,5
		>= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate	
		Acute inhalation tox- icity (dust/mist): 1,5 mg/l	
Alcohols, C11-14-iso-, C13-rich	68526-86-3 271-235-6 01-2119454259-32- XXXX	Skin Irrit. 2; H315 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,1 - < 0,25
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.

Sikaflex[®]-403 Tank & Silo



Revision Date: 28.04.2024 Date of last issue: 18.12.2023		Version 2.0	Print Date 29.04
In case of skin contact	:	Take off contaminated clothing and shoes immed Wash off with soap and plenty of water. If symptoms persist, call a physician.	diately.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	person.
4.2 Most important symptoms a	nd e	effects, both acute and delayed	
Symptoms	:	Asthmatic appearance Allergic reactions See Section 11 for more detailed information on and symptoms.	health effects
Risks	:	sensitising effects	
		May cause allergy or asthma symptoms or breat ties if inhaled.	hing difficul-
4 3 Indication of any immediate	me	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting mea	sur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/ca ide/sand/foam/alcohol resistant foam/chemical pe extinction.	
5.2 Special hazards arising from	n the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	apparatus.
Further information	:	Standard procedure for chemical fires.	

Print Date 29.04.2024

Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Version 2.0

SECTION 6: Accidental release measures

6.1 Personal precautions, protect	ctive	e equipment and emergency procedures
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
6.3 Methods and material for co	ntai	nment and cleaning up
Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	incl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.

Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Version 2.0



7.3 Specific end use(s)

Specific use(s)

: Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m3 (NCO)	CH SUVA
	es, which are of tional skin reso inhalation by th an S can lead Executive (Oc	ation: Toxic by skin easily absored throu option a substancial he airways., Sensiti to very strong allerg cupational Medicine child is not to be exp	ugh the skin, can g I higher risk compa zers; Substances gic reactions., Hea and Hygiene Lab	give by addi- ared to only marked with alth and Safety poratory), Harm
		STEL	0,02 mg/m3 (NCO)	CH SUVA

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	4,4'- diaminodiphenyl- methane: 10 µg/g creatinine (Urine)	Immediately after exposure or after working hours	CH BAT
		4,4'- diaminodiphenyl- methane: 5 nmol/mmol creati- nine (Urine)	Immediately after exposure or after working hours	CH BAT

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection		: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling
untry CH 10000012730		

Sikaflex[®]-403 Tank & Silo

Revision Date: 28.04.2024



Date of last issue: 18.12.2023		T THE BALO LON
	chemical products. Reference number EN 3 facturer specifications.	374. Follow manu-
	Suitable for short time use or protection aga Butyl rubber/nitrile rubber gloves (> 0,1 mm Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	
Skin and body protection	: Protective clothing (e.g. Safety shoes acc. t long-sleeved working clothing, long trousers and protective boots are additionaly recomm and stirring work.	s). Rubber aprons
Respiratory protection	 In case of inadequate ventilation wear respinent respirator selection must be based on known exposure levels, the hazards of the product ing limits of the selected respirator. Use a properly fitted NIOSH approved air-prespirator complying with an approved stansessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 100 Ensure adequate ventilation. This can be adexisted extraction or by general ventilation. ods for determining inhalation exposure). The ticular to the mixing / stirring area. In case to keep the concentrations under the occup limits then respiration protection measures 	wn or anticipated and the safe work- burifying or air-fed dard if a risk as- 000 ppm chieved by local . (EN 689 - Meth- his applies in par- his is not sufficent pational exposure

Version 2.0

Environmental exposure controls

advice

: Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste various
Odour	:	characteristic
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available

Sikaflex[®]-403 Tank & Silo



Revision Date: 28.04.2024 Date of last issue: 18.12.2023		Version 2.0	Print Date 29
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or e	exp	plosive limits	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 100 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	ca. 1,20 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Version 2.0



SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid	: No data available
---------------------	---------------------

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l

Sikaflex[®]-403 Tank & Silo

Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Version 2.0



Test atmosphere: dust/mist Method: Calculation method

Skin corrosion/irritation Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Sikaflex[®]-403 Tank & Silo



Revision Date: 28.04.2024 Date of last issue: 18.12.2023		Version 2.0	Print Date 29.
Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/ Exposure time: 96 h	I
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater gre 100 mg/l Exposure time: 72 h	en alga)): >
Alcohols, C11-14-iso-, C13-r	rich	:	
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 0, Exposure time: 96 h	42 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia (water flea)): 0,71 mg/l Exposure time: 48 h	
M-Factor (Acute aquatic tox- icity)	:	1	
M-Factor (Chronic aquatic toxicity)	:	1	
12.2 Persistence and degradabil No data available	ity		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB as	sse	ssment	
Product:			
Assessment	:	This substance/mixture contains no components to be either persistent, bioaccumulative and toxic very persistent and very bioaccumulative (vPvB) 0.1% or higher	c (PBT), or
12.6 Endocrine disrupting prope	rtie	s	
Product:			
Assessment	:	The substance/mixture does not contain compor ered to have endocrine disrupting properties acc REACH Article 57(f) or Commission Delegated r (EU) 2017/2100 or Commission Regulation (EU) levels of 0.1% or higher.	cording to regulation

12.7 Other adverse effects

Sikaflex[®]-403 Tank & Silo



Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Version 2.0

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.2	2 UN proper shipping name		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.3	3 Transport hazard class(es)		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.4	4 Packing group		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good
	IATA (Passenger)	:	Not regulated as a dangerous good

Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Version 2.0



14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture : Not applicable

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

4,4'-methylenediphenyl diisocyanate (Number on list 74, 56) 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (Number on list 52)

See respective Annex to the Chemi-

cal Risk Reduction Ordinance (ORRChem, 814.81) for Conditions

REACH - Candidate List of Substances of Very High : None of the components are listed (=> 0.1 %).

Not applicable

Not applicable

of Restriction.

÷

÷

÷

- REACH List of substances subject to authorisation : Not applicable (Annex XIV)
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer
- Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable : tants (recast)

PIC Ordinance, ChemPICO (814.82)

Concern for Authorisation (Article 59).

Chemical Risk Reduction Ordinance (ORRChem, SR 814.81)

Sikaflex[®]-403 Tank & Silo

Print Date 29.04.2024

Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Version 2.0

Chemical Risk Reduction Ordinance (ORRChem, SR : 4,4'-methylenediphenyl diisocyanate 814.81)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: <= 3% w/w no VOC duties
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01% w/w

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H411	:	Toxic to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Carc.	:	Carcinogenicity

Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Print Date 29.04.2024

Version 2.0

Eye Irrit. Resp. Sens. Skin Irrit. Skin Sens. STOT RE STOT SE CH BAT CH SUVA CH SUVA / TWA CH SUVA / STEL	 Eye irritation Respiratory sensitisation Skin irritation Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure Switzerland. List of BAT-values Switzerland. Limit values at the work place Time Weighted Average Short Term Exposure Limit
ADR	: European Agreement concerning the International Carriage of
CAS	Dangerous Goods by Road Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
ΙΑΤΑ	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from
OEL	Ships, 1973 as modified by the Protocol of 1978 Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Resp. Sens. 1	H334	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN

Sikaflex[®]-403 Tank & Silo

Revision Date: 28.04.2024 Date of last issue: 18.12.2023 Version 2.0

