according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



Date of last issue: 15.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Sikafloor®-377/-3290 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier Sika Schweiz AG

Tüffenwies 16 8048 Zürich

Telephone +41 58 436 40 40

Telefax

E-mail address of person responsible for the SDS

rpc@ch.sika.com

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich

+41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 H332: Harmful if inhaled. Skin irritation, Category 2 H315: Causes skin irritation. Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. Carcinogenicity, Category 2 H351: Suspected of causing cancer.

H335: May cause respiratory irritation. Specific target organ toxicity - single exposure, Category 3, Respiratory system

Specific target organ toxicity - repeated H373: May cause damage to organs through prolonged or repeated exposure.


exposure, Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

Sikafloor®-377/-3290 Part B

Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breath-

ing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged

or repeated exposure.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/

eve protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues methylenediphenyl diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikafloor®-377/-3290 Part B

Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 — specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 % specific concentration limit Skin Irrit. 2; H315 >= 5 % specific concentration limit Skin Irrit. 2; H315 >= 5 %	>= 40 - < 60

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



methylenediphenyl diisocyanate	26447-40-5 905-806-4 615-005-00-9 01-2119457015-45- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 ——————————————————————————————————	>= 40 - < 60
		specific concentration limit Skin Irrit. 2; H315 >= 5 %	
		specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks : irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



Date of last issue: 15.05.2023

ucts

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Personal precautions

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid formation of aerosol. Advice on safe handling

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products

Normal measures for preventive fire protection. Advice on protection against

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikafloor®-377/-3290 Part B

Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

fire and explosion

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Cleaning with aprotic polar solvents must be avoided.

Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	CH SUVA
_	Further information: Sensitizers; Substances marked with an S			
	can lead to ver	y strong allergic rea	actions., Health ar	nd Safety Ex-
	ecutive (Occupational Medicine and Hygiene Laboratory)			
		STEL	0,02 mg/m3 (NCO)	CH SUVA
		TWA	0,01 mg/m3 (NCO)	98/24/EC I
	Further information: Skin, Dermal and respiratory sensitisation, Binding			
		STEL	0,02 mg/m3 (NCO)	98/24/EC I
methylenediphenyl diisocyanate	26447-40-5	TWA	0,02 mg/m3 (NCO)	CH SUVA
	Further information: Sensitizers; Substances mark		Substances marke	d with an S
	can lead to very strong allergic reactions., Health and Safety Ex-			
	ecutive (Occupational Medicine and Hygiene Laboratory)			
		STEL	0,02 mg/m3 (NCO)	CH SUVA
		TWA	0,01 mg/m3 (NCO)	98/24/EC I
	Further information	ation: Skin, Dermal	and respiratory se	ensitisation,
		STEL	0,02 mg/m3	98/24/EC I

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



Date of last issue: 15.05.2023

Revision Date: 01.12.2025

(NCO)

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Hand protection

Safety glasses with side-shields conforming to EN166

: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mix-

ing and stirring work.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

General advice

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Colour light brown Odour musty

Melting point/ range / Freez-

ing point

: No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit /

Lower flammability limit

No data available

: > 150 °C Flash point

Method: open cup

No data available Auto-ignition temperature

Decomposition temperature No data available

рН Not applicable

substance/mixture is non-soluble (in water)

Viscosity

: 70 - 90 mPa.s (20 °C) Viscosity, dynamic

Viscosity, kinematic $> 20,5 \text{ mm}2/\text{s} (40 ^{\circ}\text{C})$

Solubility(ies)

Water solubility insoluble

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0.01 hPa

Density ca. 1,18 g/cm3 (20 °C)

Relative vapour density No data available

Particle characteristics No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l


Exposure time: 96 h

Country CH 100000008956

11 / 17

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



Date of last issue: 15.05.2023

Revision Date: 01.12.2025

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 1.640

mg/l

Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikafloor®-377/-3290 Part B

Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Waste code Switzerland

VeVA/LVA

: 08 05 01 [S] waste isocyanates

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B



Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 56:

Diphenylmethanediisocyanate, isomeres and homologues, methylenediphenyl diisocyanate

Number on list 74:

Diphenylmethanediisocyanate, isomeres and homologues, methylenediphenyl diisocyanate

diprieriyi diisocyanate

Number on list 75

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Regulation (EU) No 2024/590 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

PIC Ordinance, ChemPICO (814.82) : Not applicable

Ordinance on Protection against Major Accidents

Threshold quantity according to Major Accidents Ordi-

nance (MAO 814.012)

20.000 kg

Chemical Risk Reduction Ordinance

(ORRChem, SR 814.81)

Conditions of restriction for the following annexes

should be considered:

Annex 1.11 Dangerous liquid substances

Diphenylmethanediisocyanate, isomeres and homo-

logues: Annex 2.9 Plastics and additives

methylenediphenyl diisocyanate: Annex 2.9 Plastics

and additives

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

egula-



Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

Waters Protection Ordinance (WPO 814.201)

Water pollution class : slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV) no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention

and control)
Not applicable

Other regulations:

Article 13 Maternity ordinance and Safety Ordinance (SR 822.111.52): Expectant and nursing mothers are not permitted to come into contact with this product during the course of their work. However, if a risk assessment establishes that there is no specific risk to the health of mothers or their children or that any such risk can be excluded by taking suitable protective measures, mothers may work with this product (substance/preparation) (Art. 63 Ordinance 1 to the Employment Act; SR 822.111).

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H351 : Suspected of causing cancer.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

Full text of other abbreviations

Acute Tox. : Acute toxicity

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-377/-3290 Part B

Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025

Date of last issue: 15.05.2023

Carc. Carcinogenicity Eve irritation Eve Irrit.

Resp. Sens. Respiratory sensitisation

Skin Irrit. Skin irritation Skin sensitisation Skin Sens.

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

98/24/EC I Europe. Chemical Agents Directive - Annex I: Binding occupa-

tional exposure limit values

Switzerland. Limit values at the work place CH SUVA

Limit values Short-term 98/24/EC I / STEL Limit values 8 hours 98/24/EC I / TWA CH SUVA / TWA Time Weighted Average CH SUVA / STEL Short Term Exposure Limit

European Agreement concerning the International Carriage of **ADR**

Dangerous Goods by Road

Chemical Abstracts Service CAS Derived no-effect level **DNEL**

EC50 Half maximal effective concentration

GHS Globally Harmonized System

International Air Transport Association IATA

IMDG International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic **PNEC** Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament

> and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sikafloor®-377/-3290 Part B

Revision Date: 01.12.2025 Version 6.0 Print Date 01.12.2025 Date of last issue: 15.05.2023

Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

CH / EN