Sika[®] Aktivator-100



Revision Date: 21.02.2025 Date of last issue: 30.01.2025 Version 35.0

Print Date 21.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sika[®] Aktivator-100

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person responsible for the SDS	:	EHS@ch.sika.com

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air- ways.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sika[®] Aktivator-100

Revision Date: 21.02.2025 Date of last issue: 30.01.2025 Version 35.0

Print Date 21.02.2025

2.2 Label elements

Labelling (REGULATION (EC)	No 1272/2008	8)
Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H225 H304 H315 H317 H318 H336 H411	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention	:
		P210 P273 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/ face protection.
		Response:	
		P301 + P31	0 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
		P305 + P35	1 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove con- tact lenses, if present and easy to do. Con- tinue rinsing. Immediately call a POISON CENTER/ doctor.
		P331 P370 + P37	
		P391	alcohol-resistant foam to extinguish. Collect spillage.

Hazardous components which must be listed on the label:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics N-(3-(trimethoxysilyl)propyl)ethylenediamine tris(dodecylbenzenesulphonato-O)(propan-2-olato)titanium

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Revision Date: 21.02.2025 Date of last issue: 30.01.2025

Sika[®] Aktivator-100

Version 35.0

Print Date 21.02.2025

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components Chemical name	CAS-No.	Classification	Concentration
Chemical hame	EC-No.	Classification	(% w/w)
	Registration number		(/o vv/vv)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Contains: cyclohexane 2 %	Not Assigned 927-510-4 265-151-9 01-2119475515-33- XXXX	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>=80
ethanol	64-17-5 200-578-6 01-2119457610-43- XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 specific concentration limit Eye Dam. 2; H319 >= 50 %	>= 5 - < 10
N-(3- (trimethoxysi- lyl)propyl)ethylenediamine Contains: N,N'-bis[3- (trimethoxysi- lyl)propyl]ethylenediamine <= 3 % 1-(2-Aminoethyl)-2,2-dimethoxy-1- aza-2-silacyclopentane <= 3 %	1760-24-3 217-164-6 01-2119970215-39- XXXX	Eye Dam. 1; H318 Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 2,5 - < 3
tris(dodecylbenzenesulphonato- O)(propan-2-olato)titanium	61417-55-8 262-777-4	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 2,5 - < 3

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Aktivator-100



Revision Date: 21.02.2025 Version 35.0 Print Date 21.02.2025 Date of last issue: 30.01.2025 Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled Move to fresh air. : Consult a physician after significant exposure. In case of skin contact : Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. In case of eye contact Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. If swallowed Do not induce vomiting without medical advice. : Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Aspiration may cause pulmonary oedema and pneumonitis. Symptoms Allergic reactions **Excessive lachrymation** Ervthema Dermatitis Loss of balance Vertiao See Section 11 for more detailed information on health effects and symptoms. Risks Risk of serious damage to the lungs (by aspiration). irritant effects sensitising effects May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Sika[®] Aktivator-100



Revision Date: 21.02.2025 Date of last issue: 30.01.2025 Version 35.0

Print Date 21.02.2025

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
----------------------	---	--

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-



Revision Date: 21.02.2025 Date of last issue: 30.01.2025

Version 35.0

miculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling :		 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
	Advice on protection against : fire and explosion		Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
	Hygiene measures :		Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, inc	clı	uding any incompatibilities
	Requirements for storage : areas and containers		Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
	Further information on stor- : age stability		No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s) :		Consult most current local Product Data Sheet prior to any use.



Revision Date: 21.02.2025 Date of last issue: 30.01.2025

Sika[®] Aktivator-100

Version 35.0

Print Date 21.02.2025

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
ethanol	64-17-5	TWA	500 ppm 960 mg/m3	CH SUVA	
	Further information: National Institute for Occupational Safety and Health, National Institute of Research and Safety for the preven- tion of work accidents and occupational diseases, Harm to the unborn child is not to be expected when the OEL-value is re- spected				
		STEL	1.000 ppm 1.920 mg/m3	CH SUVA	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form	Control parame-	Basis *			
		of exposure)	ters *				
methanol	67-56-1	TWA	200 ppm	2006/15/EC			
			260 mg/m3				
	Further inforr	nation: Indicative, Ide	entifies the possibi	ility of signifi-			
	cant uptake t	hrough the skin					
		TŴA	200 ppm	CH SUVA			
			260 mg/m3				
	Further inforr	Further information: Toxic by skin resorption possible; Substanc-					
	es, which are	es, which are easily absored through the skin, can give by addi-					
	tional skin re	tional skin resoption a substancial higher risk compared to only					
	inhalation by	the airways., Nationa	al Institute for Occ	upational			
	Safety and H	ealth, National Institu	ute of Research ar	nd Safety for			
	the preventio	the prevention of work accidents and occupational diseases,					
		Harm to the unborn child is not to be expected when the OEL-					
		value is respected					
	· ·	STEL	400 ppm 520 mg/m3	CH SUVA			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling
Nuntry CH 00000033123		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Aktivator-100



Revision Date: 21.02.2025 Date of last issue: 30.01.2025	Version 35.0	Print Date 21.02.2025
	chemical products. Reference number EN facturer specifications. Suitable for short time use or protection a Butyl rubber/nitrile rubber gloves (> 0,1 m Contaminated gloves should be removed Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	igainst splashes: im)
Skin and body protection	: Protective clothing (e.g. Safety shoes acc long-sleeved working clothing, long trouse and protective boots are additionaly recor and stirring work.	ers). Rubber aprons
Respiratory protection	 In case of inadequate ventilation wear respective respecting respective respective respective respective respective res	10000 ppm achieved by local on. (EN 689 - Meth- This applies in par- e this is not sufficent upational exposure
Environmental exposure co	ntrols	
General advice	: Prevent product from entering drains.	

respective authorities.

If the product contaminates rivers and lakes or drains inform

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour : colourless	
Odour : hydrocarbon-like	
Melting point/ range / Freez- : No data available ing point)
Boiling point/boiling range : ca. 78 °C	
Flammability (solid, gas) : No data available)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Aktivator-100



Revision Date: 21.02.2025 Date of last issue: 30.01.2025		Version 35.0	Print Date 21.02.2025
Upper/lower flammability or Upper explosion limit / Up- per flammability limit	-		
Lower explosion limit / Lower flammability limit	:	1,1 %(V)	
Flash point	:	ca4 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	58 hPa	
Density	:	ca. 0,727 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available



Revision Date: 21.02.2025
Date of last issue: 30.01.2025

Sika[®] Aktivator-100

Version 35.0

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactio	ns
---------------------------------------	----

Hazardous reactions	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.
10.4 Conditions to avoid Conditions to avoid	:	Heat, flames and sparks.
10.5 Incompatible materials Materials to avoid	:	No data available
10.6 Hazardous decomposition	orod	lucts
Hazardous decomposition	:	methanol

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

products

Not classified due to lack of data.

Components:

N-(3-(trimethoxysilyl)propyl)ethylenediamine:

Acute oral toxicity : LD50 Oral (Rat): 2.995 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Aktivator-100

Jika®

Revision Date: 21.02.2025 Date of last issue: 30.01.2025 Version 35.0

Print Date 21.02.2025

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

2

Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or



Revision Date: 21.02.2025 Date of last issue: 30.01.2025	Version 35.0	Print Date 21.02.2025
	very persistent and very bioaccumulative (vPvB 0.1% or higher) at levels of
12.6 Endocrine disrupting proper	ies	
Product:		
Assessment	 The substance/mixture does not contain component ered to have endocrine disrupting properties ac REACH Article 57(f) or Commission Delegated (EU) 2017/2100 or Commission Regulation (EU levels of 0.1% or higher. 	cording to regulation
12.7 Other adverse effects		
Product:		
Additional ecological infor- mation	 An environmental hazard cannot be excluded ir unprofessional handling or disposal. Toxic to aquatic life with long lasting effects. 	ι the event of

SECTION 13: Disposal considerations

13.1	Waste	treatment	methods
------	-------	-----------	---------

Sika[®] Aktivator-100

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland VeVA/LVA	:	08 01 11 [S] Paint and varnish waste containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR	: UN 1866
IMDG	: UN 1866
ΙΑΤΑ	: UN 1866

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Aktivator-100



Revision Date: 21.02.2025 Date of last issue: 30.01.2025		Version	35.0	Print Date 21.02.2025
14.2 UN proper shipping name				
ADR IMDG IATA	: : :	RESIN SOLUTION RESIN SOLUTION Resin solution		
14.3 Transport hazard class(es)				
ADR	:	Class 3	Subsidiary risks	
IMDG IATA	•	3 3		
14.4 Packing group	•	5		
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	: : : : : : : : : : : : : : : : : : : :	II F1 33 3 (D/E)		
IMDG Packing group Labels EmS Code	:	II 3 F-E, <u>S-E</u>		
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	364 Y341 II Flammable Liquids		
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels				
14.5 Environmental hazards	-			
ADR Environmentally hazardous	:	yes		
IMDG Marine pollutant	:	yes		
IATA (Passenger) Environmentally hazardous	:	yes		
IATA (Cargo) Environmentally hazardous	:	yes		

Sika[®] Aktivator-100



Print Date 21.02.2025

Revision Date: 21.02.2025 Date of last issue: 30.01.2025 Version 35.0

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:	All substances contained in our Products ar	
	- registered by our upstream suppliers, and/or	
	 registered by us, and/or 	

- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 75
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
PIC Ordinance, ChemPICO (814.82)	:	Not applicable
Ordinance on Protection against Major Accidents Threshold quantity according to Major Accidents Ordi-	:	20.000 kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Aktivator-100



Revision Date: 21.02.2025 Version 35.0 Print Date 21.02.2025 Date of last issue: 30.01.2025 nance (MAO 814.012) Chemical Risk Reduction Ordinance Conditions of restriction for the following annexes • (ORRChem, SR 814.81) should be considered: Annex 1.11 Dangerous liquid substances Waters Protection Ordinance (WPO 814.201) Water pollution class : obviously hazardous to water Classification according to AwSV, Annex 1 (5.2) Volatile organic compounds Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 94,09% w/w Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 94,09% w/w

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

:	Highly flammable liquid and vapour.			
	Harmful if swallowed.			
:	May be fatal if swallowed and enters airways.			
÷	Causes severe skin burns and eye damage.			
÷	Causes skin irritation.			
÷	May cause an allergic skin reaction.			
:	Causes serious eye damage.			
:	Causes serious eye irritation.			
:	May cause respiratory irritation.			
:	May cause drowsiness or dizziness.			
:	Toxic to aquatic life with long lasting effects.			
Full text of other abbreviations				
:	Acute toxicity			
:	Long-term (chronic) aquatic hazard			

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] Aktivator-100

Revision Date: 21.02.2025 Date of last issue: 30.01.2025 Version 35.0

Print Date 21.02.2025

Eye Dam. Eye Irrit. Flam. Liq. Skin Corr. Skin Irrit. Skin Sens. STOT SE 2006/15/EC CH SUVA 2006/15/EC / TWA CH SUVA / TWA CH SUVA / STEL ADR		Serious eye damage Eye irritation Flammable liquids Skin corrosion Skin irritation Skin sensitisation Specific target organ toxicity - single exposure Europe. Indicative occupational exposure limit values Switzerland. Limit values at the work place Limit Value - eight hours Time Weighted Average Short Term Exposure Limit European Agreement concerning the International Carriage of Dangerous Coode by Road
CAS DNEL EC50 GHS IATA IMDG LD50 LC50		Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation pariad)
MARPOL OEL PBT PNEC REACH SVHC vPvB	:	period) International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 Occupational Exposure Limit Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative

Further information

Classification of the r	nixture:	Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method







Revision Date: 21.02.2025 Date of last issue: 30.01.2025 Version 35.0

Print Date 21.02.2025

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN