

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Sikalastic® M 687 Part A

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealing system, For professional users only.

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Schweiz AG  
Tüffenwies 16  
8048 Zürich  
Telephone : +41 58 436 40 40  
Telefax : -  
E-mail address of person : EHS@ch.sika.com  
responsible for the SDS

#### 1.4 Emergency telephone number

Tox Info Suisse  
CH-8028 Zurich  
+41(0)44 251 51 51 / Speed calling: 145

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling.  
P280 Wear eye protection/ face protection.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

### Additional Labelling

EUH208 Contains maleic anhydride. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Contains: methanol <= 0,2 %	2530-83-8 219-784-2 01-2119513212-58-XXXX	Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 1 - < 2,5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024

Version 1.0

Print Date 16.10.2024

Date of last issue: -

Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35-XXXX [corresponding group CAS 64742-95-6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	$\geq 1 - < 2,5$
ethylene glycol monobutyl ether	111-76-2 203-905-0 01-2119475108-36-XXXX	Acute Tox. 4; H302 Acute Tox. 3; H331 Skin Irrit. 2; H315 Eye Irrit. 2; H319  Acute toxicity estimate  Acute oral toxicity: 1.200 mg/kg Acute inhalation toxicity (vapour): 3 mg/l	$\geq 0,1 - < 0,5$
maleic anhydride	108-31-6 203-571-6 01-2119472428-31-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Inhalation, Respiratory system) EUH071  specific concentration limit Skin Sens. 1A; H317 $\geq 0,001 \%$	$< 0,001$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024

Version 1.0

Print Date 16.10.2024

Date of last issue: -

---

- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Excessive lachrymation  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

### 5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Standard procedure for chemical fires.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.  
No special environmental precautions required.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Further information on storage : No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024

Version 1.0

Print Date 16.10.2024

Date of last issue: -

age stability

### 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
ethylene glycol monobutyl ether	111-76-2	TWA	20 ppm 98 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m <sup>3</sup>	2000/39/EC
		TWA	10 ppm 49 mg/m <sup>3</sup>	CH SUVA
	Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Health and Safety Executive (Occupational Medicine and Hygiene Laboratory), Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	20 ppm 98 mg/m <sup>3</sup>	CH SUVA
maleic anhydride	108-31-6	TWA	0,1 ppm 0,4 mg/m <sup>3</sup>	CH SUVA
	Further information: The substance can be present simultaneously as vapor and aerosol, Sensitizers; Substances marked with an S can lead to very strong allergic reactions., National Institute for Occupational Safety and Health, Occupational Safety and Health Administration, Harm to the unborn child is not to be expected when the OEL-value is respected			
		STEL	0,1 ppm 0,4 mg/m <sup>3</sup>	CH SUVA

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
methanol	67-56-1	TWA	200 ppm 260 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative, Identifies the possibility of signifi-			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024

Version 1.0

Print Date 16.10.2024

Date of last issue: -

		cant uptake through the skin		
		TWA	200 ppm 260 mg/m3	CH SUVA
		Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected		
		STEL	400 ppm 520 mg/m3	CH SUVA
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
		Further information: Indicative, Identifies the possibility of significant uptake through the skin		
		TWA	200 ppm 260 mg/m3	CH SUVA
		Further information: Toxic by skin resorption possible; Substances, which are easily absorbed through the skin, can give by additional skin resorption a substantial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL-value is respected		
		STEL	400 ppm 520 mg/m3	CH SUVA

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
ethylene glycol monobutyl ether	111-76-2	2-butoxy acetic acid: 150 mg/g creatinine (Urine)	Immediately after exposure or after working hours, In case of long-term exposure: after more than one shift	CH BAT

### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards.  
Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm),

breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

### Environmental exposure controls

General advice : If the product contaminates rivers and lakes or drains inform respective authorities.  
No special environmental precautions required.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Appearance : viscous  
Colour : grey

Odour : aliphatic

Melting point/ range / Freezing point : No data available

Boiling point/boiling range : No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024

Version 1.0

Print Date 16.10.2024

Date of last issue: -

---

Flammability (solid, gas) : No data available

### Upper/lower flammability or explosive limits

Upper explosion limit / Up-  
per flammability limit : No data available

Lower explosion limit /  
Lower flammability limit : No data available

Flash point : > 110 °C  
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

### Viscosity

Viscosity, dynamic : ca. 4.700 mPa.s (20 °C)

Viscosity, kinematic : No data available

### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-  
octanol/water : No data available

Vapour pressure : 6,65 hPa

Density : ca. 1,6 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

### 9.2 Other information

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

#### 10.4 Conditions to avoid

Conditions to avoid : No data available

#### 10.5 Incompatible materials

Materials to avoid : No data available

#### 10.6 Hazardous decomposition products

: methanol

Hazardous decomposition products : methanol

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified due to lack of data.

##### Components:

##### [3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Acute oral toxicity : LD50 Oral (Rat): 7.010 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): 4.248 mg/kg

##### Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

---

### ethylene glycol monobutyl ether:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

LD50 Oral: 1.200 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Test atmosphere: vapour  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

### maleic anhydride:

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

### Skin corrosion/irritation

Not classified due to lack of data.

### Components:

#### Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

#### Respiratory sensitisation

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

#### Reproductive toxicity

Not classified due to lack of data.

#### STOT - single exposure

Not classified due to lack of data.

#### STOT - repeated exposure

Not classified due to lack of data.

#### Aspiration toxicity

Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

### 11.2 Information on other hazards

#### Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

**Components:**

**[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:**

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 55 mg/l  
Exposure time: 96 h

**Hydrocarbons, C9, aromatics:**

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 mg/l  
Exposure time: 72 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste code Switzerland : 08 01 11 [S] Paint and varnish waste containing organic sol-  
VeVA/LVA vents or other hazardous substances

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

### 14.4 Packing group

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA (Cargo)** : Not regulated as a dangerous good

**IATA (Passenger)** : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

Number on list 52: 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

Number on list 75:

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

Regulation (EC) on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

PIC Ordinance, ChemPICO (814.82) : Not applicable

Ordinance on Protection against Major Accidents  
Threshold quantity according to Major Accidents Ordinance (MAO 814.012) : Not applicable

Chemical Risk Reduction Ordinance (ORRChem, SR 814.81) : Conditions of restriction for the following annexes should be considered:  
Annex 1.11 Dangerous liquid substances

Waters Protection Ordinance (WPO 814.201)

Water pollution class : highly hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: <= 3% w/w  
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 60,84% w/w

### Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024  
Date of last issue: -

Version 1.0

Print Date 16.10.2024

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

## SECTION 16: Other information

### Full text of H-Statements

H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H331	:	Toxic if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	:	May cause respiratory irritation.
H336	:	May cause drowsiness or dizziness.
H372	:	Causes damage to organs through prolonged or repeated exposure.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Resp. Sens.	:	Respiratory sensitisation
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
CH BAT	:	Switzerland. List of BAT-values
CH SUVA	:	Switzerland. Limit values at the work place
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

## Sikalastic® M 687 Part A



Revision Date: 02.10.2024

Version 1.0

Print Date 16.10.2024

Date of last issue: -

	Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

### Further information

#### Classification of the mixture:

Eye Irrit. 2

H319

#### Classification procedure:

Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN