

Revision Date: 11.08.2023 Date of last issue: 13.04.2021 Version 12.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sika[®] Aktivator PRO

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Pretreatment agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air- ways.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Revision Date: 11.08.2023 Date of last issue: 13.04.2021



Version 12.0

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H225 H304 H315 H318 H336 H411	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:	
		P210 P273 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Wear protective gloves/ protective clothing/
			eye protection/ face protection/ hearing pro- tection.
		Response:	
		P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
		P305 + P351 + F	P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove con- tact lenses, if present and easy to do. Con- tinue rinsing. Immediately call a POISON CENTER/ doctor.
		P331 P370 + P378	Do NOT induce vomiting. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
		P391	Collect spillage.

Hazardous components which must be listed on the label:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics bis(trimethoxysilylpropyl)amine

Additional Labelling

EUH208 Contains 3-trimethoxysilylpropane-1-thiol. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sika[®] Aktivator PRO

Revision Date: 11.08.2023 Date of last issue: 13.04.2021



Version 12.0

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Hydrocarbons, C7, n-alkanes,	Not Assigned	Flam. Liq. 2; H225	>=80
isoalkanes, cyclics	927-510-4	Skin Irrit. 2; H315	
Contains:	265-151-9	STOT SE 3; H336	
cyclohexane >= 2 %	01-2119475515-33-	Asp. Tox. 1; H304	
	XXXX [corresponding	Aquatic Chronic 2;	
	group CAS 64742-49-	H411	
	[Ŏ]		
bis(trimethoxysilylpropyl)amine	82985-35-1	Eye Dam. 1; H318	>= 3 - < 5
Contains:	280-084-5		
methanol <= 0,3 %	01-2119969956-12-		
	XXXX		
3-trimethoxysilylpropane-1-thiol	4420-74-0	Acute Tox. 4; H302	>= 0,5 - < 1
Contains:	224-588-5	Skin Sens. 1B; H317	
methanol <= 0,99 %	01-2120763539-41-	Aquatic Chronic 2;	
	XXXX	H411	
		Acute toxicity esti-	
		mate	
		Acute oral toxicity:	
		1.701 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.

Sika[®] Aktivator PRO



Revision Date: 11.08.2023 Version 12.0 Date of last issue: 13.04.2021 In case of eye contact Small amounts splashed into eyes can cause irreversible tis-: sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. If swallowed Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Aspiration may cause pulmonary oedema and pneumonitis. Symptoms • Excessive lachrymation Erythema Dermatitis Loss of balance Vertigo See Section 11 for more detailed information on health effects and symptoms. Risks Risk of serious damage to the lungs (by aspiration). ÷ irritant effects May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water



Revision Date: 11.08.2023 Date of last issue: 13.04.2021		Version 12.0	Print Date 11.08.2023
		courses.	
Hazardous combustion prod- ucts	:	No hazardous combustion products are known	
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing	g apparatus.
Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water seg must not be discharged into drains. Fire residues and contaminated fire extinguishing be disposed of in accordance with local regulation	g water must

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Personal precautions Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. 6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Do not get in eyes, on skin, or on clothing. For personal protection see section 8.
	· · · ·
	Smoking, eating and drinking should be prohibited in the ap-
	plication area.

Sika® Aktivator PRO

Print Date 11.08.2023

Revision Date: 11.08.2023	
Date of last issue: 13.04.2021	

	Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, inc	cluding any incompatibilities
Requirements for storage : areas and containers	Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
Further information on stor- : age stability	No decomposition if stored and applied as directed.
7.3 Specific end use(s)	
Specific use(s) :	Consult most current local Product Data Sheet prior to any use.

Version 12.0

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

ponents CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
-----------------	----------------------------------	---------------------------	---------	--

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC	
	Further information: Indicative, Identifies the possibility of sigr				
	cant uptake thr	ough the skin			
		TWA	200 ppm	CH SUVA	
			260 mg/m3		
	Further information: Toxic by skin resorption possible; Substanc- es, which are easily absored through the skin, can give by addi- tional skin resoption a substancial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la prévention des accidents du travail et des maladies pro-				



Revision Date: 11.08.2023 Date of last issue: 13.04.2021 Version 12.0

fessionnelles, Ha when the OEL-va	arm to the unborn alue is respected	child is not to be e	expected
S	STEL	400 ppm 520 mg/m3	CH SUVA

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	No special measures required.
Environmental exposure co	ontro	ols
General advice		Prevent product from entering drains

General advice	: Prevent product from entering drains.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour		liquid colourless
Odour	:	hydrocarbon-like

Melting point/range / Freezing : No data available

Revision Date: 11.08.2023 Date of last issue: 13.04.2021 Version 12.0



point		
Boiling point/boiling range	:	> 70 °C
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	0,6 %(V)
Flash point	:	ca4 °C Method: closed cup
Auto-ignition temperature	:	200 °C
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	ca. 2 mPa.s (20 °C)
Viscosity, kinematic	:	< 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	60 hPa
Density	:	ca. 0,7 g/cm3 (20 °C)
Relative vapour density	:	No data available

Revision Date: 11.08.2023 Date of last issue: 13.04.2021



9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : S	Stable under recommended storage conditions.
-------------------------	--

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition : methanol products

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

bis(trimethoxysilylpropyl)amine:

Acute oral toxicity	:	LD50 Oral (Rat): 3.780 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 11.865 mg/kg

3-trimethoxysilylpropane-1-thiol:

Acute oral toxicity	:	LD50 Oral (Rat): 1.701 mg/kg
		Acute toxicity estimate: 1.701 mg/kg

Method: Calculation method

Sika[®] Aktivator PRO

Revision Date: 11.08.2023 Date of last issue: 13.04.2021 Version 12.0



Acute dermal toxicity : LD50 Dermal (Rat): 2.583 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

May be fatal if swallowed and enters airways.

2

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis(trimethoxysilylpropyl)amine:



Revision Date: 11.08.2023 Date of last issue: 13.04.2021		Version 12.0	Print Date 11.
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 13 Exposure time: 96 h	0 mg/l
		NOEC (Oncorhynchus mykiss (rainbow trout)): 10	00 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae) Exposure time: 72 h): > 100 mg/l
3-trimethoxysilylpropane-1-	thic	bl:	
Toxicity to fish	:	LC50 (Lepomis macrochirus (Bluegill sunfish)): 1 Exposure time: 96 h	2,3 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): 6,7 mg/l Exposure time: 48 h	
2.2 Persistence and degradabil No data available	ity		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB as	se	ssment	
Product:			
Assessment	:	This substance/mixture contains no components to be either persistent, bioaccumulative and toxic very persistent and very bioaccumulative (vPvB) 0.1% or higher	(PBT), or
2.6 Endocrine disrupting prope	rtie	s	
Product:			
Assessment	:	The substance/mixture does not contain componered to have endocrine disrupting properties according REACH Article 57(f) or Commission Delegated re(EU) 2017/2100 or Commission Regulation (EU) levels of 0.1% or higher.	ording to egulation
12.7 Other adverse effects			
Product:			
Additional ecological infor- mation	:	An environmental hazard cannot be excluded in t unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.	he event of
Country CH 000000125402			11 /
			11/

Revision Date: 11.08.2023 Date of last issue: 13.04.2021 Version 12.0



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product rest This material and its container must be disposed of in a way. Dispose of surplus and non-recyclable products via a li waste disposal contractor. Disposal of this product, solutions and any by-products at all times comply with the requirements of environmen protection and waste disposal legislation and any regio local authority requirements. Avoid dispersal of spilled material and runoff and containers. 	sidues. a safe censed should ntal nal
Waste code Switzerland VeVA/LVA	: 08 01 11 -	
Contaminated packaging	: 15 01 10 [S] packaging containing residues of or contained by dangerous substances	minat-

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1866	
IMDG	:	UN 1866	
ΙΑΤΑ	:	UN 1866	
14.2 UN proper shipping name			
ADR	:	RESIN SOLUTION	
IMDG	:	RESIN SOLUTION (n-heptane)	
ΙΑΤΑ	:	Resin solution	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	3	
IMDG	:	3	
ΙΑΤΑ	:	3	
14.4 Packing group			
ADR			

Revision Date: 11.08.2023 Date of last issue: 13.04.2021

Packing group

Print Date 11.08.2023

Classification Code Hazard Identification Number Labels Tunnel restriction code	:	 F1 33 3 (D/E)
IMDG Packing group Labels EmS Code	-	ll 3 F-E, <u>S-E</u>
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	364 Y341 II Flammable Liquids
IATA (Passenger)		

: 11

Packing instruction (passen-	:	353
ger aircraft)		
Packing instruction (LQ)	:	Y341
Packing group	:	11
Labels	:	Flammable Liquids

14.5 Environmental hazards

ADR Environmentally hazardous	:	yes
IMDG Marine pollutant	:	yes
IATA (Passenger) Environmentally hazardous	:	yes
IATA (Cargo) Environmentally hazardous	:	yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Version 12.0

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

CWC)	:	Not applicable	

REACH Information:	All substances contained in our Products are
	 registered by our upstream suppliers, and/or

Jika ®
Print Date 11.08.2023

Revision Date: 11.08.2023 Date of last issue: 13.04.2021 Version 12.0

	 registered by us, and/or excluded from the regulation, and/or exempted from the registration. 			
	REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)			Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
	REACH - Candidate List of Substa Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).
	REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable
	Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer			Not applicable
	Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu-	:	Not applicable
	PIC Ordinance, ChemPICO (814.	82)	:	Not applicable
	Chemical Risk Reduction Ordinance (ORRChem, SR 814.81)			See respective Annex to the Chemi- cal Risk Reduction Ordinance (ORRChem, 814.81) for Conditions of Restriction.
Seveso III: Directive 2012/18/EU of the European Parliam jor-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS				and of the Council on the control of ma-
	E2	ENVIRONMENTAL HA	ZA	RDS
	34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)		
	Volatile organic compounds :	(VOCV)		or volatile organic compounds Is (VOC) content: 95% w/w
		emissions (integrated p	ollu	4 November 2010 on industrial ution prevention and control) Is (VOC) content: 95% w/w

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met

Print Date 11.08.2023

Revision Date: 11.08.2023 Date of last issue: 13.04.2021 Version 12.0

and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H225 H302 H304 H315 H317 H318 H336 H411		 Highly flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Full text of other abbrev	iations	
Acute Tox.	:	Acute toxicity
Aquatic Chronic		Long-term (chronic) aquatic hazard
Asp. Tox.		Aspiration hazard
Eye Dam.		Serious eye damage
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
2006/15/EC	:	Europe. Indicative occupational exposure limit values
CH SUVA	:	Switzerland. Limit values at the work place
2006/15/EC / TWA	:	Limit Value - eight hours
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS		Chemical Abstracts Service
DNEL		Derived no-effect level
EC50		Half maximal effective concentration
GHS		Globally Harmonized System
IATA		International Air Transport Association
IMDG		International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
a - :		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
ountry CH_00000125402		15 / 1

Revision Date: 11.08.2023 Date of last issue: 13.04.2021



e of last issue: 13.04.2021	
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Version 12.0

Further information

Classification of the n	nixture:	Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN