

Revision Date: 28.11.2024 Date of last issue: 22.03.2022 Version 9.0

Print Date 28.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sika[®] RoboTec-61 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting ef- fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Version 9.0 Print Date 28.11.2024 Date of last issue: 22.03.2022 Hazard statements H314 Causes severe skin burns and eve damage. May cause an allergic skin reaction. H317 H412 Harmful to aquatic life with long lasting effects. **Prevention:** Precautionary statements P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eve protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

benzyl alcohol Phenol, styrenated 3-aminomethyl-3,5,5-trimethylcyclohexylamine Amines, polyethylenepoly-, triethylenetetramine fraction Adduct IA (epoxy amine adduct) polyaminoamide adduct

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Date of last issue: 22.03.2022 Version 9.0

Print Date 28.11.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1B; H317	>= 5 - < 10
		Acute toxicity esti- mate	
		Acute oral toxicity: 1.200 mg/kg	
(1-methylethyl)-1,1'-biphenyl Contains: diisopropyl-1,1'-biphenyl >= 9,9 %	25640-78-2 247-156-8 01-2119982993-17- XXXX	Eye Irrit. 2; H319 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 2,5 - < 5
Phenol, styrenated	Not Assigned 701-443-9 01-2119980970-27- XXXX, 01- 2119979575-18- XXXX	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 2,5 - < 5
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 2,5 - < 3
		specific concentration limit Skin Sens. 1A; H317 >= 0,001 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 1.030 mg/kg	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Date of last issue: 22.03.2022 Version 9.0

Amines, polyethylenepoly-, tri- ethylenetetramine fraction Contains: 2-(2-aminoethylamino)ethanol <= 0,3 %	90640-67-8 292-588-2 01-2119487919-13- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071 Acute toxicity esti- mate Acute oral toxicity: 1.716 mg/kg Acute dermal toxicity: 1.465 mg/kg	>= 2,5 - < 3
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity: 1.999 mg/kg	>= 1 - < 2,5
Adduct IA (epoxy amine adduct)	68609-08-5 614-657-1 01-2120106013-80- XXXX	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 1 - < 2,5
polyaminoamide adduct	157707-73-8 500-382-3	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,5 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Version 9.0 Print Date 28.11.2024 Date of last issue: 22.03.2022 ty. In case of eye contact Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. If swallowed Do not induce vomiting without medical advice. 2 Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Symptoms Allergic reactions : Dermatitis See Section 11 for more detailed information on health effects and symptoms. Risks May cause an allergic skin reaction. Causes serious eye damage. Causes severe burns. Health injuries may be delayed. corrosive effects sensitising effects 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treat symptomatically. **SECTION 5: Firefighting measures** 5.1 Extinguishing media Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction. 5.2 Special hazards arising from the substance or mixture Hazardous combustion prod- : No hazardous combustion products are known ucts 5.3 Advice for firefighters Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B

_



Revision Date: 28.11.2024 Date of last issue: 22.03.2022	Version 9.0	Print Date 28.11.2024
Further information :	Standard procedure for chemical fires.	
SECTION 6: Accidental release	measures	
6.1 Personal precautions, protectiv	ve equipment and emergency procedures	
Personal precautions :	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions		
Environmental precautions :	Do not flush into surface water or sanitary s If the product contaminates rivers and lakes respective authorities.	
6.3 Methods and material for conta	inment and cleaning up	
Methods for cleaning up :	Soak up with inert absorbent material (e.g. acid binder, universal binder, sawdust). Keep in suitable, closed containers for dispo	

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024	Version 9.0	Print Date 28.11.2024
Date of last issue: 22.03.2022		

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s) Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
benzyl alcohol	100-51-6	TWA	5 ppm 22 mg/m3	CH SUVA
	as vapor and stances, whi additional sk only inhalation Safety and H	22 mg/m3Further information: The substance can be present simultaneously as vapor and aerosol, Toxic by skin resorption possible; Sub- stances, which are easily absored through the skin, can give by additional skin resoption a substancial higher risk compared to only inhalation by the airways., National Institute for Occupational Safety and Health, Harm to the unborn child is not to be expected when the OEL-value is respected		

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.



evision Date: 28.11.2024 ate of last issue: 22.03.2022	Version 9.0	Print Date 28.11.2024
Skin and body protection	: Protective clothing (e.g. Safety sho long-sleeved working clothing, long and protective boots are additional and stirring work.	g trousers). Rubber aprons
Respiratory protection	 In case of inadequate ventilation we Respirator selection must be based exposure levels, the hazards of the ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A Ensure adequate ventilation. This of exhaust extraction or by general ve ods for determining inhalation export ticular to the mixing / stirring area. It to keep the concentrations under the limits then respiration protection meters. 	d on known or anticipated e product and the safe work- A3: < 10000 ppm can be achieved by local entilation. (EN 689 - Meth- osure). This applies in par- In case this is not sufficent he occupational exposure
Environmental exposure co	trols	
General advice	: Do not flush into surface water or s If the product contaminates rivers a	

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

intormation on basic physical	an	u chemical propert
Physical state	:	liquid
Appearance	:	paste
Colour	:	green
Odour	:	amine-like
Melting point/ range / Freez- ing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or o	exp	losive limits
Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit /	:	No data available

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Date of last issue: 22.03.2022	Version 9.0	Print Date 28.11.2024
Lower flammability limit		
Flash point	: > 101 °C Method: closed cup	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
рН	: ca. 10,8 Concentration: 50 %	
Viscosity Viscosity, kinematic	: > 20,5 mm2/s (40 °C)	
Solubility(ies) Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	
Vapour pressure	: 0,07 hPa	
Density	: ca. 2,28 g/cm3 (20 °C)	
Relative vapour density	: No data available	
Particle characteristics	: No data available	
9.2 Other information		

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Date of last issue: 22.03.2022	Version 9.0	Print Date 28.11.2024
10.4 Conditions to sucid		
10.4 Conditions to avoid Conditions to avoid	: No data available	
10.5 Incompatible materials		
Materials to avoid	: No data available	
10.6 Hazardous decomposition	roducts	
	: No hazardous decomposition pro	oducts are known.
SECTION 11: Toxicological ir	ormation	
11.1 Information on hazard class	es as defined in Regulation (EC) No	1272/2008
Acute toxicity Not classified due to lack of d	ta.	
Components:		
benzyl alcohol:		
Acute oral toxicity	: Acute toxicity estimate: 1.200 mg/ Method: Acute toxicity estimate ac No. 1272/2008	
	LD50 Oral (Rat): 1.200 mg/kg	
(1-methylethyl)-1,1'-bipheny	:	
Acute oral toxicity	: LD50 Oral (Rat): 4.650 mg/kg Method: OECD Test Guideline 40	1
Phenol, styrenated:		
Acute oral toxicity	: LD50 Oral (Rat): 2.500 mg/kg	
Acute dermal toxicity	: LD50 Dermal (Rat): > 5.000 mg/kg	g
3-aminomethyl-3,5,5-trimeth	/lcyclohexylamine:	
Acute oral toxicity	: Acute toxicity estimate: 1.030 mg/ Method: Acute toxicity estimate ac No. 1272/2008	
	LD50 Oral (Rat): 1.030 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): > 5 mg/l Exposure time: 4 h	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



ision Date: 28.11.2024 e of last issue: 22.03.2022	Version 9.0	Print Date 28.11.202
	Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.000 mg/kg	
	LD50 (Rabbit): > 2.000 - 5.000 mg/kg	
Amines, polyethylenepoly-	triethylenetetramine fraction:	
Acute oral toxicity	: LD50 Oral (Rat): 1.716 mg/kg	
	Acute toxicity estimate: 1.716 mg/kg Method: Calculation method	
Acute inhalation toxicity	: Assessment: Corrosive to the respiratory trac	t.
Acute dermal toxicity	: LD50 Dermal (Rabbit): 1.465 mg/kg	
	Acute toxicity estimate: 1.465 mg/kg Method: Calculation method	
2,4,6-tris(dimethylaminome	thyl)phenol:	
Acute oral toxicity	: LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised REGULATION (EC) No 1272/2008	
Adduct IA (choxy omino od		
Adduct IA (epoxy amine ad Acute oral toxicity	: LD50 Oral (Rat, female): 300 - 2.000 mg/kg	
	Method: OECD Test Guideline 423	
Skin corrosion/irritation		
Causes severe burns.		
Components:		
2,4,6-tris(dimethylaminome	thyl)phenol:	
Species	: Rabbit	
Assessment	: Corrosive : OECD Test Guideline 404	
Method	. OECD Test Guideline 404	
Assessment	: irritating	
Remarks	: Annex VI - Harmonised REGULATION (EC) No 1272/2008	
Serious eye damage/eye in	itation	
Causes serious eye damage		
Causes senous eye damage		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Date of last issue: 22.03.2022	Version 9.0	Print Date 28.11.2024
Species : Assessment :	Rabbit Causes serious eye damage.	
Assessment : Remarks :	irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008	
Respiratory or skin sensitisation	on	
Skin sensitisation May cause an allergic skin reaction	on.	
Respiratory sensitisation Not classified due to lack of data.		
Germ cell mutagenicity Not classified due to lack of data.		
Carcinogenicity Not classified due to lack of data.		
Reproductive toxicity Not classified due to lack of data.		
STOT - single exposure Not classified due to lack of data.		
STOT - repeated exposure Not classified due to lack of data.		
Aspiration toxicity Not classified due to lack of data.		
11.2 Information on other hazards		
Endocrine disrupting propertie	S	
Product:		
Assessment :	The substance/mixture does not contain comered to have endocrine disrupting properties REACH Article 57(f) or Commission Delegate (EU) 2017/2100 or Commission Regulation (Intersection of 0.1% or higher.	according to ed regulation

SECTION 12: Ecological information

12.1 Toxicity

Components:

benzyl alcohol: Toxicity to fish

: LC50 (Fish): > 100 mg/l

Country CH 10000008345

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Date of last issue: 22.03.2022	Version 9.0	Print Date 28.11.2024
	Exposure time: 96 h	
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 100 r Exposure time: 48 h	ng/l
(1-methylethyl)-1,1'-biphenyl:		
Toxicity to daphnia and other : aquatic invertebrates	LC50 (Daphnia magna (Water flea)): 0,167 n Exposure time: 48 h	ng/l
3-aminomethyl-3,5,5-trimethyle	cyclohexylamine:	
Toxicity to algae/aquatic : plants	ErC50 (Desmodesmus subspicatus (green a mg/l Exposure time: 72 h	lgae)): > 10 - 100
	NOEC (Desmodesmus subspicatus (green a Exposure time: 72 h	lgae)): 1,5 mg/l
Adduct IA (epoxy amine adduc	ct):	
Toxicity to algae/aquatic : plants	EC50 (Pseudokirchneriella subcapitata (alga Exposure time: 72 h	e)): 3,13 mg/l
Toxicity to fish (Chronic tox- : icity)	LC50: 1,62 mg/l Exposure time: 96 h Species: Danio rerio (zebra fish)	
Toxicity to daphnia and other : aquatic invertebrates (Chron- ic toxicity)	EC50: 1,75 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)	
12.2 Persistence and degradability		
No data available 12.3 Bioaccumulative potential		
No data available		
12.4 Mobility in soil		
No data available		
12.5 Results of PBT and vPvB asse	essment	
Product: Assessment :	This substance/mixture contains no company	ante considered
	This substance/mixture contains no component to be either persistent, bioaccumulative and t very persistent and very bioaccumulative (vP 0.1% or higher	oxic (PBT), or

12.6 Endocrine disrupting properties

Product:

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Date of last issue: 22.03.2022	Version 9.0	Print Date 28.11.2024
Assessment	 The substance/mixture does not contained to have endocrine disrupting pro REACH Article 57(f) or Commission E (EU) 2017/2100 or Commission Regulated to the second s	perties according to Delegated regulation
12.7 Other adverse effects		
Product: Additional ecological infor- mation	: An environmental hazard cannot be e unprofessional handling or disposal. Harmful to aquatic life with long lastin	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Waste code Switzerland VeVA/LVA	: 08 04 09 [S] waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

Country CH 10000008345			14
IMDG	:	CORROSIVE SOLID, N.O.S.	
ADR	:	CORROSIVE SOLID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, 2,4,6- tris(dimethylaminomethyl)phenol)	
14.2 UN proper shipping name			
ΙΑΤΑ	:	UN 1759	
IMDG	:	UN 1759	
ADR	:	UN 1759	
14.1 UN number or ID number			

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



evision Date: 28.11.2024 Pate of last issue: 22.03.2022		Version 9.0	Print Date 28.11.202
		(3-aminomethyl-3,5,5-trimethylcycl tris(dimethylaminomethyl)phenol)	ohexylamine, 2,4,6-
ΙΑΤΑ	:	Corrosive solid, n.o.s. (3-aminomethyl-3,5,5-trimethylcycle tris(dimethylaminomethyl)phenol)	ohexylamine, 2,4,6-
14.3 Transport hazard class(es)			
		Class Subsidiary r	sks
ADR	:	8	
IMDG	:	8	
ΙΑΤΑ	:	8	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III C10 80 8 (E)	
IMDG Packing group Labels EmS Code	:	III 8 F-A, S-B	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	864 Y845 III Corrosive	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	860 Y845 III Corrosive	
14.5 Environmental hazards			
ADR Environmentally hazardous	:	no	
IMDG Marine pollutant	:	no	
IATA (Passenger) Environmentally hazardous	:	no	
IATA (Cargo) Environmentally hazardous	:	no	



Revision Date: 28.11.2024 Date of last issue: 22.03.2022 Version 9.0

Print Date 28.11.2024

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:	All substances contained in our Products are
	 registered by our upstream suppliers, and/or
	 registered by us, and/or

- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Number on list 75:
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
PIC Ordinance, ChemPICO (814.82)	:	Not applicable
Ordinance on Protection against Major Accidents Threshold quantity according to Major Accidents Ordi-	:	20.000 kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Version 9.0 Print Date 28.11.2024 Date of last issue: 22.03.2022 nance (MAO 814.012) Chemical Risk Reduction Ordinance Conditions of restriction for the following annexes • (ORRChem, SR 814.81) should be considered: Annex 1.11 Dangerous liquid substances Waters Protection Ordinance (WPO 814.201) Water pollution class : obviously hazardous to water Classification according to AwSV, Annex 1 (5.2) Volatile organic compounds Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 5,86% w/w Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 5,86% w/w

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

The product belongs to group 2 according to the Swiss Chemicals Ordinance (ChemO 813.11).

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302 :	Harmful if swallowed.
H304 :	May be fatal if swallowed and enters airways.
H312 :	Harmful in contact with skin.
H314 :	Causes severe skin burns and eye damage.
H315 :	Causes skin irritation.
H317 :	May cause an allergic skin reaction.
H318 :	Causes serious eye damage.
H319 :	Causes serious eye irritation.
H332 :	Harmful if inhaled.
H400 :	Very toxic to aquatic life.
H411 :	Toxic to aquatic life with long lasting effects.
H412 :	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®] RoboTec-61 Part B



Revision Date: 28.11.2024 Date of last issue: 22.03.2022 Version 9.0

Print Date 28.11.2024

Acute Tox.	: Acute toxicity	
Aquatic Acute	: Short-term (acute) aquatic hazard	
Aquatic Chronic	: Long-term (chronic) aquatic hazard	
Asp. Tox.	: Aspiration hazard	
Eye Dam.	: Serious eye damage	
Eye Irrit.	: Eye irritation	
Skin Corr.	: Skin corrosion	
Skin Irrit.	Skin irritation	
Skin Sens.	: Skin sensitisation	
CH SUVA	: Switzerland. Limit values at the work place	
CH SUVA / TWA	Time Weighted Average	
ADR	: European Agreement concerning the International Carriage of	
	Dangerous Goods by Road	
CAS	: Chemical Abstracts Service	
DNEL	: Derived no-effect level	
EC50	: Half maximal effective concentration	
GHS	: Globally Harmonized System	
ΙΑΤΑ	: International Air Transport Association	
IMDG	: International Maritime Code for Dangerous Goods	
LD50	: Median lethal dosis (the amount of a material, given all at	
	once, which causes the death of 50% (one half) of a group of	
	test animals)	
LC50	: Median lethal concentration (concentrations of the chemical in	
	air that kills 50% of the test animals during the observation	
	period)	
MARPOL	: International Convention for the Prevention of Pollution from	
	Ships, 1973 as modified by the Protocol of 1978	
OEL	: Occupational Exposure Limit	
PBT	: Persistent, bioaccumulative and toxic	
PNEC	: Predicted no effect concentration	
REACH	: Regulation (EC) No 1907/2006 of the European Parliament	
	and of the Council of 18 December 2006 concerning the Reg-	
	istration, Evaluation, Authorisation and Restriction of Chemi-	
	cals (REACH), establishing a European Chemicals Agency	
SVHC	: Substances of Very High Concern	
vPvB	: Very persistent and very bioaccumulative	
Eurther information		

Further information

Classification of the mixture:		Classification procedure:
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sika® RoboTec-61 Part B

Revision Date: 28.11.2024 Date of last issue: 22.03.2022

Version 9.0

Changes as compared to previous version !

CH / EN



