Version 15.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikaflex[®] PRO-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person responsible for the SDS	:	EHS@ch.sika.com

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

```
Classification (REGULATION (EC) No 1272/2008)
```

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)					
Hazard pictograms	:				
Signal word	:	Warning			
Hazard statements	:	H317	May cause an allergic skin reaction.		
Precautionary statements	:	P101	If medical advice is needed, have product container or label at hand.		
		P102	Keep out of reach of children.		
11		Prevention:			

Sikaflex[®] PRO-3

Print Date 07.08.2023

not

Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Version 15.0

P261 P280	Avoid breathing mist or vapours. Wear protective gloves.
Response: P302 + P352	IF ON SKIN: Wash with plenty of water.
Disposal:	
P501	Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane Pentamethyl piperidylsebacate

Hardener LI (Isophoronedialdimine) 4,4'-methylenediphenyl diisocyanate 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate m-tolylidene diisocyanate

Additional Labelling

EUH204	Contains isocyanates. May produce an allergic reaction.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do
	breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 07.08.2023 Date of last issue: 14.07.2021



Version 15.0

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Urea,N,N''-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
Reaction product of Hexameth- ylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	192526-20-8 924-669-1 01-2120768758-32- XXXX	Skin Sens. 1A; H317 Aquatic Chronic 4; H413	>= 0,1 - < 0,25
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25
Hardener LI (Isophoronedial- dimine)	932742-30-8 700-071-4 01-2119880654-28- XXXX	Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 0,1 - < 0,25

Revision Date: 07.08.2023 Date of last issue: 14.07.2021



Version 15.0

4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l	< 0,1
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 \longrightarrow specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 0,031 mg/l	>= 0,025 - < 0,1

Sikaflex[®] PRO-3

Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Version 15.0



m-tolylidene diisocyanate	26471-62-5 247-722-4 01-2119454791-34- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H314 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 3; H412 specific concentration limit Resp. Sens. 1; H334	>= 0,025 - < 0,1
		Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (vapour): 0,107 mg/l	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: A	Allergic reactions	
Country CH 00000607576			5 / 19



Revision Date: 07.08.2023 Date of last issue: 14.07.2021		Version 15.0	Print Date 07.08.2
		See Section 11 for more detailed informa and symptoms.	tion on health effects
Risks	:	sensitising effects	
		May cause an allergic skin reaction.	
4.3 Indication of any immediate	me	dical attention and special treatment net	eded
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting meas	sur	es	_
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/wat ide/sand/foam/alcohol resistant foam/che extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are k	nown
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained b	reathing apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental releas	se i	neasures	
6.1 Personal precautions, protec	tiv	e equipment and emergency procedures	S
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions	:	Do not flush into surface water or sanitary	y sewer system.
6.3 Methods and material for cor	ntai	nment and cleaning up	
Methods for cleaning up	:	Soak up with inert absorbent material (e. acid binder, universal binder, sawdust). Keep in suitable, closed containers for dis	

6.4 Reference to other sections

For personal protection see section 8.

Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Version 15.0



SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 mg/m3 (NCO)	CH SUVA	
	Further information: Toxic by skin resorption possible; Substanc- es, which are easily absored through the skin, can give by addi- tional skin resoption a substancial higher risk compared to only inhalation by the airways., Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Health and Safety				

Sikaflex[®] PRO-3



Version 15.0

Revision Date: 07.08.2023
Date of last issue: 14.07.2021

		ccupational Medicine child is not to be ex		
		STEL	0,02 mg/m3 (NCO)	CH SUVA
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,02 mg/m3 (NCO)	CH SUVA
	can lead to ve	nation: Sensitizers; S ery strong allergic re upational Medicine a	actions., Health a	nd Safety Ex-
		STEL	0,02 mg/m3 (NCO)	CHSUVA
m-tolylidene diisocyanate	26471-62-5	STEL	0,02 mg/m3	CH SUVA
		TWA	0,02 mg/m3	CH SUVA
		TWA	0,02 mg/m3 (NCO)	CH SUVA
	Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Health and Safety Executive (Occupational Medicine and Hygiene Laboratory)			nd Safety Ex-
		STEL	0,02 mg/m3 (NCO)	CH SUVA

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	4,4'- diaminodiphenyl- methane: 10 μg/g creatinine (Urine)	Immediately after exposure or after working hours	CH BAT
		4,4'- diaminodiphenyl- methane: 5 nmol/mmol creati- nine (Urine)	Immediately after exposure or after working hours	CH BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

			• •	
Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product of Hexamethylene diisocy- anate, oligomers with Mercaptopropyltri- methoxysilane	Workers	Inhalation	Long-term systemic effects	1,7 mg/m3
	Workers	Dermal	Long-term systemic effects	4,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	1,7 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction product of Hexamethylene	Fresh water	0,1 mg/l
diisocyanate, oligomers with Mercap-		



Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Version 15.0

topropyltrimethoxysilane		
	Intermittent use/release	1 mg/l
	Marine water	0,01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	23,28 mg/kg
	Marine sediment	2,33 mg/kg
	Sewage treatment plant	100 mg/l
	Soil	4,58 mg/kg

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

Print Date 07.08.2023

Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Version 15.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance		liquid paste
Colour	:	various
Odour	:	odourless
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	exp	losive limits
Upper explosion limit / Upper flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 150 °C Method: closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	Not applicable
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-	:	No data available

Print Date 07.08.2023

Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Version 15.0

octanol/water

Vapour pressure	:	0,01 hPa
Density	:	ca. 1,36 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg



ion Date: 07.08.2023 of last issue: 14.07.2021	Version 15.0	Print Date 07.08.
	Method: OECD Test Guideline 401	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.000 mg/kg Method: OECD Test Guideline 402	
Reaction product of Hexa ysilane:	methylene diisocyanate, oligomers with Merc	aptopropyltrimethox-
Acute oral toxicity	: LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 423	
Acute dermal toxicity	: LD50 Dermal (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402	
Pentamethyl piperidylseb	acate:	
Acute oral toxicity	: LD50 Oral (Rat): 3.230 mg/kg	
Hardener LI (Isophoroned	dialdimine):	
Acute oral toxicity	: LD50 Oral (Rat): > 2.000 mg/kg	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2.000 mg/kg	
4,4'-methylenediphenyl di	isocyanate:	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401	
Acute inhalation toxicity	: LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement	
	Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method	
3-isocyanatomethyl-3,5,5-	trimethylcyclohexyl isocyanate:	
Acute oral toxicity	: LD50 Oral (Rat): 4.814 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
	Acute toxicity estimate: 0,031 mg/l Test atmosphere: dust/mist Method: Calculation method	
Acute dermal toxicity	: LD50 Dermal (Rat): > 7.000 mg/kg	
m-tolylidene diisocyanate	:	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Silcaflox® PBO 2

Sikaflex[®] PRO-3

Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Version 15.0



Exposure time: 4 h Test atmosphere: vapour

Acute toxicity estimate: 0,107 mg/l Test atmosphere: vapour Method: Calculation method

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity Not classified due to lack of data.

Reproductive toxicity Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Print Date 07.08.2023

Version 15.0

SECTION 12: Ecological information

12.1 Toxicity

Components:

Urea,N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethox-
ysilane:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Pentamethyl piperidylsebacate:

	r entametry piperuyisebacate.						
	Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h				
	M-Factor (Acute aquatic tox- icity)	:	1				
	M-Factor (Chronic aquatic toxicity)	:	1				
Hardener LI (Isophoronedialdimine):							
	Toxicity to fish	:	LC50 (Fish): 87,2 mg/l Exposure time: 96 h				
	Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h				

Exposure time: 72 h

EC50 (Desmodesmus subspicatus (green algae)): 180,4 mg/l

:

plants

Toxicity to algae/aquatic

Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Version 15.0



12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor- : There is no data mation	a available for this product.
--	-------------------------------

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues.
This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Sikaflex[®] PRO-3



Revision Date: 07.08.2023 Date of last issue: 14.07.2021		Version 15.0	Print Date 07.08.202
Waste code Switzerland VeVA/LVA	:	08 04 09 [S] waste adhesives and seala solvents or other dangerous substances	
Contaminated packaging	:	15 01 10 [S] packaging containing residued by dangerous substances	ues of or contaminat-

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.2 UN proper shipping name					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.3 Transport hazard class(es)					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
ΙΑΤΑ	:	Not regulated as a dangerous good			
14.4 Packing group					
ADR	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
IATA (Cargo)	:	Not regulated as a dangerous good			
IATA (Passenger)	:	Not regulated as a dangerous good			
14.5 Environmental hazards					

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

Sikaflex[®] PRO-3

Jika ®
Print Date 07.08.2023

Revision Date: 07.08.2023 Date of last issue: 14.07.2021 Version 15.0

REACH Information:	All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.			
REACH - Restrictions on the ma the market and use of certain da mixtures and articles (Annex XV	ngerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3	
			4,4'-methylenediphenyl diisocyanate (Number on list 74, 56) 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate (Number on list 74) m-tolylidene diisocyanate (Number on list 74) 1,2-Benzenedicarboxylic acid, di-C9- 11-branched alkyl esters, C10-rich (Number on list 52)	
REACH - Candidate List of Subs Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).	
REACH - List of substances subject to authorisation (Annex XIV)			Not applicable	
Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer			Not applicable	
Regulation (EU) 2019/1021 on p tants (recast)	ersistent organic pollu-	:	Not applicable	
PIC Ordinance, ChemPICO (814	l.82)	:	Not applicable	
Chemical Risk Reduction Ordinance (ORRChem, SR 814.81)			See respective Annex to the Chemi- cal Risk Reduction Ordinance (ORRChem, 814.81) for Conditions	
Chemical Risk Reduction Ordinance (ORRChem, SR 814.81)			of Restriction. 4,4'-methylenediphenyl diisocyanate	
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable				
Volatile organic compounds :	Law on the incentive ta (VOCV) no VOC duties	ax fo	or volatile organic compounds	

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Silvaflax® PBO 2

Sikaflex[®] PRO-3

Revision Date: 07.08.2023 Date of last issue: 14.07.2021



Version 15.0

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315	:	Causes skin irritation.				
H317	:	May cause an allergic skin reaction.				
H319	:	Causes serious eye irritation.				
H330	:	Fatal if inhaled.				
H332	:	Harmful if inhaled.				
H334	:	May cause allergy or asthma symptoms or breathing difficul-				
		ties if inhaled.				
H335	:	May cause respiratory irritation.				
H351	:	Suspected of causing cancer.				
H361f	:	Suspected of damaging fertility.				
H373	:	May cause damage to organs through prolonged or repeated				
		exposure if inhaled.				
H400	:	Very toxic to aquatic life.				
H410	:	Very toxic to aquatic life with long lasting effects.				
H411	:	Toxic to aquatic life with long lasting effects.				
H412	:	Harmful to aquatic life with long lasting effects.				
H413	:	May cause long lasting harmful effects to aquatic life.				
Full text of other abbreviations						
Acute Tox.	:	Acute toxicity				
Aquatic Acute	:	Short-term (acute) aquatic hazard				
Aquatic Chronic	:	Long-term (chronic) aquatic hazard				
Carc.	:	Carcinogenicity				
Eye Irrit.	:	Eye irritation				
Repr.	:	Reproductive toxicity				
Resp. Sens.	:	Respiratory sensitisation				
Skin Irrit.	:	Skin irritation				
Skin Sens.	:	Skin sensitisation				
STOT RE	:	Specific target organ toxicity - repeated exposure				
STOT SE	:	Specific target organ toxicity - single exposure				

Sikaflex[®] PRO-3

Revision Date: 07.08.2023 Date of last issue: 14.07.2021



Version 15.0

CH BAT	: Switzerland. List of BAT-values
CH SUVA	: Switzerland. Limit values at the work place
CH SUVA / TWA	: Time Weighted Average
CH SUVA / STEL	: Short Term Exposure Limit
ADR	: European Agreement concerning the International Carriage of
	Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at
EDS0	once, which causes the death of 50% (one half) of a group of
	test animals)
LC50	: Median lethal concentration (concentrations of the chemical in
LC30	
	air that kills 50% of the test animals during the observation
	period)
MARPOL	: International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixtur	Classification procedure:	
Skin Sens. 1	H317	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN