

Version 1.0

Print Date 07.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikaflex[®] CR 170 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Sealant/adhesive, Product is not intended for consumer use, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person responsible for the SDS	:	EHS@ch.sika.com

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 12	72/2008)
Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure if inhaled.
Long-term (chronic) aquatic hazard, Cat- egory 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

tion (EU) 2020/878 Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: -			Version 1.0	Print Date 07.10.2024
Hazard pictograms	:			
Signal word	:	Warning		
Hazard statements	:	H302 + H33 H315 H319 H373 H411	 Harmful if swallowed or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause damage to organs throug or repeated exposure if inhaled. Toxic to aquatic life with long lasting 	h prolonged
Precautionary statements	:	Prevention: P260 P264 P273 P280	Do not breathe mist or vapours. Wash skin thoroughly after hand Avoid release to the environmer Wear protective gloves/ eye pro protection.	dling. nt.
		Response: P304 + P340 P391	0 + P312 IF INHALED: Remove per air and keep comfortable for bre POISON CENTER/ doctor if you Collect spillage.	eathing. Call a

Hazardous components which must be listed on the label:

manganese dioxide

Additional Labelling

EUH208 Contains thiram (ISO). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Sikaflex[®] CR 170 Part B

Revision Date: 23.09.2024	
Date of last issue: -	

Components

3.2 Mixtures

Version 1.0

Print Date 07.10.2024

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)	
manganese dioxide	1313-13-9 215-202-6	Acute Tox. 4; H302 Acute Tox. 4; H332 STOT RE 2; H373	>= 40 - < 60	
oxydipropyl dibenzoate	27138-31-4 248-258-5 01-2119529241-49- XXXX	Aquatic Chronic 3; H412	>= 40 - < 60	
sodium hydroxide	1310-73-2 215-185-5 01-2119457892-27- XXXX	Skin Corr. 1A; H314 Met. Corr. 1; H290 Eye Dam. 1; H318 specific concentration limit Skin Corr. 1A; H314 >= 5 % specific concentration limit Skin Corr. 1B; H314 2 - < 5 % specific concentration limit Skin Irrit. 2; H315 0,5 - < 2 % specific concentration limit Eye Irrit. 2; H319 0,5 - < 2 %	>= 1 - < 2	
1,3-diphenylguanidine	102-06-7 203-002-1	Repr. 2; H361f Acute Tox. 4; H302 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Aquatic Chronic 2; H411	>= 0,5 - < 1	





Sikaflex[®] CR 170 Part B

evision Date: 23.09.2024 ate of last issue: -	Version 1.0		Print Date 07.10.2024	
thiram (ISO)	137-26-8 205-286-2	Acute Tox. 4; H332 Acute Tox. 4; H302 STOT RE 2; H373 Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	>= 0,5 - < 1	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptom	s and effects, both acute and delayed
Symptoms	: Gastrointestinal discomfort Respiratory disorder Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed information on health effects

Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: -		Version 1.0	Print Date 07.10.2024
		and symptoms.	
Risks	:	irritant effects	
		Harmful if swallowed or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause damage to organs through pro exposure if inhaled.	blonged or repeated
4.3 Indication of any immediate n Treatment	neo :	dical attention and special treatment nee Treat symptomatically.	eded
SECTION 5: Firefighting meas	ur	es	
5.1 Extinguishing media			
Suitable extinguishing media	:	In case of fire, use water/water spray/water ide/sand/foam/alcohol resistant foam/chere extinction.	
5.2 Special hazards arising from	the	e substance or mixture	
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to er courses.	nter drains or water
Hazardous combustion prod- ucts	:	No hazardous combustion products are k	nown
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained br	reathing apparatus.
Further information	:	Collect contaminated fire extinguishing war must not be discharged into drains. Fire residues and contaminated fire exting be disposed of in accordance with local re	guishing water must

6.1 Personal precautions, protec	tive equipment and emergency procedures
Personal precautions	: Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions	
Environmental precautions	 Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.



Version 1.0

Print Date 07.10.2024

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products Advice on protection against : Normal measures for preventive fire protection. fire and explosion Handle in accordance with good industrial hygiene and safety Hygiene measures practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage Keep container tightly closed in a dry and well-ventilated : place. Store in accordance with local regulations. areas and containers Further information on stor-: No decomposition if stored and applied as directed. age stability 7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: - Version 1.0

Print Date 07.10.2024

Components	CAS-No.	Value type (Form	Control parame-	Basis *		
		of exposure)	ters *			
manganese dioxide	1313-13-9	TWA (inhalable dust)	0,2 mg/m3 (Manganese)	CH SUVA		
	Further infor	mation: National Insti		nal Safety and		
		n to the unborn child i				
	OEL-value is					
		TWA (inhalable	0,2 mg/m3	2017/164/EU		
		fraction)	(Manganese)			
	Further infor	mation: Indicative	••••••	•		
		TWA (Respirable	0,05 mg/m3	2017/164/EU		
		fraction)	(Manganese)			
		TWA (alveolate dust)	0,1 mg/m3 (Manganese)	CH SUVA		
	Eurther infor			nal Safety and		
		Further information: National Institute for Occupational Safety and Health, Harm to the unborn child is not to be expected when the				
		OEL-value is respected				
sodium hydroxide	1310-73-2	TWA (inhalable dust)	2 mg/m3	CH SUVA		
		Further information: National Institute for Occupational Safety and				
	Eurther infor	mation: National Insti	tute for Occupatio	nal Safety and		
	Health, Occu	pational Safety and I	Health Administrat	tion, Harm to		
	Health, Occu the unborn c		Health Administrat	tion, Harm to		
	Health, Occu	pational Safety and I hild is not to be expe	Health Administrat cted when the OE	tion, Harm to L-value is re-		
	Health, Occu the unborn c	pational Safety and I hild is not to be expe	Health Administrat	tion, Harm to		
thiram (ISO)	Health, Occu the unborn c spected	pational Safety and I hild is not to be expe STEL (inhalable dust)	Health Administraticted when the OE	tion, Harm to L-value is re-		
thiram (ISO)	Health, Occu the unborn c	pational Safety and I hild is not to be expe	Health Administrat cted when the OE	tion, Harm to L-value is re-		
thiram (ISO)	Health, Occu the unborn c spected 137-26-8	pational Safety and I hild is not to be expe STEL (inhalable dust) TWA (inhalable dust)	Health Administrat cted when the OE 2 mg/m3 1 mg/m3	tion, Harm to L-value is re- CH SUVA CH SUVA		
thiram (ISO)	Health, Occu the unborn c spected 137-26-8 Further inform	pational Safety and I hild is not to be expe STEL (inhalable dust) TWA (inhalable dust) mation: Sensitizers; S	Health Administrat cted when the OE 2 mg/m3 1 mg/m3 Substances marke	tion, Harm to L-value is re- CH SUVA CH SUVA ed with an S		
thiram (ISO)	Health, Occu the unborn c spected 137-26-8 Further inform can lead to v	pational Safety and I hild is not to be expe STEL (inhalable dust) TWA (inhalable dust) mation: Sensitizers; S ery strong allergic re	Health Administrat cted when the OE 2 mg/m3 1 mg/m3 Substances marke actions., National	tion, Harm to L-value is re- CH SUVA CH SUVA d with an S Institute for		
thiram (ISO)	Health, Occu the unborn c spected 137-26-8 Further inform can lead to v Occupationa	pational Safety and I hild is not to be expe STEL (inhalable dust) TWA (inhalable dust) mation: Sensitizers; S	Health Administrat cted when the OE 2 mg/m3 1 mg/m3 Substances marke actions., National Harm to the unbor	tion, Harm to L-value is re- CH SUVA CH SUVA cH SUVA d with an S Institute for		

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
manganese dioxide	1313-13-9	Manganese: 20 µg/l (Blood)	Immediately after exposure or after working hours, In case of long-term expo- sure: after more than one shift	CH BAT

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: -		Version 1.0	Print Date 07.10.2024
		Eye wash bottle with pure water	
Hand protection	:	Chemical-resistant, impervious gloves complyin proved standard must be worn at all times when chemical products. Reference number EN 374. facturer specifications.	handling
		Suitable for short time use or protection against Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	splashes:
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN long-sleeved working clothing, long trousers). R and protective boots are additionaly recommend and stirring work.	ubber aprons
Respiratory protection	:	In case of inadequate ventilation wear respirator Respirator selection must be based on known o exposure levels, the hazards of the product and ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 pc Ensure adequate ventilation. This can be achieve exhaust extraction or by general ventilation. (EN ods for determining inhalation exposure). This a ticular to the mixing / stirring area. In case this is to keep the concentrations under the occupation limits then respiration protection measures must Ensure adequate ventilation, especially in confir	ppm ved by local N 689 - Meth- pplies in par- s not sufficent nal exposure t be used.

Environmental exposure controls

General advice	: Do not flush into surface water or sanitary sewer system.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour	:	liquid paste brown
Odour	:	characteristic
Melting point/ range / Freez- ing point	:	No data available
OUNTRY CH 00000720191		

Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: -		Version 1.0	Print Date 07.10.2024
Boiling point/boiling range	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	exp	blosive limits	
Upper explosion limit / Upper flammability limit	-		
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 100 °C Method: closed cup	
Auto-ignition temperature	:	No data available	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity			
Viscosity, dynamic	:	70.000 mPa.s	
Viscosity, kinematic	:	No data available	
Solubility(ies)			
Water solubility	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	•	0,001 hPa	
Density	:	ca. 1,9 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	



Version 1.0

Print Date 07.10.2024

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

	Hazardous reactions	: Stable under recommended storage conditions
--	---------------------	---

10.4 Conditions to avoid

Conditions to avoid	:	No data available
---------------------	---	-------------------

10.5 Incompatible materials

Materials to avoid	:	No data available
--------------------	---	-------------------

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed or if inhaled.

Components:

oxydipropyl dibenzoate:

Acute oral toxicity : LD50 Oral (Rat): 3.914 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.



Version 1.0

Print Date 07.10.2024

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

oxydipropyl dibenzoate:

Toxicity to daphnia and other	:	EC50: 19,3 mg/l
aquatic invertebrates (Chron-		Exposure time: 48 h
ic toxicity)		Species: Daphnia (water flea)

thiram (ISO):

M-Factor (Acute aquatic tox- : 10 icity)

Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: - Version 1.0

Print Date 07.10.2024

M-Factor (Chronic aquatic : 10 toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components consid- ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---

12.7 Other adverse effects

|--|

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues.
	This material and its container must be disposed of in a safe way.
	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: -	Version 1.0	Print Date 07.10.2024	
	protection and waste disposal legislatior local authority requirements. Avoid dispersal of spilled material and ru soil, waterways, drains and sewers.		
Waste code Switzerland VeVA/LVA	: 08 04 09 [S] waste adhesives and seala solvents or other dangerous substances		

SECTION 14: Transport information

14.1 UN number or ID number			
ADR	:	UN 3082	
IMDG	:	UN 3082	
ΙΑΤΑ	:	UN 3082	
14.2 UN proper shipping name			
ADR	:	ENVIRONMENTALL` N.O.S. (thiram (ISO), 1,3-dip	Y HAZARDOUS SUBSTANCE, LIQUID, henylguanidine)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (thiram (ISO), 1,3-diphenylguanidine)	
ΙΑΤΑ	:	Environmentally hazardous substance, liquid, n.o.s. (thiram (ISO), 1,3-diphenyIguanidine)	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	9	
IMDG	:	9	
ΙΑΤΑ	:	9	
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	: : : : : : : : : : : : : : : : : : : :	III M6 90 9 (-)	
IMDG Packing group Labels EmS Code	:	III 9 F-A, S-F	
IATA (Cargo)			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: -		Version 1.0	Print Date 07.10.2024	
Packing instruction (cargo aircraft)	:	964		
Packing instruction (LQ)	:	Y964		
Packing group	:	III		
Labels	:	Miscellaneous		
IATA (Passenger)				
Packing instruction (passen- ger aircraft)	:	964		
Packing instruction (LQ)	:	Y964		
Packing group	:	III		
Labels	:	Miscellaneous		
14.5 Environmental hazards				
ADR				
Environmentally hazardous	:	yes		
IMDG				
Marine pollutant	:	yes		
IATA (Passenger) Environmentally hazardous	:	yes		
IATA (Cargo) Environmentally hazardous	:	yes		

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: -	Version 1	0.1	Print Date 07.10.20	24
			Number on list 75:	
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).	
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable	
Regulation (EC) on substances th layer	nat deplete the ozone	:	Not applicable	
Regulation (EU) 2019/1021 on pe tants (recast)	ersistent organic pollu-	:	Not applicable	
PIC Ordinance, ChemPICO (814.	82)	:	Not applicable	
Ordinance on Protection against I Threshold quantity according to N nance (MAO 814.012)		:	20.000 kg	
Chemical Risk Reduction Ordinance : Conditions of restriction for the following annexes should be considered:				
Annex 1.11 Dangerous liquid substances Waters Protection Ordinance (WPO 814.201) Water pollution class : highly hazardous to water Classification according to AwSV, Annex 1 (5.2)				
Volatile organic compounds :	(VOCV)		for volatile organic compounds nds (VOC) content: <= 3% w/w	
	emissions (integrated	poll	24 November 2010 on industrial lution prevention and control) nds (VOC) content: < 0,01% w/w	

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: - Version 1.0

Print Date 07.10.2024

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements H290 May be corrosive to metals. H302 Harmful if swallowed. : Causes severe skin burns and eye damage. H314 : H315 Causes skin irritation. : H317 May cause an allergic skin reaction. H318 Causes serious eye damage. Causes serious eye irritation. H319 Harmful if inhaled. H332 H335 May cause respiratory irritation. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated H373 exposure if inhaled. Very toxic to aquatic life. H400 : Very toxic to aquatic life with long lasting effects. H410 Toxic to aquatic life with long lasting effects. H411 Harmful to aquatic life with long lasting effects. H412 Full text of other abbreviations Acute Tox. Acute toxicity Aquatic Acute Short-term (acute) aquatic hazard : Aquatic Chronic Long-term (chronic) aquatic hazard : Serious eye damage Eye Dam. 2 Eve Irrit. Eve irritation Met. Corr. Corrosive to metals Reproductive toxicity Repr. : Skin Corr. Skin corrosion : Skin irritation Skin Irrit. : Skin Sens. 2 Skin sensitisation STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure : Europe. Commission Directive 2017/164/EU establishing a 2017/164/EU : fourth list of indicative occupational exposure limit values Switzerland. List of BAT-values CH BAT : CH SUVA Switzerland. Limit values at the work place 2017/164/EU / TWA Limit Value - eight hours Time Weighted Average CH SUVA / TWA 2 Short Term Exposure Limit CH SUVA / STEL European Agreement concerning the International Carriage of ADR Dangerous Goods by Road CAS **Chemical Abstracts Service** DNEL Derived no-effect level EC50 Half maximal effective concentration

Sikaflex[®] CR 170 Part B



Revision Date: 23.09.2024 Date of last issue: - Version 1.0

Print Date 07.10.2024

GHS IATA	Globally Harmonized SystemInternational Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at
LDOU	once, which causes the death of 50% (one half) of a group of test animals)
LC50	 Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from
	Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H302	Calculation method
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CH / EN