Revision Date: 16.11.2023 Date of last issue: 24.05.2023 Version 7.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaTherm[®]-4800 OT

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Schweiz AG
		Tüffenwies 16
		8048 Zürich
Telephone	:	+41 58 436 40 40
Telefax	:	-
E-mail address of person	:	EHS@ch.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich +41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

	Classification (REGULATION (EC) No 127 Flammable liquids, Category 2	2/2008) H225: Highly flammable liquid and vapour.
	Eye irritation, Category 2	H319: Causes serious eye irritation.
	Specific target organ toxicity - single ex- posure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
2.2	Label elements	
	Labelling (REGULATION (EC) No 1272/20	08)

Hazard pictograms	:		
Signal word	:	Danger	
Hazard statements	:	H225	Highly flammable liquid and vapour.

SikaTherm®-4800 OT

Print Date 16.11.2023

Revision Date: 16.11.2023 Date of last issue: 24.05.2023	N	/ersion 7.0	Print Date 16.11.20
	H319 H336	Causes serious eye irritation May cause drowsiness or dia	
Supplemental Hazard Statements	: EUH066	Repeated exposure may cau or cracking.	use skin dryness
Precautionary statements	: Prevention:		
	P210	Keep away from heat, hot su open flames and other ignition smoking.	•
	P233	Keep container tightly closed	d.
	P261	Avoid breathing mist or vapo	
	P280	Wear protective gloves/ prot eye protection/ face protection	
	Response:		
	P303 + P361 +	P353 IF ON SKIN (or hair): ately all contaminated clothin with water.	
	P370 + P378	In case of fire: Use dry sand alcohol-resistant foam to ext	-

Hazardous components which must be listed on the label:

acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 16.11.2023 Date of last issue: 24.05.2023



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
acetone	67-64-1	Flam. Liq. 2; H225	>= 60 - < 80
	200-662-2	Eye Irrit. 2; H319	
	01-2119471330-49-	STOT SE 3; H336	
	XXXX	(Central nervous	
		system)	
		EUH066	
ethyl acetate	141-78-6	Flam. Liq. 2; H225	>= 2,5 - < 5
	205-500-4	Eye Irrit. 2; H319	
	01-2119475103-46-	STOT SE 3; H336	
	XXXX	(Central nervous	
		system)	
		EUH066	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures General advice Move out of dangerous area. : Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled : Move to fresh air. Consult a physician after significant exposure. In case of skin contact 2 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. : Immediately flush eye(s) with plenty of water. In case of eye contact Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. If swallowed Do not induce vomiting without medical advice. : Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 4.2 Most important symptoms and effects, both acute and delayed Symptoms : Excessive lachrymation Erythema

Sika ®
Print Date 16.11.2023

Revision Date: 16.11.2023 Date of last issue: 24.05.2023	Version 7.0	Print Date 16
	Loss of balance Vertigo See Section 11 for more detailed inform and symptoms.	nation on health effects
Risks	: irritant effects	
	Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dr	yness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically.
-----------	---	------------------------

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water
5.2 Special hazards arising from	the	e substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers.
SECTION 6: Accidental releas	se r	measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions	
Environmental precautions	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.

Revision Date: 16.11.2023 Date of last issue: 24.05.2023 Version 7.0



6.3 Methods and material for containment and cleaning up

Methods for cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage,	inc	luding any incompatibilities
Requirements for storage areas and containers	:	Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3 Specific end use(s)		
Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

Print Date 16.11.2023

Revision Date: 16.11.2023 Date of last issue: 24.05.2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC		
	Further inform	Further information: Indicative				
		TWA	500 ppm 1.200 mg/m3	CH SUVA		
	Further inforr Health	nation: National Insti	tute for Occupatio	nal Safety and		
		STEL	1.000 ppm 2.400 mg/m3	CH SUVA		
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m3	2017/164/EU		
	Further inforr	nation: Indicative				
		TWA	200 ppm 734 mg/m3	2017/164/EU		
		TWA	200 ppm 730 mg/m3	CH SUVA		
	Health, Institutive vention des a Harm to the u	Further information: National Institute for Occupational Safety and Health, Institut National de Recherche et de Sécurité pour la pré- vention des accidents du travail et des maladies professionnelles, Harm to the unborn child is not to be expected when the OEL- value is respected				
		STEL	400 ppm 1.460 mg/m3	CH SUVA		

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Biological occupational exposure limits

Substance name	CAS-No.	Control parame- ters	Sampling time	Basis
acetone	67-64-1	Acetone: 50 mg/l (Urine)	Immediately after exposure or after working hours	CH BAT
		Acetone: 1.38 Millimoles per liter (Urine)	Immediately after exposure or after working hours	CH BAT

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water

SikaTherm®-4800 OT

Revision Date: 16.11.2023 Date of last issue: 24.05.2023



01 last issue. 24.05.2023					
Hand protection :	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.				
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.				
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.				
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.				
Environmental exposure controls					
General advice :	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.				

Version 7.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour	:	liquid various
Odour	:	solvent-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available

SikaTherm[®]-4800 OT



Revision Date: 16.11.2023 Date of last issue: 24.05.2023		Version 7.0	Print Date 16.11.2023
Flammability (solid, gas)	:	No data available	
Upper/lower flammability or	-		
Upper explosion limit / Upper flammability limit	:	13 %(V)	
Lower explosion limit / Lower flammability limit	:	2,5 %(V)	
Flash point	:	-18 °C Method: closed cup	
Auto-ignition temperature	:	427 °C	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity			
Viscosity, dynamic	:	ca. 1.000 mPa.s (20 °C)	
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	2,3298 hPa	
Density	:	ca. 0,9 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	

9.2 Other information

No data available

Revision Date: 16.11.2023 Date of last issue: 24.05.2023

Version 7.0



SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

acetone: : LD50 Oral (Rat): 5.800 mg/kg Acute oral toxicity LC50 (Rat): 76 mg/l Acute inhalation toxicity : Exposure time: 4 h Test atmosphere: vapour : LD50 Dermal (Rabbit): 20.000 mg/kg Acute dermal toxicity ethyl acetate: Acute oral toxicity LD50 Oral (Rat): > 5.000 mg/kg LC50 (Rat): ca. 1.600 mg/l Acute inhalation toxicity 1 Exposure time: 4 h Test atmosphere: vapour Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

SikaTherm[®]-4800 OT

Revision Date: 16.11.2023 Date of last issue: 24.05.2023 Version 7.0



Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

acetone:

Toxicity to algae/aquatic:ErC50 (Pseudokirchneriella subcapitata (green algae)): > 530plantsmg/l

Revision Date: 16.11.2023 Date of last issue: 24.05.2023 Version 7.0



Exposure time: 96 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

	Product:		
	Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.	7 Other adverse effects		
	Product:		
	Additional ecological infor- mation	:	There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product
The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SikaTherm®-4800 OT

Jika ®
Print Date 16.11.2023

Revision Date: 16.11.2023 Date of last issue: 24.05.2023	Version 7.0	Print Date 16.11.2023
Waste code Switzerland VeVA/LVA	: 08 04 09 [S] waste adhesives and s solvents or other dangerous substa	
Contaminated packaging	: 15 01 10 [S] packaging containing r ed by dangerous substances	residues of or contaminat-

SECTION 14: Transport information

	14.1	UN	number	or ID	number
--	------	----	--------	-------	--------

	ADR	:	UN 1133	
	IMDG	:	UN 1133	
	ΙΑΤΑ	:	UN 1133	
14.2	UN proper shipping name			
	ADR	:	ADHESIVES	
	IMDG	:	ADHESIVES	
	ΙΑΤΑ	:	Adhesives	
14.3	Transport hazard class(es)			
			Class	Subsidiary risks
	ADR	:	3	
	IMDG	:	3	
	ΙΑΤΑ	:	3	
14.4	Packing group			
	ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code		II F1 33 3 (D/E)	
	IMDG Packing group Labels EmS Code	:	ll 3 F-E, S-D	
	IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	364 Y341 II Flammable Liquids	
	IATA (Passenger) Packing instruction (passen-	:	353	

SikaTherm®-4800 OT

Revision Date: 16.11.2023 Date of last issue: 24.05.2023 Version 7.0



ger aircraft) Packing instruction (LQ) Packing group Labels	:	Y341 II Flammable Liquids
14.5 Environmental hazards		

ADR

IATA (Cargo)		
IATA (Passenger) Environmentally hazardous	:	no
IMDG Marine pollutant	:	no
Environmentally hazardous	:	no

.. .

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legis	lation	specific for the substance or mixture
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	:	Not applicable

REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	trea /or gula	m suppliers, and/or tion, and/or
REACH - Restrictions on the m the market and use of certain of mixtures and articles (Annex X	langerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
REACH - Candidate List of Sul Concern for Authorisation (Arti		:	None of the components are listed (=> 0.1 %).
REACH - List of substances su (Annex XIV)	bject to authorisation	:	Not applicable
Regulation (EC) No 1005/2009	on substances that de-	:	Not applicable

SikaTherm[®]-4800 OT

Print Date 16.11.2023

Revision Date: 16.11.2023 Date of last issue: 24.05.2023

plete the ozone layer

Version 7.0

Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
PIC Ordinance, ChemPICO (814.82)	:	Not applicable
Chemical Risk Reduction Ordinance (ORRChem, SR 814.81)	:	See respective Annex to the Chemi- cal Risk Reduction Ordinance (ORRChem, 814.81) for Conditions of Restriction.
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors		
This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappear- ances and thefts should be reported to the relevant na- tional contact point.	:	acetone (ANNEX II)
Seveso III: Directive 2012/18/EU of the European Parliam jor-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS		and of the Council on the control of ma-

Volatile organic compounds	:	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 82,28% w/w
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 82,28% w/w

Other regulations:

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

	Highly flammable liquid and vapour.
H319 :	Causes serious eye irritation.
H336 :	May cause drowsiness or dizziness.

Full text of other abbreviations

Revision Date: 16.11.2023 Date of last issue: 24.05.2023 Print Date 16.11.2023

Version 7.0

Eye Irrit. : Flam. Liq. : STOT SE : 2000/39/EC :	Eye irritation Flammable liquids Specific target organ toxicity - single exposure Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU :	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
CH BAT : CH SUVA : 2000/39/EC / TWA : 2017/164/EU / STEL : 2017/164/EU / TWA : CH SUVA / TWA : CH SUVA / STEL : ADR :	Switzerland. List of BAT-values Switzerland. Limit values at the work place Limit Value - eight hours Short term exposure limit Limit Value - eight hours Time Weighted Average Short Term Exposure Limit European Agreement concerning the International Carriage of
CAS :	Dangerous Goods by Road Chemical Abstracts Service
DNEL : EC50 :	Derived no-effect level Half maximal effective concentration
GHS : IATA :	Globally Harmonized System International Air Transport Association
IMDG : LD50 :	International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 :	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL :	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL :	Occupational Exposure Limit
PBT : PNEC :	Persistent, bioaccumulative and toxic Predicted no effect concentration
REACH :	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC :	Substances of Very High Concern
vPvB :	Very persistent and very bioaccumulative
Further information	
Classification of the mixture:	Classification procedure:

Flam. Liq. 2	H225	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SikaTherm[®]-4800 OT

Revision Date: 16.11.2023 Date of last issue: 24.05.2023 Version 7.0



Changes as compared to previous version !

CH / EN