according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom[®]-531 Multipositon



Date of last issue: 21.02.2024

Revision Date: 24.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Sika Boom®-531 Multipositon

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane foam

1.3 Details of the supplier of the safety data sheet

Company name of supplier Sika Schweiz AG

Tüffenwies 16 8048 Zürich

Telephone +41 58 436 40 40

Telefax

E-mail address of person responsible for the SDS

EHS@ch.sika.com

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich

+41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Specific target organ toxicity - single ex-

posure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated H373: May cause damage to organs through proexposure, Category 2

longed or repeated exposure if inhaled.



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sika Boom®-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word	:	Danger
-------------	---	--------

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breath-

ing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged

or repeated exposure if inhaled.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

Prevention:

P202 Do not handle until all safety precautions

have been read and understood.

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other igni-

tion source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust or mist.

P271 Use only outdoors or in a well-ventilated ar-

ea.

P280 Wear protective gloves/ protective clothing/

eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to tem-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sika Boom®-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

peratures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

Reaction products of phosphoryl trichloride and methyloxirane Diphenylmethanediisocyanate, isomeres and homologues

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sika Boom®-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Reaction products of phosphoryl trichloride and methyloxirane	1244733-77-4 237-158-7 01-2119486772-26- XXXX	Acute Tox. 4; H302 Carc. 2; H351 Aquatic Chronic 3; H412 Acute toxicity estimate Acute oral toxicity: 630 mg/kg	>= 10 - < 20
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % specific concentration limit Resp. Sens. 1; H334 >= 0,1 % specific concentration limit Skin Irrit. 2; H315 >= 5 % specific concentration limit Skin Irrit. 2; H315 >= 5 %	>= 10 - < 20

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®]

Sika Boom®-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

Substances with a workplace	e exposure limit :		
dimethyl ether	115-10-6 204-065-8 01-2119472128-37- XXXX	Flam. Gas 1A; H220	>= 10 - < 20
isobutane	75-28-5 200-857-2 01-2119485395-27- XXXX	Flam. Gas 1A; H220	>= 5 - < 10
propane	74-98-6 200-827-9 01-2119486944-21- XXXX	Flam. Gas 1A; H220	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Erythema Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom[®]-531 Multipositon



Date of last issue: 21.02.2024

Revision Date: 24.10.2024

Risks irritant effects

sensitising effects

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Water spray jet

> Dry powder Foam

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod: :

ucts

Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx)

Hydrogen cyanide (hydrocyanic acid)

Bromine compounds Chlorine compounds

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

Deny access to unprotected persons.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-531 Multipositon



Date of last issue: 21.02.2024

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Allow to solidify, use mechanical handling equipment.

Ventilate the area.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent

material. Take precautionary measures against electrostatic

discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Jika

Sika Boom®-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

precautions. Store in accordance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Cleaning with aprotic polar solvents must be avoided.

Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m3 (NCO)	CH SUVA
_	Further information: Sensitizers; Substances marked with an S			d with an S
	can lead to very strong allergic reactions., Health and Safety Executive (Occupational Medicine and Hygiene Laboratory)			
		STEL	0,02 mg/m3 (NCO)	CH SUVA
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	1.000 ppm 1.910 mg/m3	CH SUVA
isobutane	75-28-5	TWA	800 ppm 1.900 mg/m3	CH SUVA
		STEL	3.200 ppm 7.600 mg/m3	CH SUVA
propane	74-98-6	STEL	4.000 ppm 7.200 mg/m3	CH SUVA
	Further information: National Institute for Occupational Safety and Health			
		TWA	1.000 ppm 1.800 mg/m3	CH SUVA

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika[®]

Sika Boom®-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers).

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol Colour : various

Odour : No data available

Melting point/ range / Freez-

ing point

: No data available

Boiling point/boiling range : No data available

Flammability : Extremely flammable aerosol.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

Sika Boom®-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

Upper/lower flammability or explosive limits

per flammability limit

Upper explosion limit / Up- : No data available

,

Lower explosion limit / Lower flammability limit

No data available

Flash point : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture reacts with water

Viscosity

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 5100 hPa

Density : ca. 1,00 g/cm3 (23 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-531 Multipositon



Date of last issue: 21.02.2024

10.2 Chemical stability

Revision Date: 24.10.2024

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Reaction products of phosphoryl trichloride and methyloxirane:

Acute oral toxicity : LD50 Oral (Rat): > 630 mg/kg

Diphenylmethanediisocyanate, isomeres and homologues:

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-531 Multipositon



Date of last issue: 21.02.2024

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Reaction products of phosphoryl trichloride and methyloxirane:

Toxicity to algae/aquatic plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 82 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 13

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom[®]-531 Multipositon



Date of last issue: 21.02.2024

Toxicity to daphnia and other : NOEC: 32 mg/l aquatic invertebrates (Chron-

ic toxicity)

Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 1.640

mg/l

Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

mation

Additional ecological infor- : There is no data available for this product.

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-531 Multipositon



Date of last issue: 21.02.2024

Revision Date: 24.10.2024

Components:

propane:

20-year global warming potential: 0,072 100-year global warming potential: 0,02 500-year global warming potential: 0,006

Atmospheric lifetime: 0,036 yr Radiative efficiency: 0 Wm2ppb

Further information: Miscellaneous compounds

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Waste code Switzerland

VeVA/LVA

: 16 05 04 [S] gases in pressure containers (including halons)

containing dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950 IMDG : UN 1950 IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

Class Subsidiary risks

ADR : 2 2.1



according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

Sika Boom®-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

IMDG : 2.1 IATA : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

Remarks : Transport according to chapter 3.4 (LQ) possible

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

Remarks : Transport according to chapter 3.4 (LQ) possible

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen: 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom®-531 Multipositon



Date of last issue: 21.02.2024

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 56: Diphenylmethanediisocyanate, isomeres and

homologues

Number on list 74: Diphenylmethanediisocyanate, isomeres and

homologues

Number on list 75:

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) on substances that deplete the ozone

layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

PIC Ordinance, ChemPICO (814.82) : Not applicable

Ordinance on Protection against Major Accidents

Threshold quantity according to Major Accidents Ordi: 50.000 kg

nance (MAO 814.012)

Chemical Risk Reduction Ordinance : Conditions of restriction for the following annexes

(ORRChem, SR 814.81) should be considered:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika ®

Sika Boom®-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

Diphenylmethanediisocyanate, isomeres and homo-

logues: Annex 2.9 Plastics and additives

Waters Protection Ordinance (WPO 814.201)

Water pollution class : obviously hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 20,51% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 20,51% w/w

Other regulations:

75/324/EEC

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.
H302 : Harmful if swallowed.
H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

. Causes serious eye i

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika Boom[®]-531 Multipositon

Revision Date: 24.10.2024 Version 8.0 Print Date 24.10.2024

Date of last issue: 21.02.2024

May cause respiratory irritation. H335 Suspected of causing cancer. H351

May cause damage to organs through prolonged or repeated H373

exposure if inhaled.

Harmful to aquatic life with long lasting effects. H412

Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic Long-term (chronic) aquatic hazard

Carc. Carcinogenicity Eye Irrit. Eve irritation Flam. Gas Flammable gases Resp. Sens. Respiratory sensitisation

Skin Irrit. Skin irritation Skin Sens. Skin sensitisation

STOT RE Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure STOT SE

Europe. Commission Directive 2000/39/EC establishing a first 2000/39/EC

list of indicative occupational exposure limit values

CH SUVA Switzerland. Limit values at the work place

Limit Value - eight hours 2000/39/EC / TWA CH SUVA / TWA Time Weighted Average CH SUVA / STEL Short Term Exposure Limit

ADR European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS Chemical Abstracts Service Derived no-effect level DNEL

Half maximal effective concentration EC50 Globally Harmonized System **GHS**

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG**

Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL Occupational Exposure Limit

PBT Persistent, bioaccumulative and toxic **PNEC** : Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament REACH

> and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC Substances of Very High Concern

vPvB Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Sika Boom®-531 Multipositon

Aerosol 1	H222, H229	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

CH / EN