

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikagard® M 790 (Formerly MSeal M 790) Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Special coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Schweiz AG
Tüffenwies 16
8048 Zürich
Telephone : +41 58 436 40 40
Telefax : -
E-mail address of person : EHS@ch.sika.com
responsible for the SDS

1.4 Emergency telephone number

Tox Info Suisse
CH-8028 Zurich
+41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Long-term (chronic) aquatic hazard, Cat-	H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:

P260 Do not breathe mist or vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P391 Collect spillage.

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>=80
bis(isopropyl)naphthalene	38640-62-9 254-052-6 01-2119565150-48- XXXX	Asp. Tox. 1; H304 Aquatic Chronic 1; H410	>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

Show this safety data sheet to the doctor in attendance.

- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Asthmatic appearance
Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Headache
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure if inhaled.
- irritant effects
sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

- Advice on safe handling : Avoid formation of aerosol.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : Cleaning with aprotic polar solvents must be avoided.
Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	TWA	0,02 mg/m ³ (NCO)	CH SUVA
	Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Health and Safety Executive (Occupational Medicine and Hygiene Laboratory)			
		STEL	0,02 mg/m ³ (NCO)	CH SUVA

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.
Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

- General advice : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : brown

Odour : aliphatic

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C
Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : ca. 2.500 mPa.s (20 °C)

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

Vapour pressure	:	0,01 hPa
Density	:	ca. 1,15 g/cm ³ (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:
No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

Acute oral toxicity : LD50 Oral (Rat): > 10.000 mg/kg

Acute inhalation toxicity : LC50: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9.400 mg/kg

bis(isopropyl)naphthalene:

Acute oral toxicity : LD50 Oral (Rat): > 3.900 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,64 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 4.500 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 3082
IMDG : UN 3082
IATA : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(bis(isopropyl)naphthalene)
IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(bis(isopropyl)naphthalene)
IATA : Environmentally hazardous substance, liquid, n.o.s.
(bis(isopropyl)naphthalene)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 9	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

IMDG : 9

IATA : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M6
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)
Remarks : Transport in accordance with special provision 375

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F
Remarks : Transport in accordance with 2.10.2.7 of the IMDG-Code

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous
Remarks : Transport in accordance with special regulation A 197

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75, 3

Diphenylmethanediisocyanate, isomers and homologues (Number on list 74, 56)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

PIC Ordinance, ChemPICO (814.82) : Not applicable

Chemical Risk Reduction Ordinance (ORRChem, SR 814.81) : See respective Annex to the Chemical Risk Reduction Ordinance (ORRChem, 814.81) for Conditions of Restriction.

Chemical Risk Reduction Ordinance (ORRChem, SR 814.81) : Diphenylmethanediisocyanate, isomers and homologues

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2

ENVIRONMENTAL HAZARDS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: \leq 3% w/w
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: $<$ 0,01% w/w

Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 : May cause respiratory irritation.
H351 : Suspected of causing cancer.
H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

Eye Irrit.	:	Eye irritation
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
CH SUVA	:	Switzerland. Limit values at the work place
CH SUVA / TWA	:	Time Weighted Average
CH SUVA / STEL	:	Short Term Exposure Limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:

Acute Tox. 4	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikagard® M 790 (Formerly MSeal M 790) Part B



Revision Date: 03.05.2024

Version 2.0

Print Date 03.05.2024

Date of last issue: 11.04.2024

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.



Changes as compared to previous version !

CH / EN