according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikalastic® M 861 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealing system

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Schweiz AG

Tüffenwies 16 8048 Zürich

Telephone : +41 58 436 40 40

Telefax :

E-mail address of person responsible for the SDS

EHS@ch.sika.com

1.4 Emergency telephone number

Tox Info Suisse CH-8028 Zurich

+41(0)44 251 51 51 / Speed calling: 145

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours. P273 Avoid release to the environment.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Disposal:

P501 Dispose of contents/container in accordance

with local regulation.

Hazardous components which must be listed on the label:

aliphatic prepolymer (d-polyether based)

Pentamethyl piperidylsebacate

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
aliphatic prepolymer (d-polyether based)	39323-37-0 Not Assigned	Skin Sens. 1; H317	>=80

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute	>= 0,25 - < 0,5	
		aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1		
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % specific concentration limit Skin Sens. 1; H317 >= 0,5 %	>= 0,1 - < 0,25	
		mate Acute inhalation toxicity (dust/mist): 0,031 mg/l		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Revision Date: 27.09.2024 Version 1.0 Print Date 07.10.2024

Date of last issue: -

Consult a physician after significant exposure.

Take off contaminated clothing and shoes immediately. In case of skin contact

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions **Symptoms**

See Section 11 for more detailed information on health effects

and symptoms.

Risks May cause an allergic skin reaction.

sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod- : No hazardous combustion products are known

ucts

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Revision Date: 27.09.2024 Version 1.0 Print Date 07.10.2024

Date of last issue: -

sealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

Recommended storage tem- : > 5 - < 30 °C

perature

7.3 Specific end use(s)

Specific use(s) Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *	
		of exposure)	ters *		
3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,02 mg/m3 (NCO)	CH SUVA	
	Further information: Sensitizers; Substances marked with an S can lead to very strong allergic reactions., Health and Safety Executive (Occupational Medicine and Hygiene Laboratory)				
		STEL	0,02 mg/m3 (NCO)	CH SUVA	

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Safety glasses with side-shields conforming to EN166 Eye/face protection

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

> proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butvl rubber/nitrile rubber gloves (> 0.1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm). breakthrough time >30 min.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Revision Date: 27.09.2024 Version 1.0 Print Date 07.10.2024

Date of last issue: -

Protective clothing (e.g. Safety shoes acc. to EN ISO 20345. Skin and body protection

> long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

In case of inadequate ventilation wear respiratory protection. Respiratory protection

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Colour grey

Odour pungent

Melting point/ range / Freez-

ing point

No data available

No data available Boiling point/boiling range

No data available Flammability (solid, gas)

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit / Lower flammability limit No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

Flash point : > 80 °C

Method: closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 7-9

Concentration: 100 %

Viscosity

Viscosity, dynamic : 160.000 mPa.s (20 °C)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : emulsifiable

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,09 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

Explosives : Not explosive

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

:

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

aliphatic prepolymer (d-polyether based):

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Pentamethyl piperidylsebacate:

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 4.814 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,031 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute toxicity estimate: 0,031 mg/l

Test atmosphere: dust/mist Method: Calculation method

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

aliphatic prepolymer (d-polyether based):

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 100 mg/l

aquatic invertebrates

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

NOEC (Daphnia (water flea)): > 100 mg/l

Toxicity to algae/aquatic

plants

EC50 (algae): > 100 mg/l

Exposure time: 72 h

Pentamethyl piperidylsebacate:

Toxicity to fish : LC50 (Fish): 0,97 mg/l

1

Exposure time: 96 h

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic : 1

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Waste code Switzerland

VeVA/LVA

: 08 05 01 [S] waste isocyanates

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Revision Date: 27.09.2024 Version 1.0 Print Date 07.10.2024

Date of last issue: -

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

: Not applicable

REACH Information: All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

Number on list 52: 1,2-

Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich

Number on list 74: 3isocyanatomethyl-3,5,5trimethylcyclohexyl isocyanate

Number on list 75:

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) on substances that deplete the ozone

layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

PIC Ordinance, ChemPICO (814.82) : Not applicable

Ordinance on Protection against Major Accidents

Threshold quantity according to Major Accidents Ordi: Not applicable

nance (MAO 814.012)

Chemical Risk Reduction Ordinance

(ORRChem, SR 814.81)

: Conditions of restriction for the following annexes

should be considered:

Annex 1.11 Dangerous liquid substances

Waters Protection Ordinance (WPO 814.201)

Water pollution class : obviously hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: <= 3% w/w

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,5% w/w

Other regulations:

Article 13 Maternity ordinance (SR 822.111.52): Expectant and nursing mothers are only permitted to come into contact with this product during the course of their work if, based on a risk assessment carried out in accordance with Article 63 of Ordinance 1 on the Employment Act (ArGV 1) (SR 822.111), the chemicals in question have been found not to cause any specific harm to mothers or children or if such harm can be ruled out by taking appropriate protective measures.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Young people undergoing basic vocational training may only work with this product if the relevant training ordinance makes provision for them to do so with a view to enabling them to achieve their training objectives and if the preconditions for the training plan have been met and the applicable age restrictions have been complied with. Young people who are not completing any basic vocational training are not permitted to work with this product. Employees of either sex who are under 18 years old are classed as young people.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikalastic® M 861 Part B



Date of last issue: -

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H319 : Causes serious eye irritation.

H330 : Fatal if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H361f : Suspected of damaging fertility.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Irrit. : Eye irritation

Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT SE : Specific target organ toxicity - single exposure CH SUVA : Switzerland. Limit values at the work place

CH SUVA / TWA : Time Weighted Average CH SUVA / STEL : Short Term Exposure Limit

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sika®

Sikalastic® M 861 Part B

Date of last issue: -

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method Aquatic Chronic 3 H412 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

CH / EN